

TS 35X15 2M/ST/ZN**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Product image**

Steel DIN rails are the most widespread on the market. Among metal DIN rails, they have the lowest shortcircuit protection, similar to stainless steel.

General ordering data

Version	Rail, TS 35, TS 35 x 15, without slot, Steel, galvanic zinc plated and passivated
Order No.	0236400000
Type	TS 35X15 2M/ST/ZN
GTIN (EAN)	4008190114558
Qty.	2 m

TS 35X15 2M/ST/ZN

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	15 mm	Depth (inches)	0.591 °C
Height	35 mm	Height (inches)	1.378 °C
Width	2,000 mm	Width (inches)	78.74 °C
Net weight	670 g		

Mounting rail

Installation advice		Direct mounting	
Length of the terminal rail	min.		0 mm
	max.		2,000 mm
	nominal		2,000 mm
Material	Steel		
Pre-punched mounting rail	No		
Short circuit strength corresponds to E-Cu wire	50 Nm		
Short-time withstand current according to IEC 60947-7-2	6 V AC/DC ±10 %		
Slit gap			
Slit length			
Slit width			
Standards	In accordance with DIN EN 60715		
Surface finish	galvanic zinc plated and passivated		
Thickness	1.5 mm		

Classifications

ETIM 6.0	EC001285	ETIM 7.0	EC001285
ETIM 8.0	EC001285	ECLASS 9.0	27-40-06-02
ECLASS 9.1	27-40-06-02	ECLASS 10.0	27-40-06-02
ECLASS 11.0	27-40-06-02		

Approvals

ROHS	Conform
------	---------

Downloads

Engineering Data	STEP
Engineering Data	EPLAN, WSCAD, Zuken E3.S
User Documentation	StorageConditionsTerminalBlocks
Catalogues	Catalogues in PDF-format
Brochures	