

MAS DC/DC SELECT**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Product image****Only remaining stock
available****General ordering data**

Version	MICROSERIES, Signal converter/insulator
Order No.	8594810000
Type	MAS DC/DC SELECT
GTIN (EAN)	4032248252442
Qty.	1 pc(s).

MAS DC/DC SELECT

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	97.8 mm	Depth (inches)	3.85 °C
Width	6.1 mm	Width (inches)	0.24 °C
Length	88 mm	Length (inches)	3.465 °C
Net weight	51 g		

Temperatures

Storage temperature	-20 °C...85 °C	Operating temperature	0 °C...55 °C
---------------------	----------------	-----------------------	--------------

Probability of failure

MTTF	440 Jahre
------	-----------

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Input

Input current	0...20 mA, 4...20 mA	Input resistance, current	≤ 5 Ω
Input resistance, voltage	100 kΩ	Input voltage	0...10 V
Number of inputs	1	Voltage drop	< 0.1 V @ I _{IN} = 20 mA (current input)

Output

Cut-off frequency (-3 dB)	> 100 Hz	Load impedance current	≤ 500 Ω
Number of outputs	1	Output current	0...20 mA, 4...20 mA
Output voltage, note	0...10 V	load impedance voltage	≥ 10 kΩ

General data

Current-carrying capacity of cross-connect.	≤ 20 A	Galvanic isolation	3-way isolator
Input/Output	configurable	Power consumption	ca. 0.6 W
Rail	TS 35	Temperature coefficient	≤ 150 ppm/K of final value
Type of connection	Screw connection	Voltage supply	24 V DC ± 15 %

Insulation coordination

EMC standards	DIN EN 61326	Galvanic isolation	3-way isolator
Insulation voltage	500 V _{eff} / 1 s	Insulation voltage input or output/rail	500 V _{eff} / 1 s
Insulation voltage input or output/supply	500 V _{eff} / 1 s	Pollution severity	2
Rated voltage	50 V	Surge voltage category	II

Connection data

Type of connection	Screw connection	Clamping range, rated connection	2.5 Nm
Clamping range, min.	0.5 Nm	Clamping range, max.	2.5 Nm

MAS DC/DC SELECT

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Classifications

ETIM 6.0	EC002653	ETIM 7.0	EC002653
ETIM 8.0	EC002653	ECLASS 9.0	27-21-01-20
ECLASS 9.1	27-21-01-90	ECLASS 10.0	27-21-01-20
ECLASS 11.0	27-21-01-20		

Approvals

Approvals



ROHS	Conform
UL File Number Search	E345958

Downloads

Approval/Certificate/Document of Conformity	Declaration of Conformity
Engineering Data	STEP
Engineering Data	EPLAN, WSCAD
User Documentation	Instruction sheet
Catalogues	Catalogues in PDF-format

MAS DC/DC SELECT

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Drawings

Electric symbol

