

**LIF 1,5F638 R****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Insulated tab-connector sleeves made from PVC  
with copper sleeve**

- Commercially available designs
- Not soldered
- With conical entry funnel

**General ordering data**

|            |                                                                                               |
|------------|-----------------------------------------------------------------------------------------------|
| Version    | cable lug, terminal end, Insulated cable connector, 0.5 mm <sup>2</sup> - 1.5 mm <sup>2</sup> |
| Order No.  | <a href="#">9200540000</a>                                                                    |
| Type       | LIF 1,5F638 R                                                                                 |
| GTIN (EAN) | 40322484 10385                                                                                |
| Qty.       | 100 pc(s).                                                                                    |

## LIF 1,5F638 R

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|            |         |                |          |
|------------|---------|----------------|----------|
| Depth      | 7.7 mm  | Depth (inches) | 0.303 °C |
| Width      | 20.8 mm | Width (inches) | 0.819 °C |
| Net weight | 0.95 g  |                |          |

## Technical data

|                        |                                                               |
|------------------------|---------------------------------------------------------------|
| Description of article | Insulated tab-connector sleeves 1.5 mm <sup>2</sup> / 6.3x0.8 |
|------------------------|---------------------------------------------------------------|

## Connectors

|                               |              |                                  |              |
|-------------------------------|--------------|----------------------------------|--------------|
| Conductor cross-section, max. | 1.5 Nm       | Conductor cross-section, min.    | 0.5 Nm       |
| Dimension                     | 6.3 x 0.8 mm | Dimension (flat blade connector) | 6.3 x 0.8 mm |
| Identification colour         | red          | Insulation                       | Available    |
| Material/plastic              | PVC          | Plastic collar diameter (D)      | 4 mm         |
| Plastic collar length (b)     | 10 mm        | Plug-in density (d3)             | 0.8 mm       |
| Plug-in width (d2)            | 6.3 mm       |                                  |              |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000516    | ETIM 7.0    | EC000516    |
| ETIM 8.0    | EC000516    | ECLASS 9.0  | 27-44-03-92 |
| ECLASS 9.1  | 27-40-02-90 | ECLASS 10.0 | 27-44-03-92 |
| ECLASS 11.0 | 27-44-03-92 |             |             |

## Approvals

Approvals



|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

## Downloads

|                  |                                          |
|------------------|------------------------------------------|
| Engineering Data | <a href="#">EPLAN</a>                    |
| Catalogues       | <a href="#">Catalogues in PDF-format</a> |
| Brochures        |                                          |

### LIF 1,5F638 R

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Drawings

