

LIR 2,5M5 V**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Insulated ring-cable connector made from PVC**

- Commercially available designs
- Not soldered
- With conical entry funnel

General ordering data

Version	cable lug, terminal end, Insulated cable connector, 1.5 mm ² - 2.5 mm ²
Order No.	9200180000
Type	LIR 2,5M5 V
GTIN (EAN)	4032248409808
Qty.	100 pc(s).

LIR 2,5M5 V

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	6.2 mm	Depth (inches)	0.244 °C
Width	23.8 mm	Width (inches)	0.937 °C
Net weight	0.71 g		

Technical data

Description of article	Insulated ring-cable connector 2.5 mm² / M5
------------------------	---

Connectors

Conductor cross-section, max.	2.5 Nm	Conductor cross-section, min.	1.5 Nm
Connection density (S1)	0.8 mm	Connection length (l)	19.05 mm
Dimension	M 5	Dimension (bolt)	M 5
Identification colour	blue	Inside diameter (d1)	5.3 mm
Insulation	Available	Material/plastic	PVC
Outside diameter (d)	8.5 mm	Plastic collar diameter (D)	4.5 mm
Plastic collar length (b)	11.3 mm		

Classifications

ETIM 6.0	EC001059	ETIM 7.0	EC001059
ETIM 8.0	EC001059	ECLASS 9.0	27-40-02-92
ECLASS 9.1	27-40-02-12	ECLASS 10.0	27-40-02-92
ECLASS 11.0	27-40-02-92		

Approvals

Approvals



ROHS	Conform
------	---------

Downloads

Engineering Data	STEP
Engineering Data	EPLAN
Catalogues	Catalogues in PDF-format
Brochures	