

**H1,0/14 GE SV****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

- in multi-pack bag (5 x 100 pcs.)
- Weidmüller colour code
- DIN colour code
- other colour code

**General ordering data**

|            |                                                  |
|------------|--------------------------------------------------|
| Version    | Wire-end ferrule, insulated, 10 mm, 8 mm, yellow |
| Order No.  | <a href="#">9026080000</a>                       |
| Type       | H1,0/14 GE SV                                    |
| GTIN (EAN) | 4008190026158                                    |
| Qty.       | 500 pc(s).                                       |
| Packaging  | Multipack bag                                    |

## H1,0/14 GE SV

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|            |         |
|------------|---------|
| Net weight | 0.108 g |
|------------|---------|

## Technical data

|                        |                                              |         |           |
|------------------------|----------------------------------------------|---------|-----------|
| Description of article | Wire end ferrule with plastic collar, yellow | Version | insulated |
|------------------------|----------------------------------------------|---------|-----------|

## Wire-end ferrules

|                             |         |                                         |            |
|-----------------------------|---------|-----------------------------------------|------------|
| Collar diameter (D2)        | 3 mm    | Colour code                             | Weidmüller |
| Conductor cross-section     | 1 Nm    | Contact surface diameter (D1)           | 1.4 mm     |
| Contact surface length (L2) | 8 mm    | L1 in mm                                | 14 mm      |
| Metal sleeve thickness (S1) | 0.15 mm | Plastic collar thickness (S2)           | 0.25 mm    |
| Stripping length            | 10 mm   | Wire connection cross section AWG, max. | AWG 17     |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000005    | ETIM 7.0    | EC000005    |
| ETIM 8.0    | EC000005    | ECLASS 9.0  | 27-40-02-01 |
| ECLASS 9.1  | 27-40-02-01 | ECLASS 10.0 | 27-40-02-01 |
| ECLASS 11.0 | 27-40-02-01 |             |             |

## Approvals

Approvals



|                       |         |
|-----------------------|---------|
| ROHS                  | Conform |
| UL File Number Search | E499744 |

## Downloads

|                    |                                                                                          |
|--------------------|------------------------------------------------------------------------------------------|
| Engineering Data   | <a href="#">STEP</a>                                                                     |
| Engineering Data   | <a href="#">EPLAN, WSCAD, Zuken E3.S</a>                                                 |
| User Documentation | <a href="#">Technical information - EN</a><br><a href="#">Technical information - DE</a> |
| Catalogues         | <a href="#">Catalogues in PDF-format</a>                                                 |
| Brochures          |                                                                                          |

## H1,0/14 GE SV

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

# Drawings

## Drawing

