

**LIR 2,5M8 V****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Insulated ring-cable connector made from PVC**

- Commercially available designs
- Not soldered
- With conical entry funnel

**General ordering data**

|            |                                                                                               |
|------------|-----------------------------------------------------------------------------------------------|
| Version    | cable lug, terminal end, Insulated cable connector, 1.5 mm <sup>2</sup> - 2.5 mm <sup>2</sup> |
| Order No.  | <a href="#">9200200000</a>                                                                    |
| Type       | LIR 2,5M8 V                                                                                   |
| GTIN (EAN) | 4032248410026                                                                                 |
| Qty.       | 100 pc(s).                                                                                    |

## LIR 2,5M8 V

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|            |         |                |          |
|------------|---------|----------------|----------|
| Depth      | 6.2 mm  | Depth (inches) | 0.244 °C |
| Width      | 29.3 mm | Width (inches) | 1.154 °C |
| Net weight | 1.002 g |                |          |

## Technical data

|                        |                                                         |
|------------------------|---------------------------------------------------------|
| Description of article | Insulated ring-cable connector 2.5 mm <sup>2</sup> / M8 |
|------------------------|---------------------------------------------------------|

## Connectors

|                               |        |                               |           |
|-------------------------------|--------|-------------------------------|-----------|
| Conductor cross-section, max. | 2.5 Nm | Conductor cross-section, min. | 1.5 Nm    |
| Connection density (S1)       | 0.8 mm | Dimension                     | M 8       |
| Dimension (bolt)              | M 8    | Identification colour         | blue      |
| Inside diameter (d1)          | 8.4 mm | Insulation                    | Available |
| Material/plastic              | PVC    | Outside diameter (d)          | 14 mm     |
| Plastic collar diameter (D)   | 4.5 mm | Plastic collar length (b)     | 11.3 mm   |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC001059    | ETIM 7.0    | EC001059    |
| ETIM 8.0    | EC001059    | ECLASS 9.0  | 27-40-02-92 |
| ECLASS 9.1  | 27-40-02-12 | ECLASS 10.0 | 27-40-02-92 |
| ECLASS 11.0 | 27-40-02-92 |             |             |

## Approvals

Approvals



ROHS

Conform

## Downloads

|                  |                                          |
|------------------|------------------------------------------|
| Engineering Data | <a href="#">EPLAN</a>                    |
| Catalogues       | <a href="#">Catalogues in PDF-format</a> |
| Brochures        |                                          |