

**A4C 4****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Product image****Spring connection with PUSH IN Technology**

The innovative PUSH IN technology reduces the amount of time you spend on wiring to a minimum. Direct insertion guarantees high conductor pull-out forces and simple handling for all conductor types.

**General ordering data**

|            |                                                                             |
|------------|-----------------------------------------------------------------------------|
| Version    | Feed-through terminal, PUSH IN, 4 mm <sup>2</sup> , 800 V, 32 A, dark beige |
| Order No.  | <a href="#">2051500000</a>                                                  |
| Type       | A4C 4                                                                       |
| GTIN (EAN) | 4050118411621                                                               |
| Qty.       | 50 pc(s).                                                                   |

## A4C 4

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|                          |          |                |          |
|--------------------------|----------|----------------|----------|
| Depth                    | 39.5 mm  | Depth (inches) | 1.555 °C |
| Depth including DIN rail | 40.5 mm  | Height         | 87.5 mm  |
| Height (inches)          | 3.445 °C | Width          | 6.1 mm   |
| Width (inches)           | 0.24 °C  | Net weight     | 15.06 g  |

## Temperatures

|                                  |                |                                  |        |
|----------------------------------|----------------|----------------------------------|--------|
| Storage temperature              | -25 °C...55 °C | Continuous operating temp., min. | -60 °C |
| Continuous operating temp., max. | 130 °C         |                                  |        |

## Material data

|                                |        |                           |            |
|--------------------------------|--------|---------------------------|------------|
| Material                       | Wemid  | Colour                    | dark beige |
| Colour of operational elements | orange | UL 94 flammability rating | V-0        |

## Rating data IECEx/ATEX

|                                |                   |                                 |                   |
|--------------------------------|-------------------|---------------------------------|-------------------|
| Certificate No. (ATEX)         | TUEV16ATEX7909U   | Certificate No. (IECEX)         | IECEXTUR16.0036U  |
| Max. voltage (ATEX)            | 550 V             | Current (ATEX)                  | 30 A              |
| Wire cross section max. (ATEX) | 4 mm <sup>2</sup> | Max. voltage (IECEX)            | 550 V             |
| Current (IECEX)                | 30 A              | Wire cross section max. (IECEX) | 4 mm <sup>2</sup> |
| Marking EN 60079-7             | Ex eb II C Gb     | Ex 2014/34/EU label             | II 2 G D          |

## System specifications

|                               |       |                                     |    |
|-------------------------------|-------|-------------------------------------|----|
| End cover plate required      | Yes   | Number of potentials                | 1  |
| Number of levels              | 1     | Number of clamping points per level | 4  |
| Number of potentials per tier | 1     | PE connection                       | No |
| Rail                          | TS 35 | N-function                          | No |
| PE function                   | No    | PEN function                        | No |

## Additional technical data

|                     |       |                   |         |
|---------------------|-------|-------------------|---------|
| Installation advice | Rail  | Open sides        | right   |
| Snap-on             | No    | Type of fixing    | Snap-on |
| Type of mounting    | TS 35 | With snap-in pegs | No      |

## CSA rating data

|                               |                 |                               |        |
|-------------------------------|-----------------|-------------------------------|--------|
| Certificate No. (CSA)         | 200039-70089609 | Current size B (CSA)          | 30 A   |
| Current size C (CSA)          | 30 A            | Current size D (CSA)          | 5 A    |
| Voltage size B (CSA)          | 600 V           | Voltage size C (CSA)          | 600 V  |
| Voltage size D (CSA)          | 600 V           | Wire cross section max. (CSA) | 10 AWG |
| Wire cross section min. (CSA) | 26 AWG          |                               |        |

## Conductors for clamping (rated connection)

|                                          |              |
|------------------------------------------|--------------|
| Blade size                               | 0.6 x 3.5 mm |
| Clamping range, max.                     | 4 Nm         |
| Clamping range, min.                     | 0.14 Nm      |
| Connection cross-section, stranded, max. | 4 Nm         |
| Connection cross-section, stranded, min. | 0.5 Nm       |
| Connection direction                     | top          |
| Gauge to IEC 60947-1                     | A4           |

Creation date July 23, 2021 3:16:59 PM CEST

## A4C 4

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Technical data

|                                                                                         |                                        |             |        |
|-----------------------------------------------------------------------------------------|----------------------------------------|-------------|--------|
| Number of connections                                                                   | 4                                      |             |        |
| Stripping length                                                                        | 12 mm                                  |             |        |
| Tube length for AEH with plastic collar<br>DIN 46228/4                                  | Cross-section for conductor connection | min.        | 0.5 Nm |
|                                                                                         |                                        | max.        | 1 Nm   |
|                                                                                         | Tube length                            | max.        | 12 mm  |
|                                                                                         |                                        | min.        | 6 mm   |
|                                                                                         | Cross-section for conductor connection | min.        | 1.5 Nm |
|                                                                                         |                                        | max.        | 2.5 Nm |
|                                                                                         | Tube length                            | max.        | 12 mm  |
|                                                                                         |                                        | min.        | 8 mm   |
|                                                                                         | Cross-section for conductor connection | nominal     | 4 Nm   |
|                                                                                         |                                        | Tube length | max.   |
|                                                                                         | min.                                   |             | 10 mm  |
| Tube length for AEH without plastic collar<br>DIN 46228/1                               | Cross-section for conductor connection | min.        | 0.5 Nm |
|                                                                                         |                                        | max.        | 1 Nm   |
|                                                                                         | Tube length                            | max.        | 10 mm  |
|                                                                                         |                                        | min.        | 6 mm   |
|                                                                                         | Cross-section for conductor connection | min.        | 1.5 Nm |
|                                                                                         |                                        | max.        | 2.5 Nm |
|                                                                                         | Tube length                            | max.        | 12 mm  |
|                                                                                         |                                        | min.        | 7 mm   |
|                                                                                         | Cross-section for conductor connection | nominal     | 4 Nm   |
|                                                                                         |                                        | Tube length | max.   |
|                                                                                         | min.                                   |             | 9 mm   |
| Tube length for twin wire-end ferrule                                                   | Tube length                            | max.        | 12 mm  |
|                                                                                         |                                        | min.        | 8 mm   |
|                                                                                         | Cross-section for conductor connection | min.        | 0.5 Nm |
|                                                                                         |                                        | max.        | 1.5 Nm |
| Twin wire-end ferrules, max.                                                            | 1.5 Nm                                 |             |        |
| Twin wire-end ferrules, min.                                                            | 0.5 Nm                                 |             |        |
| Type of connection                                                                      | PUSH IN                                |             |        |
| Wire connection cross section AWG, max.                                                 | AWG 12                                 |             |        |
| Wire connection cross section AWG, min.                                                 | AWG 26                                 |             |        |
| Wire connection cross section, finely stranded, max.                                    | 4 Nm                                   |             |        |
| Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, max. | 4 Nm                                   |             |        |
| Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, min. | 0.5 Nm                                 |             |        |
| Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, max. | 4 Nm                                   |             |        |
| Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, min. | 0.5 Nm                                 |             |        |
| Wire connection cross-section, solid core, max.                                         | 4 Nm                                   |             |        |
| Wire connection cross-section, solid core, min.                                         | 0.5 Nm                                 |             |        |

## A4C 4

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## General

|                                         |               |                                         |        |
|-----------------------------------------|---------------|-----------------------------------------|--------|
| Installation advice                     | Rail          | Rail                                    | TS 35  |
| Standards                               | IEC 60947-7-1 | Wire connection cross section AWG, max. | AWG 12 |
| Wire connection cross section AWG, min. | AWG 26        |                                         |        |

## Rating data

|                                 |               |                                              |        |
|---------------------------------|---------------|----------------------------------------------|--------|
| Rated cross-section             | 4 Nm          | Rated voltage                                | 800 V  |
| Rated current                   | 32 A          | Current at maximum wires                     | 32 A   |
| Standards                       | IEC 60947-7-1 | Volume resistance according to IEC 60947-7-x | 1 °C   |
| Rated impulse withstand voltage | 8 kV          | Power loss in accordance with IEC 60947-7-x  | 1.02 W |
| Pollution severity              | 3             | Surge voltage category                       | III    |

## UL rating data

|                                            |        |                                            |        |
|--------------------------------------------|--------|--------------------------------------------|--------|
| Certificate No. (cURus)                    | E60693 | Conductor size Factory wiring max. (cURus) | 10 AWG |
| Conductor size Factory wiring min. (cURus) | 28 AWG | Conductor size Field wiring max. (cURus)   | 10 AWG |
| Conductor size Field wiring min. (cURus)   | 28 AWG | Current size B (cURus)                     | 30 A   |
| Current size C (cURus)                     | 30 A   | Current size D (cURus)                     | 5 A    |
| Voltage size B (cURus)                     | 600 V  | Voltage size C (cURus)                     | 600 V  |
| Voltage size D (cURus)                     | 600 V  |                                            |        |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000897    | ETIM 7.0    | EC000897    |
| ETIM 8.0    | EC000897    | ECLASS 9.0  | 27-14-11-20 |
| ECLASS 9.1  | 27-14-11-20 | ECLASS 10.0 | 27-14-11-20 |
| ECLASS 11.0 | 27-14-11-20 |             |             |

## Approvals

Approvals



ROHS Conform

UL File Number Search E60693

## A4C 4

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Technical data

### Downloads

|                                             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|---------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Approval/Certificate/Document of Conformity | <a href="#">Attestation of Conformity</a><br><a href="#">IECEX Certificate</a><br><a href="#">ATEX Certificate</a><br><a href="#">CB Test Certificate</a><br><a href="#">CB Certificate</a><br><a href="#">EAC certificate</a><br><a href="#">DNVGL certificate</a><br><a href="#">BV certificate</a><br><a href="#">MARITREG certificate</a><br><a href="#">CCC Ex Certificate</a><br><a href="#">Declaration of Conformity</a><br><a href="#">Declaration of Conformity all terminals</a> |
| Engineering Data                            | <a href="#">STEP</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Engineering Data                            | <a href="#">EPLAN, WSCAD, Zuken E3.S</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Tender specification                        | <a href="#">Klippon® Connect 205 1500000 DE</a><br><a href="#">Klippon® Connect 205 1500000 EN</a>                                                                                                                                                                                                                                                                                                                                                                                          |
| User Documentation                          | <a href="#">NTI_A4C 4.pdf</a><br><a href="#">StorageConditionsTerminalBlocks</a><br><a href="#">NTI ALO 16</a>                                                                                                                                                                                                                                                                                                                                                                              |
| Catalogues                                  | <a href="#">Catalogues in PDF-format</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Brochures                                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |

### A4C 4

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Drawings

