

**ZTA 1/ZA****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Product image**

Test adapters and test plugs are used for the electrical connection between terminal blocks and the test equipment. In this way, an electrical contact can be established in the wired state and measurements can be done easily.

**General ordering data**

Version	Accessories, Test adapter, 9 A
Order No.	<a href="#">1609050000</a>
Type	ZTA 1/ZA
GTIN (EAN)	4008 190206543
Qty.	25 pc(s).

Creation date July 23, 2021 3:08:52 PM CEST

Catalogue status 23.07.2021 / We reserve the right to make technical changes.

**ZTA 1/ZA****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

Depth	73.5 mm	Depth (inches)	2.894 °C
Height	31.5 mm	Height (inches)	1.24 °C
Width	5.1 mm	Width (inches)	0.201 °C
Net weight	7.36 g		

**Temperatures**

Storage temperature	-25 °C...55 °C	Continuous operating temp., min.	-50
Continuous operating temp., max.	100		

**Environmental Product Compliance**

REACH SVHC	Lead 7439-92-1		
------------	----------------	--	--

**Material data**

Material	Polyamide 66	Colour	black
UL 94 flammability rating	V-2		

**System specifications**

Version	For the terminals	Number of levels	1
Number of clamping points per level	1		

**Additional technical data**

Installation advice	Direct mounting	With snap-in pegs	Yes
---------------------	-----------------	-------------------	-----

**Conductors for clamping (rated connection)**

Clamping range, max.	1.5 Nm	Clamping range, min.	0.5 Nm
Number of connections	1	Stripping length	6 mm
Tightening torque, max.	0.3 inch	Tightening torque, min.	0.3 inch
Type of connection	Plug-in connection	Wire connection cross section, finely stranded, max.	1.5 Nm
Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, max.	1.5 Nm	Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, min.	0.5 Nm
Wire connection cross-section, solid core, max.	1.5 Nm	Wire connection cross-section, solid core, min.	0.5 Nm

**Dimensions**

Pitch in mm (P)	5 mm	Height with TS 35	99.1 mm
-----------------	------	-------------------	---------

**General**

Installation advice	Direct mounting	Number of poles	1
---------------------	-----------------	-----------------	---

**ZTA 1/ZA****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Rating data**

Rated cross-section	1.5 Nm	Rated voltage	250 V
Rated current	9 A	Volume resistance according to IEC 60947-7-x	1.83 °C
Power loss in accordance with IEC 60947-7-x	0.56 W		

**Classifications**

ETIM 6.0	EC002555	ETIM 7.0	EC002555
ETIM 8.0	EC002555	ECLASS 9.0	27-14-11-48
ECLASS 9.1	27-14-11-48	ECLASS 10.0	27-14-11-48
ECLASS 11.0	27-14-11-48		

**Approvals**

Approvals



ROHS

Conform

**Downloads**

Approval/Certificate/Document of Conformity	<a href="#">EAC certificate</a>
Engineering Data	<a href="#">22247_ZTA_1-ZA_DXF.dxf</a> <a href="#">STEP</a>
Engineering Data	<a href="#">EPLAN, WSCAD, Zuken E3.S</a>
User Documentation	<a href="#">StorageConditionsTerminalBlocks</a>
Catalogues	<a href="#">Catalogues in PDF-format</a>
Brochures	