

**WQV 6/2****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Product image**

Screwable cross-connections are easy to mount and de mount. Thanks to the big contact surface, even high currents can be transmitted with maximum contact reliability.

**General ordering data**

|            |                                                                     |
|------------|---------------------------------------------------------------------|
| Version    | W-Series, Cross-connector, For the terminals,<br>Number of poles: 2 |
| Order No.  | <a href="#">1052360000</a>                                          |
| Type       | WQV 6/2                                                             |
| GTIN (EAN) | 4008 190075866                                                      |
| Qty.       | 50 pc(s).                                                           |

## WQV 6/2

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|            |         |                 |          |
|------------|---------|-----------------|----------|
| Depth      | 18 mm   | Depth (inches)  | 0.709 °C |
| Height     | 14.1 mm | Height (inches) | 0.555 °C |
| Width      | 7.6 mm  | Width (inches)  | 0.299 °C |
| Net weight | 3.2 g   |                 |          |

## Temperatures

|                                  |                |                                  |        |
|----------------------------------|----------------|----------------------------------|--------|
| Storage temperature              | -25 °C...55 °C | Continuous operating temp., min. | -60 °C |
| Continuous operating temp., max. | 130 °C         |                                  |        |

## Material data

|                           |       |        |        |
|---------------------------|-------|--------|--------|
| Material                  | PA 66 | Colour | yellow |
| UL 94 flammability rating | V-0   |        |        |

## System specifications

|         |                   |
|---------|-------------------|
| Version | For the terminals |
|---------|-------------------|

## Additional technical data

|                |                 |
|----------------|-----------------|
| Type of fixing | when screwed in |
|----------------|-----------------|

## Cross-connector

|                                     |                 |                                          |              |
|-------------------------------------|-----------------|------------------------------------------|--------------|
| Number of cross-connected terminals | 2               | Rated current, 2-pole                    | 57 A         |
| Rated current, multi-pole           | 57 A            | Tightening torque range for fixing screw | 0.5...1.0 Nm |
| Type                                | Cross-connector |                                          |              |

## Dimensions

|                 |      |
|-----------------|------|
| Pitch in mm (P) | 8 mm |
|-----------------|------|

## General

|                 |   |
|-----------------|---|
| Number of poles | 2 |
|-----------------|---|

## Rating data

|               |      |
|---------------|------|
| Rated current | 57 A |
|---------------|------|

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000489    | ETIM 7.0    | EC000489    |
| ETIM 8.0    | EC000489    | ECLASS 9.0  | 27-14-11-40 |
| ECLASS 9.1  | 27-14-11-40 | ECLASS 10.0 | 27-14-11-40 |
| ECLASS 11.0 | 27-14-11-40 |             |             |

## WQV 6/2

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Technical data

### Approvals

Approvals



ROHS

Conform

### Downloads

Approval/Certificate/Document of  
Conformity

[EAC certificate](#)

Engineering Data

[EPLAN, WSCAD, Zuken E3.S](#)

User Documentation

[Beipackzettel\\_WQV.pdf](#)  
[StorageConditionsTerminalBlocks](#)

Catalogues

[Catalogues in PDF-format](#)

Brochures