

**A4C 2.5 PE****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Product image****Spring connection with PUSH IN Technology**

The innovative PUSH IN technology reduces the amount of time you spend on wiring to a minimum. Direct insertion guarantees high conductor pull-out forces and simple handling for all conductor types.

**General ordering data**

|            |                                                          |
|------------|----------------------------------------------------------|
| Version    | PE terminal, PUSH IN, 2.5 mm <sup>2</sup> , Green/yellow |
| Order No.  | <a href="#">1521540000</a>                               |
| Type       | A4C 2.5 PE                                               |
| GTIN (EAN) | 4050118328349                                            |
| Qty.       | 50 pc(s).                                                |

**A4C 2.5 PE****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

|                          |          |                |          |
|--------------------------|----------|----------------|----------|
| Depth                    | 36.5 mm  | Depth (inches) | 1.437 °C |
| Depth including DIN rail | 37 mm    | Height         | 77.5 mm  |
| Height (inches)          | 3.051 °C | Width          | 5.1 mm   |
| Width (inches)           | 0.201 °C | Net weight     | 12.74 g  |

**Temperatures**

|                                  |                |                                  |        |
|----------------------------------|----------------|----------------------------------|--------|
| Storage temperature              | -25 °C...55 °C | Continuous operating temp., min. | -60 °C |
| Continuous operating temp., max. | 130 °C         |                                  |        |

**Material data**

|                                |        |                           |              |
|--------------------------------|--------|---------------------------|--------------|
| Material                       | Wemid  | Colour                    | Green/yellow |
| Colour of operational elements | orange | UL 94 flammability rating | V-0          |

**Rating data IECEx/ATEX**

|                                |                     |                                 |                     |
|--------------------------------|---------------------|---------------------------------|---------------------|
| Certificate No. (ATEX)         | TUEV16ATEX7909U     | Certificate No. (IECEX)         | IECEXTUR16.0036U    |
| Wire cross section max. (ATEX) | 2.5 mm <sup>2</sup> | Wire cross section max. (IECEX) | 2.5 mm <sup>2</sup> |
| Marking EN 60079-7             | Ex eb II C Gb       | Ex 2014/34/EU label             | II 2 G D            |

**System specifications**

|                               |       |                                     |     |
|-------------------------------|-------|-------------------------------------|-----|
| End cover plate required      | Yes   | Number of potentials                | 1   |
| Number of levels              | 1     | Number of clamping points per level | 4   |
| Number of potentials per tier | 1     | PE connection                       | Yes |
| Rail                          | TS 35 | N-function                          | No  |
| PE function                   | Yes   | PEN function                        | No  |

**Additional technical data**

|                     |       |                   |         |
|---------------------|-------|-------------------|---------|
| Installation advice | Rail  | Open sides        | right   |
| Snap-on             | No    | Type of fixing    | Snap-on |
| Type of mounting    | TS 35 | With snap-in pegs | No      |

**CSA rating data**

|                               |                 |                               |        |
|-------------------------------|-----------------|-------------------------------|--------|
| Certificate No. (CSA)         | 200039-70089609 | Voltage size B (CSA)          | 600 V  |
| Voltage size C (CSA)          | 600 V           | Voltage size D (CSA)          | 600 V  |
| Wire cross section max. (CSA) | 12 AWG          | Wire cross section min. (CSA) | 28 AWG |

**Conductors for clamping (rated connection)**

|                                          |              |
|------------------------------------------|--------------|
| Blade size                               | 0.6 x 3.5 mm |
| Clamping range, max.                     | 2.5 Nm       |
| Clamping range, min.                     | 0.14 Nm      |
| Connection cross-section, stranded, max. | 2.5 Nm       |
| Connection cross-section, stranded, min. | 0.5 Nm       |
| Connection direction                     | top          |
| Gauge to IEC 60947-1                     | A3           |
| Number of connections                    | 4            |
| Stripping length                         | 10 mm        |

## A4C 2.5 PE

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

|                                                                                         |                                        |         |         |
|-----------------------------------------------------------------------------------------|----------------------------------------|---------|---------|
| Tube length for AEH with plastic collar<br>DIN 46228/4                                  | Cross-section for conductor connection | min.    | 0.34 Nm |
|                                                                                         |                                        | max.    | 0.14 Nm |
|                                                                                         | Tube length                            | max.    | 6 mm    |
|                                                                                         |                                        | min.    | 8 mm    |
|                                                                                         | Cross-section for conductor connection | min.    | 1 Nm    |
|                                                                                         |                                        | max.    | 0.5 Nm  |
|                                                                                         | Tube length                            | max.    | 6 mm    |
|                                                                                         |                                        | min.    | 12 mm   |
|                                                                                         | Cross-section for conductor connection | min.    | 2.5 Nm  |
|                                                                                         |                                        | max.    | 1.5 Nm  |
|                                                                                         | Tube length                            | max.    | 8 mm    |
|                                                                                         |                                        | min.    | 12 mm   |
| Tube length for AEH without plastic collar<br>DIN 46228/1                               | Cross-section for conductor connection | nominal | 0.25 Nm |
|                                                                                         |                                        | nominal | 5 mm    |
|                                                                                         | Cross-section for conductor connection | min.    | 0.5 Nm  |
|                                                                                         |                                        | max.    | 1 Nm    |
|                                                                                         | Tube length                            | max.    | 10 mm   |
|                                                                                         |                                        | min.    | 6 mm    |
|                                                                                         | Cross-section for conductor connection | min.    | 1.5 Nm  |
|                                                                                         |                                        | max.    | 2.5 Nm  |
|                                                                                         | Tube length                            | max.    | 12 mm   |
|                                                                                         |                                        | min.    | 7 mm    |
| Tube length for twin wire-end ferrule                                                   | Tube length                            | max.    | 12 mm   |
|                                                                                         |                                        | min.    | 8 mm    |
|                                                                                         | Cross-section for conductor connection | min.    | 0.5 Nm  |
|                                                                                         |                                        | max.    | 0.75 Nm |
| Twin wire-end ferrules, max.                                                            | 0.75 Nm                                |         |         |
| Twin wire-end ferrules, min.                                                            | 0.5 Nm                                 |         |         |
| Type of connection                                                                      | PUSH IN                                |         |         |
| Wire connection cross section AWG, max.                                                 | AWG 12                                 |         |         |
| Wire connection cross section AWG, min.                                                 | AWG 26                                 |         |         |
| Wire connection cross section, finely stranded, max.                                    | 2.5 Nm                                 |         |         |
| Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, max. | 2.5 Nm                                 |         |         |
| Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, min. | 0.5 Nm                                 |         |         |
| Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, max. | 2.5 Nm                                 |         |         |
| Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, min. | 0.5 Nm                                 |         |         |
| Wire connection cross-section, solid core, max.                                         | 2.5 Nm                                 |         |         |
| Wire connection cross-section, solid core, min.                                         | 0.5 Nm                                 |         |         |

## General

|                                         |               |                                         |        |
|-----------------------------------------|---------------|-----------------------------------------|--------|
| Installation advice                     | Rail          | Rail                                    | TS 35  |
| Standards                               | IEC 60947-7-2 | Wire connection cross section AWG, max. | AWG 12 |
| Wire connection cross section AWG, min. | AWG 26        |                                         |        |

Creation date July 23, 2021 3:17:05 PM CEST

## A4C 2.5 PE

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## PE rating data

|                          |                              |              |    |
|--------------------------|------------------------------|--------------|----|
| Rated short-time current | 300 A (2.5 mm <sup>2</sup> ) | PEN function | No |
|--------------------------|------------------------------|--------------|----|

## Rating data

|                                 |               |                                              |         |
|---------------------------------|---------------|----------------------------------------------|---------|
| Rated cross-section             | 2.5 Nm        | Rated voltage to adjoining terminal          | 800 V   |
| Standards                       | IEC 60947-7-2 | Volume resistance according to IEC 60947-7-x | 1.33 °C |
| Rated impulse withstand voltage | 8 kV          | Power loss in accordance with IEC 60947-7-x  | 0.77 W  |
| Pollution severity              | 3             | Surge voltage category                       | III     |

## UL rating data

|                                            |        |                                            |        |
|--------------------------------------------|--------|--------------------------------------------|--------|
| Certificate No. (cURus)                    | E60693 | Conductor size Factory wiring max. (cURus) | 12 AWG |
| Conductor size Factory wiring min. (cURus) | 28 AWG | Conductor size Field wiring max. (cURus)   | 12 AWG |
| Conductor size Field wiring min. (cURus)   | 28 AWG | Voltage size B (cURus)                     | 600 V  |
| Voltage size C (cURus)                     | 600 V  | Voltage size D (cURus)                     | 600 V  |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000901    | ETIM 7.0    | EC000901    |
| ETIM 8.0    | EC000901    | ECLASS 9.0  | 27-14-11-41 |
| ECLASS 9.1  | 27-14-11-41 | ECLASS 10.0 | 27-14-11-41 |
| ECLASS 11.0 | 27-14-11-41 |             |             |

## Approvals

Approvals



|                       |         |
|-----------------------|---------|
| ROHS                  | Conform |
| UL File Number Search | E60693  |

## A4C 2.5 PE

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Technical data

### Downloads

|                                             |                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|---------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Approval/Certificate/Document of Conformity | <a href="#">Attestation of Conformity</a><br><a href="#">IECEX Certificate</a><br><a href="#">ATEX Certificate</a><br><a href="#">CB Test Certificate</a><br><a href="#">EAC certificate</a><br><a href="#">DNVGL certificate</a><br><a href="#">BV certificate</a><br><a href="#">MARITREG certificate</a><br><a href="#">CCC Ex Certificate</a><br><a href="#">Declaration of Conformity</a><br><a href="#">Declaration of Conformity all terminals</a> |
| Engineering Data                            | <a href="#">STEP</a>                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Engineering Data                            | <a href="#">EPLAN, WSCAD, Zuken E3.S</a>                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Tender specification                        | <a href="#">Klippon® Connect 1521540000 DE</a><br><a href="#">Klippon® Connect 1521540000 EN</a>                                                                                                                                                                                                                                                                                                                                                          |
| User Documentation                          | <a href="#">NTI_A4C 2.5.pdf</a><br><a href="#">StorageConditionsTerminalBlocks</a><br><a href="#">NTI ALO 16</a>                                                                                                                                                                                                                                                                                                                                          |
| Catalogues                                  | <a href="#">Catalogues in PDF-format</a>                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Brochures                                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                           |

### A4C 2.5 PE

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Drawings

