

**WQL 2 WFF300****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Product image**

Similar to illustration

Screwable cross-connections are easy to mount and de mount. Thanks to the big contact surface, even high currents can be transmitted with maximum contact reliability.

**General ordering data**

|            |                                                                   |
|------------|-------------------------------------------------------------------|
| Version    | Bolt-type screw terminals, Cross-connector,<br>Number of poles: 2 |
| Order No.  | <a href="#">1065300000</a>                                        |
| Type       | WQL 2 WFF300                                                      |
| GTIN (EAN) | 4008190110000                                                     |
| Qty.       | 5 pc(s).                                                          |

## WQL 2 WFF300

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|            |          |                 |          |
|------------|----------|-----------------|----------|
| Depth      | 5 mm     | Depth (inches)  | 0.197 °C |
| Height     | 95 mm    | Height (inches) | 3.74 °C  |
| Width      | 40 mm    | Width (inches)  | 1.575 °C |
| Net weight | 148.43 g |                 |          |

## Temperatures

|                     |                |
|---------------------|----------------|
| Storage temperature | -25 °C...55 °C |
|---------------------|----------------|

## Material data

|          |               |        |      |
|----------|---------------|--------|------|
| Material | Copper - zinc | Colour | grey |
|----------|---------------|--------|------|

## Additional technical data

|                          |                 |                     |                 |
|--------------------------|-----------------|---------------------|-----------------|
| Explosion-tested version | No              | Installation advice | Direct mounting |
| Type of fixing           | when screwed in |                     |                 |

## Cross-connector

|                                     |       |                       |                 |
|-------------------------------------|-------|-----------------------|-----------------|
| Number of cross-connected terminals | 2     | Rated current, 2-pole | 520 A           |
| Rated current, multi-pole           | 520 A | Type                  | Cross-connector |

## Dimensions

|                 |       |
|-----------------|-------|
| Pitch in mm (P) | 55 mm |
|-----------------|-------|

## General

|                     |                 |                 |   |
|---------------------|-----------------|-----------------|---|
| Installation advice | Direct mounting | Number of poles | 2 |
|---------------------|-----------------|-----------------|---|

## Rating data

|               |       |
|---------------|-------|
| Rated current | 520 A |
|---------------|-------|

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000489    | ETIM 7.0    | EC000489    |
| ETIM 8.0    | EC000489    | ECLASS 9.0  | 27-14-11-40 |
| ECLASS 9.1  | 27-14-11-40 | ECLASS 10.0 | 27-14-11-40 |
| ECLASS 11.0 | 27-14-11-40 |             |             |

## Approvals

Approvals



ROHS

Conform

## WQL 2 WFF300

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Technical data

### Downloads

|                                             |                                                 |
|---------------------------------------------|-------------------------------------------------|
| Approval/Certificate/Document of Conformity | <a href="#">EAC certificate</a>                 |
| Engineering Data                            | <a href="#">STEP</a>                            |
| Engineering Data                            | <a href="#">EPLAN, WSCAD, Zuken E3.S</a>        |
| User Documentation                          | <a href="#">StorageConditionsTerminalBlocks</a> |
| Catalogues                                  | <a href="#">Catalogues in PDF-format</a>        |
| Brochures                                   |                                                 |