


Mer om VW3A3401

- [Karakteristiker](#)
- [Download & Dokumenter](#)

Discover your Schneider-
Electric tools

**VW3A3401**

encoder interface card with RS422 compatible differential
outputs - 5 V DC



 [Last ned produktdatablad for VW3A3401](#)

Karakteristikker

Teknisk informasjon

Produktspekter	Altivar
Produkt eller type komponent	Encoder interface card
Serie kompatibilitet	Altivar Lift Altivar 61 Altivar 71Q Altivar 71 Altivar 61Q
Digitale utganger	Differensial
Kommunikasjonsprotokoll	RS422
[Us] matespenning	5 V DC (voltage limits 5...5.5 V)
Antall pulser pr. omdreining	10000 for ATV71H.....383 5000 for all ATV61 drives 5000 for ATV71H...M3 5000 for ATV71H...M3X 5000 for ATV71H...N4

Komplementær

Maximum supply current	0,2 A
Type vern	Kortslutningsvern Overlastbeskyttelse
Maximum cable distance between devices	50 m
Maksimal driftsfrekvens	300 kHz
Inngangssignal	A B Compliment of A Compliment of B
Inngangsimpedans	440 Ohm
Elektrisk tilkobling	Terminal, connection capacity: 0.2 mm ² (AWG 24) <25 m cable length, encoder, 100 mA at 4.5 V Terminal, connection capacity: 0.5 mm ² (AWG 20) <25 m cable length, encoder, 200 mA at 4.5 V Terminal, connection capacity: 0.5 mm ² (AWG 20) <50 m cable length, encoder, 100 mA at 4.5 V Terminal, connection capacity: 0.75 mm ² (AWG 18) <50 m cable length, encoder, 200 mA at 4.5 V
Vekt	0,2 kg

Offer Sustainability

Produktets miljøstatus	Green Premium miljømerket produkt
REACH-regelverk	REACH-erklæring
EU RoHS-direktiv	Proaktivt i samsvar (Produktet inngår ikke i EUs RoHS direktivet) EU RoHS-erklæring
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	Ja
Kinas RoHS-forskrift	Kinas RoHS-erklæring
Miljøinformasjon	Produktmiljøprofil