

FDV – DOKUMENTASJON		Nr.:109
		Rev.:
		Dato: 19.12.2016
Produktspesifikasjon	PERFECT cable gland PG	
Produktnavn	50.0xx	
Anvisning for drift	Ingen anvisning for drift	
Vedlikehold	Ingen vedlikehold	
Henvisninger Vedlegg	Datablad	
Produsent	Jacob GmbH Elektrotechnische Fabrik Gottlieb-Daimler-Strasse 11 D-71394 Kernen Germany	
Importør	EFA Elektro AS, Postboks 593, 1411 Kolbotn, Norway Tlf. 66812400 e-mail: post@efa.no - www.efa.no	

PERFECT cable gland

50.0xx

Dome nut	Brass CuZn39Pb3, nickel-plated
Lamellar insert	Polyamide PA6 V-2
Sealing ring	Polychloroprene-Nitrile rubber CR/NBR
Gland body	Brass CuZn39Pb3, nickel-plated
O-ring	Nitrile rubber NBR
Connecting thread	Pg as per DIN 40430



Properties	
	- integrated anchorage - protection against twisting, - wide sealing and clamping range - easy-to-install
Temperature range (°C)	-20°C / +100°C (dynamic) -40°C (static, short term)
Protection grade	68 5

