

Floor standing distribution board with locking rotary lever, prepared for F3A gland plate inserts, incl. modular insert, W=600mm, H = 1860 mm, D = 320 mm

Part no. **BPM-F-600/17/3-P-F3A-W/BS6**  
Catalog No. **187855**

EL-Nummer **2456432**  
(Norway)

## Delivery program

Mounting type			Floor standing distribution board
Material			Sheet steel
Door interlock			Rotary lever
Installation site			Indoor
Degree of Protection			IP55
Surface finish			With powder coating
Width		mm	600
Depth		mm	320
Height		mm	1860
Colour			white (RAL 9016)
Modular spacing (space units)			168 SU
Rows	Count		7

## Technical data ETIM 7.0

Cabinet enclosures (EG000011) / Enclosure/switchgear cabinet (empty) (EC000261)			
Electric engineering, automation, process control engineering / Electrical cabinet, housing, rack / Electrical cabinet (empty) / Electrical cabinet (ecl@ss10.0.1-27-18-01-01 [AGZ056016])			
Width		mm	600
Height		mm	1860
Depth		mm	320
Material			Steel
Material quality			Other
Surface finishing			Powder coating
Colour			White
RAL-number			9016
With mounting plate			No
Mounting plate depth-adjustable			No
Number of locks			0
Floor installation possible			Yes
Wall fastening possible			No
Wall build in			No
Pole fastening			No
Tackable			No
Number of doors			1
Suitable for metrical mounting			Yes
Suitable for outdoor set-up			No
Pitched roof			No
EMC-version			Yes
With glazed door			No
With ventilation door			No
With backside door			No
Impact strength			IK10
Degree of protection (IP)			IP55
Degree of protection (NEMA)			

