



**Floor-standing distribution board with double-bit lock, IP55,
HxWxD=2060x600x320mm, white**

Part no. BPM-F-600/20-W
Catalog No. 111080

EL-Nummer 0002459532
(Norway)

Delivery program

Mounting type			Floor standing distribution board
Material			Sheet steel
Door interlock			Double-ward lock
Installation site			Moisture-proof
Degree of Protection			IP55
Surface finish			With powder coating
Width		mm	600
Depth		mm	320
Height		mm	2060
Colour			white (RAL 9016)

Design verification as per IEC/EN 61439

Technical data for design verification			
Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890			
Individual enclosure, free-standing	P _V	W	176
Starting enclosure, free-standing	P _V	W	173
Middle enclosure, free-standing	P _V	W	153
Individual enclosure for wall mounting	P _V	W	155
Starting enclosure for wall mounting	P _V	W	140
Middle enclosure for wall mounting	P _V	W	128
Heat dissipation, at an ambient temperature of 35°C, delta T: 35 degrees in top of the enclosure, calculated as per IEC 60890			
Individual enclosure, free-standing	P _V	W	352
Starting enclosure, free-standing	P _V	W	347
Middle enclosure, free-standing	P _V	W	306
Individual enclosure for wall mounting	P _V	W	311
Starting enclosure for wall mounting	P _V	W	280
Middle enclosure for wall mounting	P _V	W	256
IEC/EN 61439 design verification			
10.2 Strength of materials and parts			
10.2.2 Corrosion resistance			Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures			Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat			Meets the product standard's requirements.
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects			Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation			Not relevant to indoor installations.
10.2.5 Lifting			Met; assembled and secured as per the latest applicable instruction leaflet.

10.2.6 Mechanical impact		IK10
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of ASSEMBLIES		IP55
10.4 Clearances and creepage distances		Is the panel builder's responsibility.
10.5 Protection against electric shock		< 0.1 Ω; meets the product standard's requirements.
10.6 Incorporation of switching devices and components		Is the panel builder's responsibility.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9 Insulation properties		
10.9.2 Power-frequency electric strength		$U_i = 440 \text{ V AC}$
10.9.3 Impulse withstand voltage		4 kV
10.9.4 Testing of enclosures made of insulating material		Does not apply to metal enclosures.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility.
10.13 Mechanical function		Meets the product standard's requirements.

Technical data ETIM 7.0

Cabinet enclosures (EG000011) / Enclosure/switchgear cabinet (empty) (EC000261)		
Electric engineering, automation, process control engineering / Electrical cabinet, housing, rack / Electrical cabinet (empty) / Electrical cabinet (ecl@ss10.0.1-27-18-01-01 [AGZ056016])		
Width	mm	600
Height	mm	2060
Depth	mm	320
Material		Steel
Material quality		Other
Surface finishing		Powder coating
Colour		White
RAL-number		9016
With mounting plate		No
Mounting plate depth-adjustable		No
Number of locks		0
Floor installation possible		Yes
Wall fastening possible		No
Wall build in		No
Pole fastening		No
Tackable		Yes
Number of doors		1
Suitable for metrical mounting		No
Suitable for outdoor set-up		No
Pitched roof		No
EMC-version		No
With glazed door		No
With ventilation door		No
With backside door		No
Impact strength		IK10
Degree of protection (IP)		IP55
Degree of protection (NEMA)		