DATASHEET - BPM-F-1000/17/3-P-F3A-W/BS4

Floor standing distribution board with locking rotary lever, prepared for F3A gland plate inserts, incl. modular insert with mounting plate, W=1000mm, $H=1860\,mm$, $D=320\,mm$



Part no. BPM-F-1000/17/3-P-F3A-W/BS4

Catalog No. 187853

EL-Nummer 0002456430 (Norway)

Delivery program

Mounting type			Floor standing distribution board
Material			Sheet steel
Door interlock			Rotary lever
Installation site			Indoor
Degree of Protection			IP55
Surface finish			With powder coating
Width		mm	1000
Depth		mm	320
Height		mm	1860
Colour			white (RAL 9016)
Modular spacing (space units)			192 SU
Rows	Count		8

Technical data ETIM 7.0

IECIIIICAI UALA LIIIVI 7.0		
Cabinet enclosures (EG000011) / Enclosure/switchgear cabinet (empty) (EC000261)		
Electric engineering, automation, process control engineering / Electrical cabinet, h	ousing, rack / Electrica	al cabinet (empty) / Electrical cabinet (ecl@ss10.0.1-27-18-01-01 [AGZ056016])
Width	mm	1000
Height	mm	1860
Depth	mm	320
Material		Steel
Material quality		Other
Surface finishing		Powder coating
Colour		White
RAL-number		9016
With mounting plate		Yes
Mounting plate depth-adjustable		No
Number of locks		0
Floor installation possible		Yes
Wall fastening possible		No
Wall build in		No
Pole fastening		No
Tackable		No
Number of doors		2
Suitable for metrical mounting		Yes
Suitable for outdoor set-up		No
Pitched roof		No
EMC-version		Yes
With glazed door		No
With ventilation door		No
With backside door		No
Impact strength		IK10
Degree of protection (IP)		IP55
Degree of protection (NEMA)		