



168992
S811+T30V3S

[Overview](#)

[Specifications](#)

[Resources](#)



[Delivery program](#)

[Technical data](#)

[Design verification as
per IEC/EN 61439](#)

[Technical data ETIM 7.0](#)

[Approvals](#)

[Dimensions](#)

DELIVERY PROGRAM

Description
With internal bypass contacts

Function
Soft starter for three-phase loads, with control
unit and pump algorithm, for 690-V grids

Mains supply voltage (50/60 Hz) [U_N]
200 - 690 V AC

Supply voltage [U_s]
24 V DC

Control voltage [U_c]
24 V DC

Assigned motor rating (Standard connection, In-Line)

at 400 V, 50 Hz [P]
160 kW

at 690 V, 50 Hz [P]
250 kW

at 460 V, 60 Hz [P]
250 HP

Rated operational current

AC-53 [I_e]
304 A

Startup class
CLASS 10 (star-delta replacement)
CLASS 20 (heavy starting duty $3 \times I_e$ for 45 s)
CLASS 30 ($6 \times I_e$ for 30 s)

Rated operational voltage [U_e]
200 V
230 V
400 V
480 V
600 V
690 V

Connection to SmartWire-DT
no

Frame size
T

Ordering information
Terminal blocks for the terminals are required for
frame sizes T, U, and V -> Accessories

TECHNICAL DATA

General

Standards
IEC/EN 60947-4-2
UL 508
CSA22.2-14-1995
GB14048

Approvals
CE

Approvals
UL
CSA
C-Tick
CCC

Climatic proofing
Damp heat, constant, to IEC 60068-2-3
Damp heat, cyclic, to IEC 60068-2-10

Ambient temperature
Operation [9]
-30 - +50 °C

Ambient temperature
Storage [9]
-50 - +70 °C

Altitude
0 - 2000 m, above that each 100 m 0.5% Derating
m

Mounting position
As required

Degree of protection
Degree of Protection
IP20 (terminals IP00)

Degree of protection
Integrated
An IP20 degree of protection can be achieved on all sides by using optional terminal covers SS-IP20-TU.

Protection against direct contact
Finger- and back-of-hand proof

Overvoltage category/pollution degree
II/3

Shock resistance
15 g

Radio interference level (IEC/EN 55011)

A

Static heat dissipation, non-current-dependent [P_{st}]

45 W

Weight

18.6 kg

Main conducting paths

Rated operating voltage [U_e]

200 - 690 V AC

Supply frequency [f_{LN}]

50/60 Hz

Rated operational current [I_e]

AC-53 [I_e]

304 A

Assigned motor rating (Standard connection, In-Line)

at 230 V, 50 Hz [P]

90 kW

Assigned motor rating (Standard connection, In-Line)

at 400 V, 50 Hz [P]

160 kW

Assigned motor rating (Standard connection, In-Line)

at 500 V, 50 Hz [P]

200 kW

Assigned motor rating (Standard connection, In-Line)

at 690 V, 50 Hz [P]

250 kW

Assigned motor rating (Standard connection, In-Line)

at 200 V, 60 Hz [P]

100 HP

Assigned motor rating (Standard connection, In-Line)
at 230 V, 60 Hz [P]
100 HP

Assigned motor rating (Standard connection, In-Line)
at 460 V, 60 Hz [P]
250 HP

Assigned motor rating (Standard connection, In-Line)
at 600 V, 60 Hz [P]
300 HP

Assigned motor rating (Standard connection, In-Line)
at 690 V, 60 Hz [P]
350 HP

Assigned motor rating (delta connection)
at 690 V, 60 Hz [P]
600 HP

Overload cycle to IEC/EN 60947-4-2
AC-53a
304 A: AC-53a: 4.0 - 32: 99 - 3

Overload cycle to IEC/EN 60947-4-2
Internal bypass contacts
☐

Short-circuit rating
Type "1" coordination
NZMN3-S320

Terminal capacities

Cable lengths
Solid
1 x (70 - 240)
2 x (25 - 240) mm²

Cable lengths
Flexible with ferrule
1 x (70 - 240)
2 x (25 - 240) mm²

Cable lengths
Stranded
1 x (70 - 240)
2 x (25 - 240) mm²

Cable lengths
Solid or stranded
1 x (4 - 500 kcmil)
2 x (4 - 500 kcmil) AWG

Cable lengths
Tightening torque
25.5 (≤ 150 mm²); 28.3 (> 150 mm²) Nm

Cable lengths
Screw driver (PZ: Pozidriv)
4 mm Innensechskant mm

Control cables
Solid
1 x (2.5 - 4)
2 x (1.0 - 2.5) mm²

Control cables
Flexible with ferrule
1 x (2.5 - 4)
2 x (1.0 - 2.5) mm²

Control cables
Stranded
1 x (2.5 - 4)
2 x (1.0 - 2.5) mm²

Control cables
Solid or stranded
17 x (12 - 14)
2 x (12 - 14) AWG

Control cables
Tightening torque
0.4 Nm

Control cables
Screw driver
0,6 x 3,5 mm

Control circuit

Digital inputs
Control voltage
DC-operated
24 V DC +10 %/- 10 % V DC

Digital inputs
Current consumption 24 V
External 24 V
150 mA

Digital inputs
Current consumption 24 V
External 24 V (no-load)
100 mA

Digital inputs
Pick-up voltage
DC-operated
21.6 - 26.4 V DC

Digital inputs
Drop-out voltage [$\times U_s$]
DC operated
Drop-out voltage, DC-operated, max.
3 V DC

Digital inputs
Pick-up time
DC operated
100 ms

Digital inputs
Drop-out time
DC operated
100 ms

Regulator supply
Voltage [U_s]
24 V DC +10 %/- 10 % V

Regulator supply
Current consumption [I_b]
1000 mA

Regulator supply
Current consumption at peak performance (close
bypass) at 24 V DC [I_{peak}]
10/150 A/ms

Regulator supply
Notes
External supply voltage

Analog inputs
Number of current inputs
1

Analog inputs
Current input
4 - 20 mA

Relay outputs
Number
2

Relay outputs
of which programmable
2

Relay outputs
Voltage range
120 V AC/DC V AC

Relay outputs
AC-11 current range
3 A, AC-11 A

Soft start function

Ramp times
Acceleration
Ramp time, max.
360 s

Ramp times
Deceleration
0 - 120 s

Start voltage (= turn-off voltage)
Start voltage, max.
85 %

Start pedestal
Start voltage, max.
85 %

Kickstart
Voltage
Kickstart voltage, max.
100 %

Kickstart
Duration
50 Hz
Kickstart Duration 50 Hz max.
2000 ms

Kickstart
Duration
60 Hz
Kickstart Duration 60 Hz max.
2000 ms

Fields of application
Fields of application
Soft starting of three-phase asynchronous motors

Fields of application
3-phase motors
☐

Functions

Fast switching (semiconductor contactor)
- (minimum ramp time 1s)

Soft start function
☐

Reversing starter
External solution required (reversing contactor)

Suppression of closing transients
☐

Current limitation
☐

Overload monitoring
☐

Underload monitoring



Fault memory
10 Faults

Suppression of DC components for motors



Potential isolation between power and control
sections
☐

Communication Interfaces
Mdbus RTU

DESIGN VERIFICATION AS PER IEC/EN 61439

Technical data for design verification

Rated operational current for specified heat
dissipation [I_n]
304 A

Heat dissipation per pole, current-dependent [P_{id}]
0 W

Equipment heat dissipation, current-dependent
[P_{id}]
45 W

Static heat dissipation, non-current-dependent [P_{is}]
45 W

Heat dissipation capacity [P_{diss}]
0 W

Operating ambient temperature min.
-30 °C

Operating ambient temperature max.
+50 °C

10.2 Strength of materials and parts
10.2.2 Corrosion resistance
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.3.1 Verification of thermal stability of enclosures
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.3.2 Verification of resistance of insulating materials to normal heat
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.4 Resistance to ultra-violet (UV) radiation
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.5 Lifting
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts
10.2.6 Mechanical impact
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts
10.2.7 Inscriptions
Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES
Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances
Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9 Insulation properties

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9 Insulation properties

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9 Insulation properties

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

TECHNICAL DATA ETIM 7.0

Low-voltage industrial components (EG000017) / Soft starter (EC000640)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Load breakout, motor breakout / Semiconductor motor controller or soft starter (ec1@ss10.0.1-27-37-09-07 [ACO300011])

Rated operation current I_e at 40 °C T_u
304 A

Rated operating voltage U_e
200 - 690 V

Rated power three-phase motor, inline, at 230 V
90 kW

Rated power three-phase motor, inline, at 400 V
160 kW

Rated power three-phase motor, inside delta, at
230 V
160 kW

Rated power three-phase motor, inside delta, at
400 V
250 kW

Function
Single direction

Internal bypass
Yes

With display
Yes

Torque control
No

Rated surrounding temperature without derating
50 °C

Rated control supply voltage U_s at AC 50Hz

0 - 0 V

Rated control supply voltage U_s at AC 60Hz
0 - 0 V

Rated control supply voltage U_s at DC
24 - 24 V

Voltage type for actuating
DC

Integrated motor overload protection
Yes

Release class
Adjustable

Degree of protection (IP)
IP00

Degree of protection (NEMA)
Other

APPROVALS

Product Standards
IEC/EN 60947-4-2; UL 508; CE marking

UL File No.
E202571

UL Category Control No.
NMFT

North America Certification
UL listed

Suitable for
Branch Circuits, not as BCPD

Max. Voltage Rating

690 Vac

Degree of Protection
IP20 with kit

DIMENSIONS



