

Mer om 33511

- [Karakteristikk](#)
- [Download & Dokumenter](#)

Discover your Schneider-
Electric tools

**33511**
Micrologic 5.0

EI-nummer: 4320541

EAN: 3303430335115

[Last ned produktdatablad for 33511](#) [3D CAD Modell](#)**Karakteristikk****Teknisk informasjon**

Serie	Compact
Produktspekter	ComPact NS1600b...3200 ComPact NS630b...1600
Produkt eller type komponent	Vern
Navn på vern	Micrologic 5.0
Vernteknologi	Elektronisk
Kompatibel med	Compact NS1600b...3200 Compact NS630b...1600
Applikasjon	Distribusjon
Number of poles	4P 3P
Polbeskrivelse	3t 3t + N/2 4t
Vernfunksjoner	Selektivt vern
Beskyttelsestype	Kort-tid kortslutningsvern Overlastvern (lang tid) Momentan kortslutningsvern
Trip unit rating	630 A at 50 °C 800 A at 50 °C 1000 A at 50 °C 1250 A at 50 °C 1600 A at 50 °C 2000 A på 50 °C 2500 A på 50 °C 3200 A på 50 °C
Type nettverk	AC
Nettverksfrekvens	50/60 Hz
Circuit breaker mounting mode	Utrekkbar Fast

Komplementær

Long-time pick-up adjustment type Ir (thermal protection)	Justerbar 9 innstillinger
[Ir] long-time protection pick-up adjustment range	0.4...1 x In
Long-time protection delay adjustment type tr	Justerbar 9 innstillinger

[tr] long-time protection delay adjustment range	0.7...16.6 s at 7.2 x Ir 0.5...24 s at 6 x Ir 12.5...600 s at 1.5 x Ir
Termisk minne	20 mn
Short-time protection pick-up adjustment type Isd	Justerbar 9 innstillinger
[Isd] Short-time protection pick-up adjustment range	1.5...10 x Ir
Short-time protection delay adjustment type tsd	Justerbar
[tsd] Short-time protection delay adjustment range	0...0,4 s I _Δ =off 0,1...0,4 s I _Δ =on
Instantaneous protection pick-up adjustment type li	Justerbar 9 innstillinger
[li] instantaneous protection pick-up adjustment range	2...15 x In AV
Jordfeilbeskyttelse	Uten
Lokal varslng	Elektrisk feil: 3 LEDs (rød) Innvendig feil: 1 LED (rød)
Miljø	
Omgivelsestemperatur drift	-25...70 °C
Omgivelsestemperatur for lagring	-50...85 °C
Packing Units	
Enhetsstype forpakning 1	PCE
Antall enheter forpakning 1	1
Forpakning 1 vekt	190 g
Forpakning 1 høyde	6,9 cm
Forpakning 1 bredde	8 cm
Forpakning 1 lengde	21,5 cm
Offer Sustainability	
Produktets miljøstatus	Green Premium miljømerket produkt
REACH-regelverk	REACH-erklæring
EU RoHS-direktiv	I samsvar EU RoHS-erklæring
Kvikksølv fri	Ja
Informasjon om RoHS-unntak	Ja
Kinas RoHS-forskrift	Kinas RoHS-erklæring
PVC-fri	Ja
Garantiperiode	
Garanti	18 months