



Oversikt

Presentasjon	High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions.
Leveringstid	Usually in Stock

General

Inkludert utstyr	CD with software User manual USB cable
Number of tare power	40 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Physical

Number of rack unit	4U
Dybde	63,2 cm
Høyde	8,6 cm
Vekt	27 kg
Monteringsmetode	Rack-mounted
USB compatible	No
Bredde	43,7 cm

Input

Network frequency	40...70 Hz
Plug standard	IEC 60320 C14
Input voltage limits	110...285 V half load 160...280 V full load
Inputvolt_other	220 V 240 V
Verntype på inngang	Circuit breaker and fuse
Antall kabler	1
Forsyningsspenning	230 V

Output

Merkeeffekt i W	2400 W
Maximum configurable power in W	2400 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Output voltage	220 V 240 V
Crest faktor	3:1

UPS type	Double conversion online
Wave type	Sine wave
Nb of power socket outlets	6 IEC 60320 C13 1 IEC 60320 C19
Bypass type	Internal bypass (automatic and manual)
Half load runtime	00:13:00 1200 W
Output voltage	230 V
Maximum configurable power in VA	3000 VA
Merkeffekt VA	3000 VA
Runtime at 600W	00:31:00

Conformance

Produktsertifikater	CE
Standarder	IEC 62040-1-1 IEC 62040-1-2

Environmental

Omgivelsestemperatur drift	0...40 °C
Relativ fuktighet	0...95 % ikke-kondenserende
Driftshøyde	0...3000 m
Omgivelsestemperatur for lagring	-20...50 °C
Storage Relative Humidity	0...95 % Ikke-kondenserende
Storage altitude	0...15000 m

Batteries & Runtime

Batteritype	Bly-syre batteri
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	4 t
Liquid value	0
Battery curve	D
Battery charger power	234 W rated
Battery option	SRVS72RLBP-9A 1 1878 VAh SRVS72RLBP-9A 2 2817 VAh SRVS72RLBP-9A 3 3756 VAh SRVS72RLBP-9A 4 4695 VAh

Communications & Management

Control panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rate	600 J
-------------------	-------

Packing Units

Forpakning 1 vekt	31,7 kg
Forpakning 1 høyde	22,9 cm
Forpakning 1 bredde	56,9 cm
Forpakning 1 lengde	79,5 cm

Garantiperiode

Garanti	2 years repair or replace
---------	---------------------------