



Oversikt

Presentasjon	Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
Leveringstid	Usually in Stock

General

Inkludert utstyr	CD with software Documentation CD USB cable
Product web sub-family	Entry level
Number of tare power	45 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Physical

Farge	Black
Dybde	43,9 cm
Høyde	21,9 cm
Montasjeplassering	Front
Mounting preference	No preference
Vekt	17,27 kg
Monteringsmetode	Not rack-mountable
Two post mountable	0
USB compatible	Yes
Bredde	17,1 cm

Input

Network frequency	50/60 Hz +/- 3 Hz auto-sensing
Plug standard	IEC 320 C14
Input voltage limits	170...300 V Justrbar 180...287 V
Inputvolt_other	220 V 240 V
Forsyningsspenning	230 V

Output

Merkeeffekt i W	600 W
Maximum configurable power in W	600 W
Harmonic distortion	Mindre enn 5 % ved full last
Output frequency	50/60 Hz +/- 3 Hz sync to mains
UPS type	Line interactive
Wave type	Sine wave
Nb of power socket outlets	8 IEC 320 C13 2 IEC Jumpers
Output voltage	230 V
Maximum configurable power in VA	1000 VA
Merkeeffekt VA	1000 VA

Conformance

Produktsertifikater	CE CSA GOST VDE EAC
Standarder	UL 1778

Environmental

Omgivelsestemperatur drift	0...40 °C
Relativ fuktighet	0...95 %
Driftshøyde	0...10000 ft
Omgivelsestemperatur for lagring	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0,00...15240,00 m
Akkustikknivå	41 dBA
Varmeavgivelse	100 Btu/t

Batteries & Runtime

Batteritype	Bly-syre batteri
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 t
Number of battery replacement quantity	1
Liquid value	0
Battery charger power	56 W rated
Battery power in VAH	170 VAh runtime
Batterilevetid	3...5 år
Extended runtime	0

Communications & Management

Ledige plasser	0
Control panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

Surge Protection and Filtering

Surge energy rate	455 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Packing Units

Forpakning 1 vekt	19,55 kg
Forpakning 1 høyde	37,6 cm
Forpakning 1 bredde	32,8 cm
Forpakning 1 lengde	59,5 cm
Antall enheter forpakning 2	1
Antall enheter forpakning 3	18

Offer Sustainability

Produktets miljøstatus	Green Premium miljømerket produkt
REACH-regelverk	REACH-erklæring
EU RoHS-direktiv	I samsvar EU RoHS-erklæring
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	Ja
Miljøinformasjon	Produktmiljøprofil
Produktets livssyklus	Informasjon Om Levetidsslutt
WEEE	Innen EU må produktet avhendes i henhold til bestemte regler for avfallshåndtering og aldri kastes som husholdningsavfall.
Optimalisert energieffektivitet	Energieffektivt produkt
Take-back	Take-back program available

Garantiperiode

Garanti	2 years repair or replace
---------	---------------------------