

Select your language

- [German](#)
- [English](#)
- [Spanish](#)
- [French](#)
- [Dutch](#)
- [Italian](#)
- [Polish](#)
- [Czech](#)
- [Russian](#)
- [Norwegian Bokmål](#)

Worldwide English



CI-K1H-95-TS - Insulated enclosure, HxWxD=120x80x95mm, +mounting rail



105853 CI-K1H-95-TS

[Overview](#) [Specifications](#) [Resources](#)



105853 CI-K1H-95-TS

Insulated enclosure, HxWxD=120x80x95mm, +mounting rail

EL-Nummer (Norway)

4138020

Insulated enclosure, With mounting rail to IEC/EN 60715, Product range: CI-K small enclosures, Basic enclosures, Single unit, Degree of Protection: Front IP65, IP65, with push-through cable entry, Material: Glass-fibre reinforced polycarbonate, Colour: Enclosure base RAL 9005, black, Operator only RAL 7035, light gray, Description: Metric cable entry knockouts top, bottom and in the back plate, Lamp indicator L-... can be mounted in base knock-out M20/M25, Cable entry: hard knockout version, Dimensions Width: 80 mm, Height: 120 mm, Depth: 95 mm, Mounting depth for mounting rail 7.5 mm height: 72 mm, Standards: IEC/EN 60529, DIN EN 62208

• [Delivery program](#)

• [Technical data](#)

• [Design verification as per IEC/EN 61439](#)

• [Technical data ETIM 7.0](#)

• [Dimensions](#)

Delivery program

Product range

CI-K small enclosures

Basic function

Basic enclosures

Product function

CI-K empty enclosures

Single unit/Complete unit

Single unit

Degree of Protection

Front IP65

IP65, with push-through cable entry

Degree of Protection

Front IP65

IP65, with push-through cable entry

Material

Glass-fibre reinforced polycarbonate

Colour

Enclosure base RAL 9005, black

Operator only RAL 7035, light gray

Description

Metric cable entry knockouts top, bottom and in the back plate


Lamp indicator L-... can be mounted in base knock-out M20/M25

Cable entry

hard knockout version


Dimensions

Width
80 mm
Height
120 mm
Depth
95 mm
Dimensions



Enclosure depth
Legend for the graphic
Dimensions from top:

Mounting depth with mounting plate
Mounting depth for mounting rail 7.5 mm height
Mounting depth for mounting rail 15 mm height
Enclosure depth



Mounting depth for mounting rail 7.5 mm height
72 mm

Features
With mounting rail to IEC/EN 60715

Notes

L
Knockouts
2 X M20 or push-through membrane up to max. □ 12 mm
S
Back plate:
2 x push-through membrane up to max. □ 8mm

Technical data

General
Standards
IEC/EN 60529
DIN EN 62208
Climatic proofing
Damp heat, constant, to IEC 60068-2-78
Damp heat, cyclic, to IEC 60068-2-30
Ambient temperature
-25 - +70
-25 - +40 (with push-through cable entry) °C
Degree of Protection
Front IP65
IP65, with push-through cable entry
Power lossMax. radiated heat dissipation with separate mounting, ambient air temperature +20 °C
10 W
Material characteristics
MaterialBase
Glass-fibre reinforced polycarbonate
MaterialCover
Glass-fibre reinforced polycarbonate

Surface treatment
 Resistant to corrosion
 ColourBase
 RAL 9005, black (matt)
 ColourHousing body
 Enclosure cover RAL 7035, light grey (matt)
 Material properties
 ElectricalTrack resistance
 CTI 175 (base, to IEC 60112)
 CTI 175 (cover, to IEC 60112)
 ElectricalSurface resistance to IEC 60093
 $1 \Omega \times 10^{13}$
 ElectricalDielectric strength to IEC 60243-1
 30 kV/mm
 ThermalTemperature resistant
 -40 °C - 120 °C (enclosure)
 -40 °C - +80 °C (gasket)
 MechanicalImpact resistance
 IK04 according to EN 50102
 Mechanicalmax. assembly weightsMounting plate
 0.5 kg
 Mechanicalmax. assembly weightsMounting rail
 0.5 kg
 Chemical resistanceChemical resistant
 Base, Cover
 Resistant against: Acids < 10 %, mineral oil, alcohol, gasoline, greases, salt solutions
 Partly resistant to: Acids > 10 %, alcohol
 Not resistant to: alkalis, benzene
 Push-through membrane (Cl-K1/Cl-K2) and sealing material
 Resistant against: Acids < 10 %, alkalis, benzene, salt solutions
 Partly resistant to: Acids > 10 %, greases, benzene
 Not resistant to: Mineral oil, benzene
 AtmosphericSaline spray
 IEC 60068-2-11
 AtmosphericUV resistance
 Beneath protective shield
 AtmosphericWater consumption to DIN EN ISO 62
 0.29 %
 Flammability characteristicsGlow wire testFlammability characteristics
 960 °C/1mm thickness (base, cover; glow wire to VDE 0471 Part 2)
 650 °C/1mm thick (push-through membrane and seal material) to VDE 0471 Part 2)
 Flammability characteristicsGlow wire testto UL 94
 V0/1.5 mm thickness
 Flammability characteristicsGlow wire testto UL 94
 HB
 Flammability characteristicsHalogen free
 Yes

Design verification as per IEC/EN 61439

Technical data for design verification
 Operating ambient temperature min.
 -25 °C
 Operating ambient temperature max.
 +70 °C
 Degree of Protection
 Front IP65
 IP65, with push-through cable entry
 Max. radiated heat dissipation with separate mounting, ambient air temperature +20 °C
 10 W
 Flammability characteristics
 960 °C/1mm thickness (base, cover; glow wire to VDE 0471 Part 2)
 650 °C/1mm thick (push-through membrane and seal material) to VDE 0471 Part 2)
 Track resistance
 CTI 175 (base, to IEC 60112)
 CTI 175 (cover, to IEC 60112)
 Surface treatment
 Resistant to corrosion
 Impact resistance

IK04 according to EN 50102

Temperature resistant

-40 °C - 120 °C (enclosure)

-40 °C - +80 °C (gasket)

UV resistance

Beneath protective shield

IEC/EN 61439 design verification

10.2 Strength of materials and parts 10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.4 Resistance to ultra-violet (UV) radiation

Please enquire

10.2 Strength of materials and parts 10.2.5 Lifting

Not applicable.

10.2 Strength of materials and parts 10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.4 Testing of enclosures made of insulating material

Meets the product standard's requirements.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Empty enclosure for switchgear (EC000712)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Empty housing for switch devices (ecl@ss10.0.1-27-37-13-01 [AKN343014])

Material housing

Plastic

Width

80 mm

Height

137 mm

Depth

95 mm

With transparent cover

No

Suitable for emergency stop

No

Model
Surface mounting
Degree of protection (IP)
IP65
Degree of protection (NEMA)
Other

Dimensions

CAD data

- [Product-specific CAD data](#)
(Web)
- [3D Preview](#)
(Web)

DWG files

- [DA-CD-ci_k1_ts](#)
File
(Web)



edz files

- [DA-CE-ETN.Q-K1H-95-TS](#)
File
(Web)

Step files

- [DA-CS-ci_k_ts_2](#)
File
(Web)

Dimensions single product

- 
[461N002](#)
Line drawing
Mounting depth
- 
[461N003](#)
Line drawing
Mounting depth
- ☐ [461X001](#)
Line drawing
Small enclosures

3D drawing

- ☐ [321I025](#)
Line drawing
C-K device view

Product photo



1150PIC-1385

Photo

Insulating material small enclosure

Instruction Leaflet

- [Insulated small enclosures \(IL01502081Z\)](#)
Asset
(PDF, multilingual)

Declaration of Conformity

UK

- [C-K General Purpose Enclosures \(DA-DC-00004028\)](#)
Asset
(PDF)

Download-Center

- [Download-Center \(this item\)](#)
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)
Eaton EMEA Download-Center



Generate data sheet in PDF format



Generate data sheet in Excel format



[Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2021 by Eaton Industries GmbH

