

Select your language

- German
- English
- Spanish
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norwegian Bokmål

Worldwide English



CSDS4A4CY2201.5-D - Connection cable, 4p, DC current, coupling M12 flat, plug M12 flat, L=1.5m



136316 CSDS4A4CY2201.5-D

[Overview](#) [Specifications](#) [Resources](#)



## 136316 CSDS4A4CY2201.5-D

Connection cable, 4p, DC current, coupling M12 flat, plug M12 flat, L=1.5m

Alternate Catalog No.

CSDS4A4CY2201P5-D

EL-Nummer (Norway)

4315406

Connecting cable, Basic function: Accessories, Length: 1500 mm, Voltage type: DC, 4 pole, Style output side: Plug, straight, Style input side: Coupling, straight, For use with: DC sensors, 4 pole, 2, 3 or 4-wire connection, M12

- Delivery program

Design verification as per  
IEC/EN 61439

- Technical data ETIM 7.0

- Approvals

### Delivery program

Basic function

Accessories


Accessories

Connecting cables

Length

1500 mm

Pin assignment



Voltage type

DC

Number of poles

4 pole

Style output side

Plug, straight

Style input side

Coupling, straight

For use with

For use with

DC sensors, 4 pole, 2, 3 or 4-wire connection, M12

### Design verification as per IEC/EN 61439

Operating ambient temperature min.

-25 °C

Operating ambient temperature max.

+70 °C

### Technical data ETIM 7.0

Sensors (EG000026) / Sensor-actuator patch cord (EC001855)

Electric engineering, automation, process control engineering / Cable, wire / Ready-made data cable / Assembled sensor actuator-line (ecl@ss10.0.1-27-06-03-11 [AFR601003])

Number of poles

4

Type of electrical connection, field-sided

M12

Type of plug-in contact, field sided

Female (bus)

Positioning cable feed, field-sided

Straight

Type of electrical connection, box-sided

M12

Type of plug-in contact, box-sided

Male (plug)

Positioning cable feed, box-sided

Straight

Cable length

1.5 m

Material of cable sheath

Other

Halogen free

No

Colour cable sheath

Other

With LED indication

No

Screened

No

Type of cable

Multi-core

Vulcanize

No

Material contact body

Other

Material of contact surface

Other

Permitted cable outer temperature after assembling without vibration

40 - 70 °C

Permitted cable outer temperature during assembling/handling

40 - 70 °C

Rated current In

0 A

Rated voltage

0 V

Continuity resistor

0 mOhm

Degree of protection (IP)


Other

## Approvals

Product Standards

CE marking

## Wiring diagram



## Product photo



1360PIC-183  
Photo

## 3D drawing

-   
1360DRV-86  
Line drawing

## Download-Center

- [Download-Center \(this item\)](#)  
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)  
Eaton EMEA Download-Center

 [Generate data sheet in PDF format](#)

 [Generate data sheet in Excel format](#)

 [Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)  
© 2021 by Eaton Industries GmbH