### BOLLARD LIGHTS

## **ALVA**



+ Protected against sea air



Device category	Bollard light
Installation type	Free standing
Installation position	Floor
Protection type	IP65
Dimensions	Height/Depth 940 mm, Ø 170 mm
Diffusor	transparent
Luminous efficacy	74 lm/W
Luminous flux	1270 lm
Rated output P	17 W
Colour temperature	3100 K
In-rush current	12 A/ 57 μs
Permissible ambient temperature	-25 °C+40 °C
Warranty	5 years

### **ACCESSORIES**

#### **MOUNTING**



#### ALVA GROUND ANCHOR


 $Item \ number \ EL10820083$ 

Ground anchor galvanised for installation of bollard lights in concrete foundation or solid ground





### **INSTALLATION VIDEO**





Discover the full potential of the ALVA series.





CATALOGUE 2020/2021



CONTACT US	
Salutation	
Firstname *	
Lastname *	
Company *	
Phone	
E-mail-address*	
Subject *	
Your message *	
Yes, I agree that ESYLUX will inform me about news in the future via newsletter.  I have read and agreed to the privacy policy *	
* Required	

# OTHER PRODUCTS





Solutions

Offices

Education

Health Care **Innovations** Demand-driven Automation Intelligent Lighting Human Centric Lighting Light control with DALI-2 Service Downloads Knowledge Support **ESYLUX Services** Company Vision and mission Experience and quality Corporate responsibility Research and development Cooperations and memberships Awards and prizes References Highlights **ESYLUX Light Control DEFENSOR** COMPACT ESY-Pen ALVA FLAT **ISABELLE Imprint** Privacy policy Privacy settings General terms and conditions | Guarantee

Disclaimer Contact

© 2021 ESYLUX GmbH