EMERGENCY LIGHTS



1 Indoor lighting | Emergencylights | SLX | 24 m/ Flat





SLX EL LED FLAT COVER 8h 24m IR WM





The SLX series emergency lights provide variable LED solutions for indicating escape routes. Whether a classic, robust design, a modern, discreet design or a slim body especially for wall mounting: Due to the modular design concept, there is the right design for almost every requirement for the shared basic housing. In addition to the single-battery

variants, versions for systems with central battery operation are also available.



Rated output P 3 W Permissible ambient temperature 5 °C+35 °C Warranty 5 year ACCESSORIES	Device category	Escape sign light
Protection type Length 388 mm x Width 148 mm x Height/Depth 40 mm Rated output P 3 W Permissible ambient temperature 5 °C+35 °C Warranty 5 year	Installation type	Surface mounting
Dimensions Length 388 mm x Width 148 mm x Height/Depth 46 mm Rated output P 3 W Permissible ambient temperature 5 °C+35 °C Warranty 5 year	Installation position	Wall
Rated output P 3 W Permissible ambient temperature 5 °C+35 °C Warranty 5 year ACCESSORIES	Protection type	IP54
Permissible ambient temperature 5 °C+35 °C Warranty 5 year ACCESSORIES	Dimensions	Length 388 mm x Width 148 mm x Height/Depth 46 mm
Warranty 5 year ACCESSORIES	Rated output P	3 W
ACCESSORIES	Permissible ambient temperature	5 °C+35 °C
	Warranty	5 year
DATTEDV		
BATTERY	BATTERY	

SLX BATTERY NiCd 800mAh





MOUNTING



SLX/ELX MOUNTING FRAME 430 FM

Item number EN10077234

Installation frame for SLX and ELX series, installation hole size 430 x 155 mm $\,$





PROTECTION



SLX/ELX BASKET GUARD WALL

Item number EN10077265

Basket guard for SLX and ELX series, 80 mm high





REMOTE CONTROL



SL REMOTE CONTROL

Item number EN10017704
IR remote control for emergency lights







ESY-Pen

Item number EP10425356

All-in-one device (remote control) for four core functions: (1) Parameterisation, (2) Remote control, (3) Light measurement, (4) Mobile project management





SYMBOL



Item number EN10077500

Symbol set for SLX series, FLAT, 24 m detection range right, left, upwards, downwards







SLX 24 FLAT SYMBOL SET II

Item number EN10077517

Symbol set for SLX series, FLAT, 24 m detection range right upwards, left upwards, right downwards, left downwards









Discover the full potential of the SLX/ELX series.



ESY-PEN AND ESY-APP!



Easy parameterisation, remote control and documentation of all ESYLUX remote controllable products and solutions.







3D-MODEL: SLX

Experience this product in the



CONTACT US
Salutation
Firstname *
Lastname *
Company *
Phone
E-mail-address*
Subject *
Your message *
Yes, I agree that ESYLUX will inform me about news in the future via newsletter. I have read and agreed to the privacy policy *
* Required

SIMILAR PRODUCTS

OTHER PRODUCTS





Solutions

Offices

Education

Health Care Innovations

Demand-driven Automation

Intelligent Lighting

Human Centric Lighting

Light control with DALI-2

Service

Downloads

Knowledge

Support

ESYLUX Services

Company

Vision and mission

Experience and quality

Corporate responsibility

Research and development

Cooperations and memberships

Awards and prizes

References

Highlights

ESYLUX Light Control

DEFENSOR

COMPACT

ESY-Pen

ALVA
FLAT
ISABELLE

Imprint | Privacy policy | Privacy settings | Ceneral terms and conditions | Guarantee | Disclaimer | Contact | Conta