

Mer om 47298

- [Karakteristikk](#)
- [Download & Dokumenter](#)

Discover your Schneider-
Electric tools



47298

Micrologic 6.0 P For Uttrekkbar Bryter

EI-nummer: 4322055

EAN: 3303430472988



Last ned produktdatablad for 47298



3D CAD Modell

Karakteristikk

Teknisk informasjon

Serie	Masterpact
Produktspekter	Masterpact NT
Produkt eller type komponent	Vern
Navn på vern	Micrologic 6.0 P
Vernteknologi	Elektronisk
Kompatibel med	Masterpact NT06...16
Applikasjon	Distribusjon
Number of poles	3P 4P
Polbeskrivelse	4t 3t 3t + N/2
Vernfunksjoner	Selektiv + jordfeilvern
Beskyttelsestype	For overload protection (long time) For short time short-circuit protection For instantaneous short-circuit protection For earth fault
Trip unit rating	630 A at 50 °C 800 A at 50 °C 1000 A at 50 °C 1250 A at 50 °C 1600 A at 50 °C
Type nettverk	AC
Nettverksfrekvens	50/60 Hz
Circuit breaker mounting mode	Uttrekkbar

Komplementær

Long-time pick-up adjustment type Ir (thermal protection)	Justerbar 9 innstillinger
[Ir] long-time protection pick-up adjustment range	0.4...1 x In
Long-time protection delay adjustment type tr	Justerbar 9 innstillinger
[tr] long-time protection delay adjustment range	0.7...16.6 s at 7.2 x Ir 0.7...24 s at 6 x Ir 12.5...600 s at 1.5 x Ir
Termisk minne	20 mn
Short-time protection pick-up adjustment type Isd	Justerbar 9 innstillinger

[Isd] Short-time protection pick-up adjustment range	1.5...10 x Ir
Short-time protection delay adjustment type tsd	Justerbar
[tsd] Short-time protection delay adjustment range	0...0.4 s I _{Δt} =off 0.1...0.4 s I _{Δt} =on
Instantaneous protection pick-up adjustment type li	Justerbar 9 innstillinger
[li] instantaneous protection pick-up adjustment range	2...15 x In Off
Ground-fault protection pick-up adjustment type Ig	9 justerbare innstillinger
[Ig] ground-fault protection pick-up adjustment range	0.2...1 x In for 400 A < In < 1250 A 0.3...1 x In for In ≤ 400 A 500...1200 A for In ≥ 1250 A
Ground-fault protection time delay adjustment type tg	Justrbar
[tg] ground-fault protection time delay adjustment range	0...0.4 s I _{Δt} =off 0.1...0.4 s I _{Δt} =on
Jordfeilbeskyttelse	Uten
Zone selektiv forrigling (logisk selektivitet) ZSI	Med
Lokal varslng	3 LEDs (red) for electrical fault 1 LED (red) for internal error
Skjermtype	Digitalt display
Type måling	Effektmåler
Datakommunikasjon	Measurement readout Vem og alarm innstillinger Vedlikeholdsindikatorer
Miljø	
Omgivelsestemperatur drift	-25...70 °C
Omgivelsestemperatur for lagring	-40...85 °C
Packing Units	
Enhets type forpakning 1	PCE
Antall enheter forpakning 1	1
Forpakning 1 vekt	449 g
Forpakning 1 høyde	6,7 cm
Forpakning 1 bredde	7,9 cm
Forpakning 1 lengde	21,5 cm
Offer Sustainability	
REACH-regelverk	REACH-erklæring
EU RoHS-direktiv	I samsvar EU RoHS-erklæring
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	Ja
Kinas RoHS-forskrift	Kinas RoHS-erklæring
PVC-fri	Ja

Contractual warranty

Garanti

18 months