

Mer om 33505

- [Karakteristikk](#)
- [Download & Dokumenter](#)

Discover your Schneider-
Electric tools

**33505****Micrologic 2.0A For Fast Compact NS**

EI-nummer: 4320540

EAN: 3303430335054



Last ned produktdatablad for 33505



3D CAD Modell

Karakteristikk**Teknisk informasjon**

Serie	Compact
Produktspekter	ComPact NS1600b...3200 ComPact NS630b...1600
Produkt eller type komponent	Vern
Navn på vern	Micrologic 2.0 A
Vernteknologi	Elektronisk
Kompatibel med	Compact NS1600b...3200 Compact NS630b...1600
Applikasjon	Distribusjon
Number of poles	4P 3P
Polbeskrivelse	3t + N/2 3t 4t
Vernfunksjoner	Standard vern
Beskyttelsestype	For overload protection (long time) For instantaneous short-circuit protection
Trip unit rating	630 A at 50 °C 800 A at 50 °C 1000 A at 50 °C 1250 A at 50 °C 1600 A at 50 °C 2000 A at 50 °C 2500 A at 50 °C 3200 A at 50 °C
Type nettverk	AC
Nettverksfrekvens	50/60 Hz
Circuit breaker mounting mode	Fast

Komplementær

Long-time pick-up adjustment type Ir (thermal protection)	Justerbar 9 innstillinger
[Ir] long-time protection pick-up adjustment range	0.4...1 x In
Long-time protection delay adjustment type tr	Justerbar 9 innstillinger
[tr] long-time protection delay adjustment range	0.7...16.6 s at 7.2 x Ir 0.7...24 s at 6 x Ir 12.5...600 s at 1.5 x Ir

Termisk minne	20 mn
Instantaneous protection pick-up adjustment type II	Justerbar 9 innstillinger
[II] instantaneous protection pick-up adjustment range	1.5...10 x I _r
Jordfeilbeskyttelse	Uten
Zone selektiv forrigling (logisk selektivitet) ZSI	Uten
Lokal varslings	3 LEDs (red) for electrical fault 1 LED (red) for internal error
Skjermtype	Digitalt display
Type måling	Amperemeter
Datakommunikasjon	Measurement readout Vem og alarm innstillinger
Miljø	
Omgivelsestemperatur drift	-25...70 °C
Omgivelsestemperatur for lagring	-40...85 °C
Packing Units	
Enhets type forpakning 1	PCE
Antall enheter forpakning 1	1
Forpakning 1 vekt	265 g
Forpakning 1 høyde	6,8 cm
Forpakning 1 bredde	8 cm
Forpakning 1 lengde	21,5 cm
Offer Sustainability	
Produktets miljøstatus	Green Premium miljømerket produkt
REACH-regelverk	REACH-erklæring
EU RoHS-direktiv	I samsvar EU RoHS-erklæring
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	Ja
Kinas RoHS-forskrift	Kinas RoHS-erklæring
PVC-fri	Ja
Contractual warranty	
Garanti	18 months