

C25N34V160

Effektbryter ComPacT NSX250N -elektronisk
vern-jordfeil-Micrologic 4.2 160A 3p
90kA/230V- 50kA/415V



Teknisk informasjon

Serie	ComPacT new generation
Produktnavn	ComPacT NSX new generation
Produktspekter	ComPacT NSX100...250 new generation
Kortnavn utstyr	NSX250N
Produkt eller type komponent	Earth leakage circuit breaker
Applikasjon	Distribusjon
Antall poler	3P
Polbeskrivelse	3t
[In] merkestrøm	160 A at 40 °C
[Ue] merkespenning	440 V AC 50/60 Hz
Type nettverk	AC
Nettverksfrekvens	50/60 Hz
Egnethet for isolasjon	Yes conforming to EN/IEC 60947-2
Driftskategori	Kategori A
[Icu] rated ultimate short-circuit breaking capacity	90 KA Icu på 220/240 V AC 50/60 Hz i samsvar med IEC 60947-2 50 KA Icu at 380/415 V AC 50/60 Hz conforming to IEC 60947-2 50 KA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2
Performance level	N 50 kA 415 V AC
Navn på vern	Micrologic 4.2
Vernteknologi	Elektronisk
Vernfunksjoner	LSolR
Kontrolltype	Kipp
Circuit breaker mounting mode	Fast

Komplementær

[Ui] isolasjonsspenning	500 V AC 50/60 Hz
[Uimp] Nominell impuls-spenning	8 kV
[Ics] rated service short-circuit breaking capacity	90 KA på 220/240 V AC 50/60 Hz i samsvar med IEC 60947-2 50 KA at 380/415 V AC 50/60 Hz conforming to IEC 60947-2 50 KA at 440 V AC 50/60 Hz conforming to IEC 60947-2
Mekanisk levetid	20000 sykluser
Elektrisk levetid	10000 Cycles at 440 V In 20000 cycles at 440 V In/2
Power losses	10,24 W
Montering	Bakplate
Tilkobling oppe	Front
Tilkobling i bunn	Front
Connection pitch	35 mm
Beskyttelsestype	L : for overload protection (long time) So : for short time short-circuit protection with fixed delay I : for instantaneous short-circuit protection R : for earth-leakage protection
Vernstørrelse	160 A at 40 °C
Long-time pick-up adjustment type Ir (thermal protection)	Justerbar 9 innstillinger

[Ir] long-time protection pick-up adjustment range	63...160 A
Long-time protection delay adjustment type tr	Fast
[tr] long-time protection delay adjustment range	11 S på 7.2 x Ir 16 S på 6 x Ir 400 s på 1.5 x Ir
Termisk minne	20 min før og etter utkobling
Short-time protection pick-up adjustment type Isd	Justerbar
[Isd] Short-time protection pick-up adjustment range	1.5...10 x Ir
Short-time protection delay adjustment type tsd	Fast
[tsd] Short-time protection delay adjustment range	0.02 s
Instantaneous protection pick-up adjustment type li	Fast
[li] instantaneous protection pick-up adjustment range	2400 A
Jordfeilbeskyttelse	Integrert
Jordfeilvern klasse	A-klasse
Earth-leakage protection sensivity adjustment type IΔn	Justrbar
[IΔn] earth-leakage protection sensitivity adjustment range	30 MA 100 MA 300 MA 500 MA 1 A 3 A 5 A
Earth-leakage protection specific mode	AV using the IΔn rotary switch
Earth-leakage protection time delay adjustment type Δt	Justerbar
[Δt] Earth-leakage protection time delay adjustment range	0 Ms 60 Ms 150 Ms 500 Ms 1 s
Number of slots for electrical auxiliaries	5 slot(s)
Lokal varslng	Flashing LED (green) for ready to operate LED 105 % Ir (red) for overload LED 90 % Ir (orange) for overload
Width (W)	105 mm
Height (H)	161 mm
Depth (D)	86 mm
Vekt	2,05 kg

Miljø

Standarder	EN/IEC 60947
Produktsertifikater	CCC EAC Marine
Overspenningskategori	Klasse II
Beskyttelsesklasse for elektrisk støt	Klasse II
Forurensninggrad	3 conforming to IEC 60664-1
IP-grad	IP40 conforming to IEC 60529
IK beskyttelsesklasse	IK07 conforming to IEC 62262
Omgivelsestemperatur drift	-25...70 °C
Omgivelsestemperatur for lagring	-50...85 °C
Relativ fuktighet	0...95 %
Operating altitude	0...2000 m without derating 2000 m...5000 m with derating

Packing Units

Enhetstype forpakning 1	PCE
Antall enheter forpakning 1	1
Forpakning 1 vekt	2,086 kg
Forpakning 1 høyde	13 cm
Forpakning 1 bredde	17 cm
Forpakning 1 lengde	11 cm

Offer Sustainability

REACH-regelverk	 REACH-erklæring
EU RoHS-direktiv	I samsvar  EU RoHS-erklæring
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	 Ja
Kinas RoHS-forskrift	 Kinas RoHS-Erklæring

Contractual warranty

Garanti	18 måneder
---------	------------