

Mer om 48367

- [Karakteristikk](#)
- [Download & Dokumenter](#)

Discover your Schneider-
Electric tools



48367

Micrologic 6.0 H For Uttrekbar Bryter

EI-nummer: 4322839

EAN: 3303430483670



Last ned produktdatablad for 48367



3D CAD Modell

Karakteristikk

Teknisk informasjon

Serie	Masterpact
Produktspekter	Masterpact NW
Produkt eller type komponent	Vern
Navn på vern	Micrologic 6.0 H
Vernteknologi	Elektronisk
Kompatibel med	Masterpact NW08...40 Masterpact NW40b...63 Masterpact NW H10 Masterpact NW H2 korrosjonsbeskyttet
Applikasjon	Distribusjon
Number of poles	3P 4P
Polbeskrivelse	4t 3t 3t + N/2
Vernfunksjoner	Selektiv + jordfeilvern
Beskyttelsestype	For overload protection (long time) For short time short-circuit protection For instantaneous short-circuit protection For earth fault
Trip unit rating	800 A at 50 °C 1000 A at 50 °C 1250 A at 50 °C 1600 A at 50 °C 2000 A at 50 °C 2500 A at 50 °C 3200 A at 50 °C 4000 A at 50 °C 5000 A at 50 °C 6300 A på 50 °C
Type nettverk	AC
Nettverksfrekvens	50/60 Hz
Circuit breaker mounting mode	Uttrekbar

Komplementær

Long-time pick-up adjustment type Ir (thermal protection)	Justerbar 9 innstillinger
[Ir] long-time protection pick-up adjustment range	0.4...1 x In
Long-time protection delay adjustment type tr	Justerbar 9 innstillinger

[tr] long-time protection delay adjustment range	0.7...16.6 s at 7.2 x Ir 0.7...24 s at 6 x Ir 12.5...600 s at 1.5 x Ir
Termisk minne	20 mn
Short-time protection pick-up adjustment type Isd	Justerbar 9 innstillinger
[Isd] Short-time protection pick-up adjustment range	1.5...10 x Ir
Short-time protection delay adjustment type tsd	Justerbar
[tsd] Short-time protection delay adjustment range	0...0.4 s I _Δ t=off 0.1...0.4 s I _Δ t=on
Instantaneous protection pick-up adjustment type li	Justerbar 9 innstillinger
[li] instantaneous protection pick-up adjustment range	Off 2...15 x In
Ground-fault protection pick-up adjustment type Ig	9 justerbare innstillinger
[Ig] ground-fault protection pick-up adjustment range	0.2...1 x In for 400 A < In < 1250 A 0.3...1 x In for In ≤ 400 A 500...1200 A for In ≥ 1250 A
Ground-fault protection time delay adjustment type tg	Justrbar
[tg] ground-fault protection time delay adjustment range	0...0.4 s I _Δ t=off 0.1...0.4 s I _Δ t=on
Jordfeilbeskyttelse	Uten
Zone selektiv forrigling (logisk selektivitet) ZSI	Med
Lokal varslng	3 LEDs (red) for electrical fault 1 LED (red) for internal error
Skjermtype	Digitalt display
Type måling	Måling av overharmoniske Effektmåler
Datakommunikasjon	Measurement readout Vem og alarm innstillinger Vedlikeholdsindikatorer

Miljø

Omgivelsestemperatur drift	-25...70 °C
Omgivelsestemperatur for lagring	-40...85 °C

Packing Units

Enhets type forpakning 1	PCE
Antall enheter forpakning 1	1
Forpakning 1 vekt	1,117 kg
Forpakning 1 høyde	7 cm
Forpakning 1 bredde	8 cm
Forpakning 1 lengde	22 cm

Offer Sustainability

REACH-regelverk	REACH-erklæring
EU RoHS-direktiv	I samsvar EU RoHS-erklæring
Kvikksølvfri	Ja

Informasjon om RoHS-unntak

[!\[\]\(1d3a1175dd4902218e694b9c098adb83_img.jpg\) Ja](#)

Kinas RoHS-forskrift

[!\[\]\(4729e517bc6a7cd81c8025b9646574fb_img.jpg\) Kinas RoHS-erklæring](#)

PVC-fri

Ja

Contractual warranty

Garanti

18 months
