

Select your language

- German
- English
- Spanish
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norwegian Bokmål

Worldwide English



CSDR4A4CY2203-D - Connection cable, 4p, DC current, coupling M12 flat, plug, angled, L=3m



136315 CSDR4A4CY2203-D

[Overview](#) [Specifications](#) [Resources](#)



136315 CSDR4A4CY2203-D

Connection cable, 4p, DC current, coupling M12 flat, plug, angled, L=3m

Alternate Catalog No.

CSDR4A4CY2203-D

EL-Nummer (Norway)

4315405

Connecting cable, Basic function: Accessories, Length: 3000 mm, Voltage type: DC, 4 pole, Style output side: Plug, angled, Style input side: Coupling, straight, For use with: DC sensors, 4 pole, 2, 3 or 4-wire connection, M12

- Delivery program

Design verification as per
IEC/EN 61439

- Technical data ETIM 7.0

- Approvals

Delivery program

Basic function

Accessories


Accessories

Connecting cables

Length

3000 mm

Pin assignment



Voltage type

DC

Number of poles

4 pole

Style output side

Plug, angled

Style input side

Coupling, straight

For use with

For use with

DC sensors, 4 pole, 2, 3 or 4-wire connection, M12

Design verification as per IEC/EN 61439

Operating ambient temperature min.

-25 °C

Operating ambient temperature max.

+70 °C

Technical data ETIM 7.0

Technical data E HM 7.0

Sensors (EG000026) / Sensor-actuator patch cord (EC001855)

Electric engineering, automation, process control engineering / Cable, wire / Ready-made data cable / Assembled sensor actuator-line (ec1@ss10.0.1-27-06-03-11 [AFR601003])

Number of poles

4

Type of electrical connection, field-sided

M12

Type of plug-in contact, field sided

Female (bus)

Positioning cable feed, field-sided

Straight

Type of electrical connection, box-sided

M12

Type of plug-in contact, box-sided

Male (plug)

Positioning cable feed, box-sided

Angled

Cable length

3 m

Material of cable sheath

Other

Halogen free

No

Colour cable sheath

Other

With LED indication

No

Screened

No

Type of cable

Multi-core

Vulcanize

No

Material contact body

Other

Material of contact surface

Other

Permitted cable outer temperature after assembling without vibration

40 - 70 °C

Permitted cable outer temperature during assembling/handling

40 - 70 °C

Rated current In

0 A

Rated voltage

0 V

Continuity resistor

0 mOhm

Degree of protection (IP)


Other

Approvals

Product Standards

CE marking

Wiring diagram



Product photo



3D drawing



Download-Center

- [Download-Center \(this item\)](#)
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)
Eaton EMEA Download-Center

 [Generate data sheet in PDF format](#)

 [Generate data sheet in Excel format](#)

 [Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2021 by Eaton Industries GmbH

