

Select your language

- [German](#)
- [English](#)
- [Spanish](#)
- [French](#)
- [Dutch](#)
- [Italian](#)
- [Polish](#)
- [Czech](#)
- [Russian](#)
- [Norwegian Bokmål](#)

Worldwide English



CSDR4A4CY2202 - Connection cable, 4p, DC current, coupling m12 angled, open end, L=2m



136279 CSDR4A4CY2202

[Overview](#) [Specifications](#) [Resources](#)



## 136279 CSDR4A4CY2202

Connection cable, 4p, DC current, coupling m12 angled, open end, L=2m

Alternate Catalog Nb.

CSDR4A4CY2202

EL-Nummer (Norway)

4315395

Connecting cable, Basic function: Accessories, Range: connecting cables, Length: 2000 mm, Voltage type: DC, 4 pole, Style output side: Cable end, open, Style input side: Coupling, angled, For use with: DC sensors, 4 pole, 2, 3 or 4-wire connection, M12, RS2...-02..., RS2...-11..., RS4-02...

- [Delivery program](#)

Design verification as per  
IEC/EN 61439

- [Technical data ETIM 7.0](#)

- [Approvals](#)

### Delivery program

Basic function

Accessories

Accessories

Connecting cables

Basic function

Accessories


Range

connecting cables

Length

2000 mm

Pin assignment



Voltage type

DC

Number of poles

4 pole

Style output side

Cable end, open

Style input side

Coupling, angled

For use with

For use with

DC sensors, 4 pole, 2, 3 or 4-wire connection, M12

RS2...-02...

RS2...-11...

RS4-02...

### Design verification as per IEC/EN 61439

Operating ambient temperature min.

-25 °C

Operating ambient temperature max.

+70 °C

## Technical data ETIM 7.0

Sensors (EG000026) / Sensor-actuator patch cord (EC001855)

Electric engineering, automation, process control engineering / Cable, wire / Ready-made data cable / Assembled sensor actuator-line (ec1@ss10.0.1-27-06-03-11 [AFR601003])

Number of poles

4

Type of electrical connection, field-sided

M12

Type of plug-in contact, field sided

Female (bus)

Positioning cable feed, field-sided

Angled

Type of electrical connection, box-sided

Other

Type of plug-in contact, box-sided

Positioning cable feed, box-sided

Other

Cable length

2 m

Material of cable sheath

Other

Halogen free

No

Colour cable sheath

Other

With LED indication

No

Screened

No

Type of cable

Multi-core

Vulcanize

No

Material contact body

Other

Material of contact surface

Other

Permitted cable outer temperature after assembling without vibration

40 - 70 °C

Permitted cable outer temperature during assembling/handling

40 - 70 °C

Rated current In

0 A

Rated voltage

0 V

Continuity resistor

0 mOhm

Degree of protection (IP)

Other

## Approvals

Product Standards

CE marking

## Wiring diagram

- 

1 = Brown  
2 = White  
3 = Blue  
4 = Black

1360SW-115

Line drawing

## Product photo

- 

1360PIC-211

Photo

## 3D drawing



1360DRW-85

Line drawing

## Download-Center

- [Download-Center \(this item\)](#)  
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)  
Eaton EMEA Download-Center



[Generate data sheet in PDF format](#)



[Generate data sheet in Excel format](#)



[Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2021 by Eaton Industries GmbH

