



216526
M22-WRS/KC11/I

Overview

Specifications

Resources



Delivery program

Technical data

Design verification as per IEC/EN 61439

Technical data ETIM 7.0

Approvals

Dimensions

DELIVERY PROGRAM

Product range
RMQ-Titan

Basic function
Housing
Key-operated buttons

Mounting hole diameter [□]
22.5 mm

Single unit/Complete unit
Complete unit

Design
Enclosure

maintained

Function: [□ = spring-return]

□ 60°

Connection type
Screw connection

Not suitable for master key systems

2 positions

Number of locations
1 Qty.

Key withdrawable in position

0

1

Colour

Enclosure covers
Grey

RAL Value
RAL 7035

light grey, RAL 7035

Degree of Protection
IP66

Front ring
Bezel: titanium

Connection to SmartWire-DT
no

Contacts

NC = Normally closed

1 NC □

NO = Normally open
1 NO

Notes

□ = safety function, by positive opening to IEC/EN
60947-5-1


Actuator travel and actuation force as per DIN EN 60947-5-1, K.5.4.1

[mm]
4.8

Maximum travel [mm]
5.7

Minimum force for positive opening [N]
20

Contact sequence



Instructions

Stay-put/spring-return function, can be changed
with coding parts M22-XC-Y
Key withdraw convertible with coding adapters
M22-XC-...

Information about equipment supplied
With 1 key

TECHNICAL DATA

General

Standards
IEC/EN 60947
VDE 0660

Lifespan, mechanical [Operations]
> 0.1 x 10⁶

Operating frequency [Operations/h]
 100

Operating torque
 0.5 Nm

Climatic proofing
Damp heat, constant, to IEC 60068-2-78
Damp heat, cyclic, to IEC 60068-2-30

Degree of Protection
IP66

Ambient temperature
Open
-25 - +70 °C

Mounting position
As required

Mechanical shock resistance
30
Shock duration 11 ms
Sinusoidal
according to IEC 60068-2-27 g

Cable entry knockouts
Base
2 x 16 Quantity x M...

Cable entry knockouts
Sides
1 x 20
2 x 25/20 Quantity x M...

shipping classification
DNV
GL
LR



Germanischer Lloyd



Contacts

Rated conditional short-circuit current [I_q]
1 kA

DESIGN VERIFICATION AS PER IEC/EN 61439

Technical data for design verification

Rated operational current for specified heat
dissipation [I_r]
6 A

Heat dissipation per pole, current-dependent [P_{id}]
0.11 W

Equipment heat dissipation, current-dependent
[P_{id}]
0 W

Static heat dissipation, non-current-dependent [P_{is}]
0 W

Heat dissipation capacity [P_{diss}]
0 W

Operating ambient temperature min.
-25 °C

Operating ambient temperature max.
+70 °C

IEC/EN 61439 design verification

10.2 Strength of materials and parts
10.2.2 Corrosion resistance
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.3.1 Verification of thermal stability of
enclosures

Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.3.2 Verification of resistance of insulating materials to normal heat
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.4 Resistance to ultra-violet (UV) radiation
Please enquire

10.2 Strength of materials and parts
10.2.5 Lifting
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts
10.2.6 Mechanical impact
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts
10.2.7 Inscriptions
Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES
Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances
Meets the product standard's requirements.

10.5 Protection against electric shock
Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components
Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors
Is the panel builder's responsibility.

10.9 Insulation properties
10.9.2 Power-frequency electric strength
Is the panel builder's responsibility.

10.9 Insulation properties
10.9.3 Impulse withstand voltage
Is the panel builder's responsibility.

10.9 Insulation properties
10.9.4 Testing of enclosures made of insulating material
Is the panel builder's responsibility.

10.10 Temperature rise
The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function
The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

TECHNICAL DATA ETIM 7.0

Low-voltage industrial components (EG000017) / Control circuit devices combination in enclosure (EC000225)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Command and alarm device combination in housing (ecl@ss10.0.1-27-37-12-16 [AKF034014])

Number of command positions

1

Number of push buttons

0

Number of indicator lights

0

Number of key switches

1

Number of selector switches

1

Number of mushroom-shaped push-buttons

0

Suitable for emergency stop

No

Rated control supply voltage U_s at AC 50HZ

115 - 500 V

Rated control supply voltage U_s at AC 60HZ

115 - 500 V

Rated control supply voltage U_s at DC

24 - 220 V

Colour housing cover

Grey

Material housing

Plastic

Number of contacts as normally open contact

1

Number of contacts as normally closed contact

1

