


Mer om SUA750I

- [Karakteristikk](#)
- [Download & Dokumenter](#)

Discover your Schneider-
Electric tools

**SUA750I**
APC Smart-UPS 750VA USB & Serial 230V

EI-nummer: 6605212

EAN: 0731304212683



Last ned produktdatablad for SUA750I

Karakteristikk

Overview

Presentasjon	Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
Leveringstid	Usually in Stock

General

Inkludert utstyr	CD with software Smart UPS signalling RS-232 cable User manual USB kabel
Number of tare power	15 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Physical

Number of rack unit	0U
Farge	Black
Dybde	36,1 cm
Høyde	15,7 cm
Montasjeplassering	Front
Mounting preference	No preference
Vekt	13,18 kg
Monteringsmetode	Not rack-mountable
Two post mountable	0
USB compatible	Yes
Bredde	13,7 cm

Input

Network frequency	50/60 Hz +/- 3 Hz automatisk gjenkjenning
Plug standard	IEC 320 C14
Input voltage limits	151...302 V Justbar 160...286 V

Forsyningsspenning	230 V
Output	
Merkeeffekt i W	500 W
Maximum configurable power in W	500 W
Harmonic distortion	Mindre enn 5 % ved full last
Output frequency	47...53 Hz for 50 Hz nominal sync to mains 57...63 Hz for 60 Hz nominal sync to mains
Crest faktor	Opp til 5: 1
UPS type	Line interactive
Wave type	Sine wave
Nb of power socket outlets	6 IEC 320 C13 2 IEC Jumpers
Output voltage	230 V
Maximum configurable power in VA	750 VA
Merkeeffekt VA	750 VA
Transfer time	2 ms typical
Conformance	
Produktsertifikater	C-Tick CE GOST VDE
Standarder	EN 50091-1 EN 50091-2 EN 55022 klasse A IEC 60950
Environmental	
Omgivelsestemperatur drift	0..40 °C
Relativ fuktighet	0..95 %
Driftshøyde	0...10000 ft
Omgivelsestemperatur for lagring	-15..45 °C
Storage Relative Humidity	0..95 %
Storage altitude	0,00...15240,00 m
Akkustikknivå	40 dBA
Varmeavgivelse	90 Btu/t
Batteries & Runtime	
Batteritype	Bly-syre batteri
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 t
Number of battery replacement quantity	1
Tilleggsinformasjon	Configurable for 220 : 230 or 240 nominal output voltage
Liquid value	0
Batterispenningen	24 V
Kapasitet på batteri	7,0 Ah

Battery charger power	50 W rated
Battery power in VAh	149 VAh runtime
Batterilevetid	3..5 år
Extended runtime	0
Communications & Management	
Ledige plasser	1
Control panel	LED status display with load and battery bar-graphs and on line : on battery : replace battery : and overload indicators
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
Emergency power off	Optional
Surge Protection and Filtering	
Surge energy rate	340 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449
Packing Units	
Forpakning 1 vekt	14,55 kg
Forpakning 1 høyde	29 cm
Forpakning 1 bredde	27 cm
Forpakning 1 lengde	50 cm
Antall enheter forpakning 2	1
Antall enheter forpakning 3	24
Contractual warranty	
Garanti	2 years repair or replace