



266121  
LSE-11

Overview

Specifications

Resources



Delivery program

Technical data

Design verification as per IEC/EN 61439

Technical data ETIM 7.0

Approvals

Dimensions

## DELIVERY PROGRAM

Basic function  
Position switches  
Safety position switches

Part group reference  
LSE

Product range  
Position switch with electronically adjustable operating point

Degree of Protection  
IP66, IP67

Features  
Basic device, expandable

Ambient temperature  
-25 - +70 °C

Description

Visual status indication  
comparable with positive opening function  
Device goes into safe state on high interference.  
Can be used in safety circuits  
partly short-circuit proof  
Restart after reset  
Individual operating point adjustment

Approval




## Contacts

NO = Normally open  
1 NO

NC = Normally closed  
1 NC

Contact sequence



Contact travel ■ = Contact closed □ = Contact open



Rated voltage [ $U_e$ ]  
12 - 30 V DC

## Colour

Enclosure covers  
Yellow

Enclosure covers



Housing  
Insulated material

Connection type  
Cage Clamp

#### Notes

Cage-Clamp is a registered trademark of Wago Kontakttechnik, 32432 Minden, Germany.  
Accessories for the Cage-Clamp terminals from Wago: power comb, gray, Wago Article No. 264-402

## TECHNICAL DATA

### General

Standards  
IEC/EN 60947  
EN 61000-4

Climatic proofing  
Damp heat, constant, to IEC 60068-2-78; damp heat, cyclical, to IEC 60068-2-30

Ambient temperature  
-25 - +70 °C

Mounting position  
As required

Degree of Protection  
IP66, IP67

Terminal capacities  
Solid  
1 x (0.5 - 2.5) mm<sup>2</sup>

Terminal capacities  
Flexible with ferrule  
1 x (0.5 - 1.5) mm<sup>2</sup>

Repetition accuracy  
0.02 mm

### Power supply

Rated voltage [ $U_e$ ]  
12 - 30 V DC

Rated operational current [ $I_e$ ]  
12 V [ $I_e$ ]  
0.015 A

Rated operational current [ $I_e$ ]  
24 V [ $I_e$ ]  
18 mA

Rated operational current [ $I_e$ ]  
30 V [ $I_e$ ]  
0.019 A

### Contacts/switching capacity

Overvoltage category/pollution degree  
III/3

Rated operational current [ $I_e$ ]  
DC-13  
24 V [ $I_e$ ]  
0.2 A

### Mechanical variables

Lifespan, mechanical [Operations]  
 $3 \times 10^6$

**Notes**  
(electronic)

Contact temperature of roller head  
 100 °C

Mechanical shock resistance (half-sinusoidal  
shock, 20 ms)  
Basic unit  
30 g

Operating frequency [Operations/h]  
 3000

Switching point  
0.5 - 5.5 mm, freely adjustable

Hysteresis  
0.4 mm

Contact sequence (contact closed open Zw =  
positive opening clearance)  
0.04 mm

## Actuation

Mechanical  
Actuating force at beginning/end of stroke  
3.5/8.0 N

Mechanical  
Actuating torque of rotary drives  
0.2 Nm

Mechanical  
Max. operating speed with DIN cam  
1/0.5 m/s

Mechanical  
**Notes**  
for angle of actuation  $\alpha = 0^\circ/30^\circ$

## Electromagnetic compatibility (EMC)

Electrostatic discharge (IEC/EN 61000-4-2, Level 3,  
ESD)  
Air discharge  
8 kV

Electrostatic discharge (IEC/EN 61000-4-2, Level 3,  
ESD)  
Contact discharge  
4 kV

Electromagnetic fields (RFI) to IEC/EN 61000-4-3  
10 V/m

Burst Impulse (IEC/EN 61000-4-4, Level 3)  
Supply cable  
2 kV

Burst Impulse (IEC/EN 61000-4-4, Level 3)  
Signal lines  
2 kV

Power pulses (surge) (IEC/EN 61000-4-5)  
0.5 kV

Immunity to line-conducted interference to (IEC/EN  
61000-4-6)  
10 V

## DESIGN VERIFICATION AS PER IEC/EN 61439

### Technical data for design verification

Rated operational current for specified heat  
dissipation [ $I_r$ ]  
0.2 A

Heat dissipation per pole, current-dependent [ $P_{id}$ ]  
0.15 W

Equipment heat dissipation, current-dependent  
[ $P_{id}$ ]  
0 W

Static heat dissipation, non-current-dependent [ $P_{is}$ ]  
0.4 W

Heat dissipation capacity [ $P_{diss}$ ]  
0 W

Operating ambient temperature min.  
-25 °C

Operating ambient temperature max.  
+70 °C

### IEC/EN 61439 design verification

10.2 Strength of materials and parts

10.2.2 Corrosion resistance  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.3.1 Verification of thermal stability of enclosures  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.3.2 Verification of resistance of insulating materials to normal heat  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.4 Resistance to ultra-violet (UV) radiation  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.5 Lifting  
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts  
10.2.6 Mechanical impact  
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts  
10.2.7 Inscriptions  
Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES  
Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances  
Meets the product standard's requirements.

10.5 Protection against electric shock  
Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and

components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9 Insulation properties

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9 Insulation properties

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9 Insulation properties

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## TECHNICAL DATA ETIM 7.0

Electric engineering, automation, process control engineering / Binary sensor technology, safety-related sensor technology / Position switch / Position switch (Type 1) (ecl@ss10.0.1-27-27-06-01 [AGZ382015])

Width sensor  
31 mm

Diameter sensor  
0 mm

Height of sensor  
61 mm

Length of sensor  
33.5 mm

Rated operation current  $I_e$  at AC-15, 24 V  
0 A

Rated operation current  $I_e$  at AC-15, 125 V  
0 A

Rated operation current  $I_e$  at AC-15, 230 V  
0 A

Rated operation current  $I_e$  at DC-13, 24 V  
0.2 A

Rated operation current  $I_e$  at DC-13, 125 V  
0 A

Rated operation current  $I_e$  at DC-13, 230 V  
0 A

Switching function  
Slow-action switch

Switching function latching  
No

Output electronic  
Yes

Forced opening  
No

Number of safety auxiliary contacts  
0

Number of contacts as normally closed contact  
1

Number of contacts as normally open contact  
1

Number of contacts as change-over contact  
0

Type of interface  
None

Type of interface for safety communication  
None

Construction type housing  
Cuboid

Material housing  
Plastic

Coating housing  
Other

Type of control element  
Flunger

Alignment of the control element  
Other

Type of electric connection  
Other

With status indication  
Yes

Suitable for safety functions

Yes

Explosion safety category for gas  
None

Explosion safety category for dust  
None

Ambient temperature during operating  
25 - 70 °C

Degree of protection (IP)  
IP67

Degree of protection (NEMA)  
4X

## APPROVALS

Product Standards  
IEC/EN 60947-5; UL 508; CSA-C22.2 No. 14; CE  
marking

UL File No.  
E29184

UL Category Control No.  
NKCR

CSA File No.  
12528

CSA Class No.  
3211-03

North America Certification  
UL listed, CSA certified

Degree of Protection  
IEC: IP66, 67, UL/CSA Type 3R, 4X (indoor use  
only), 12, 13

## DIMENSIONS

- Tightening torque of cover screws: 0.8 Nm±0.2 Nm
  - only with LS (insulated version)
  - Fixing screws 2 x M4  30
- $M_A = 1.5 \text{ Nm}$

