

Select your language

- [German](#)
- [English](#)
- [Spanish](#)
- [French](#)
- [Dutch](#)
- [Italian](#)
- [Polish](#)
- [Czech](#)
- [Russian](#)
- [Norwegian Bokmål](#)

Worldwide English



LSM-XLA - Angled roller lever, metal



266157 LSM-XLA

[Overview](#) [Specifications](#) [Resources](#)



- [Delivery program](#)
- [Design verification as per IEC/EN 61439](#)
- [Technical data ETIM 7.0](#)
- [Approvals](#)
- [Dimensions](#)

266157 LSM-XLA

Angled roller lever, metal

Alternate Catalog No.

EL-Nummer (Norway)

LSM-XLA

4356158

Operating head for LS-Titan position switch, IEC EN 60947-5-1, high degree of protection IP66, device for world markets, modular system, easy mounting technology operating heads can be attached in any 4 directions and snapped on simple, quick and safely using the bayonet fitting.

Delivery program

Basic function
Operating heads
Part group reference
LS(M)-...
Product range
Angled roller lever
For use with
Basic devices LS(M)...

Notes

The operating head can be rotated at 90° intervals to adapt to the specified approach direction.

Design verification as per IEC/EN 61439

Technical data for design verification

Rated operational current for specified heat dissipation [I_n]

0 A

Heat dissipation per pole, current-dependent [P_{rd}]

0 W

Equipment heat dissipation, current-dependent [P_{ed}]

0 W

Static heat dissipation, non-current-dependent [P_{vs}]

0 W

Heat dissipation capacity [P_{diss}]

0 W

Operating ambient temperature min.

-25 °C

Operating ambient temperature max.

+70 °C

IEC/EN 61439 design verification

10.2 Strength of materials and parts 10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.1 Verification of thermal stability of enclosures

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Square roller lever

UL listed, CSA certified

CAD data

- [Product-specific CAD data](#)
(Web)
- [3D Preview](#)
(Web)


DWG files

- [DA-CD-Is_xla](#)
File
(Web)

Step files

- [DA-CS-Is_xla](#)
File
(Web)

Dimensions single product

- 
[131X115](#)
Line drawing
Angled roller lever

3D drawing

- 
[131I183](#)
Line drawing
Angled roller lever

Product photo

- 
[1310PIC-39](#)
Photo
Angled roller lever

Instruction Leaflet

- [Position switch LS-Titan: Basic unit LS\(M\) \(IL053001ZU\)](#)
Asset
(PDF, 07/2021, multilingual)

Declaration of Conformity

EU

- [Limit switch LS-Titan \(DA-DC-00003472\)](#)
Asset
(PDF)

UK

- [Limit switch LS-Titan \(DA-DC-00003963\)](#)

Download-Center

- [Download-Center \(this item\)](#)
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)
Eaton EMEA Download-Center



Generate data sheet in PDF format



Generate data sheet in Excel format



Write a comment

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2021 by Eaton Industries GmbH

