

Item no. 771-9985/207-502

WINSTA® MIDI > pre-assembled connecting cable; Eca;
 Plug/open-ended; 5-pole; Cod. I; H05VV-F 5G 2.5 mm²; 5 m;
 2,50 mm²; blue



Cable assembly WINSTA® MIDI rated current 20 A

Use effective pluggable connections instead of laborious screw connections: With the **WINSTA® MIDI** cable assembly with protection against mismating. On PCBs, in control cabinets or for connecting lights – pluggable installation connectors from **WAGO** allow you to make connections according to a huge variety of requirements in next to no time.

For greater protection in electrical installations, the pluggable installation connector is equipped with mechanical protection against mismating. The pluggable installation connector offers touch-proof protection with live components in accordance with protection type IP20. I coding in blue is used to mark **WINSTA® MIDI** pluggable installation connectors, which are used predominantly in automation of buildings for controlling lighting. This pluggable installation connector can be used for a current load of up to 20 A. Thus, it can also be used for high power loads. The **WINSTA® MIDI** Pluggable Connection System with Push-in **CAGE CLAMP®** spring pressure connection technology facilitates safe electrification. Due to the included test slot, connections can be checked even when they are plugged in. That saves time and reduces installation labor and expense. This product meets all the mandatory fire protection requirements of fire class E; therefore it can be used in domains where fire safety is relevant.

Fast, error-free assembly thanks to cable assemblies from WAGO

A plug and a free end are available. The WINSTA® Pluggable Connection System allows pluggable electrical installation. This saves time, lowers costs, and reduces the need for servicing. Now you can also cut installation costs without compromising quality and safety. The WINSTA® MDI pluggable installation connector with fire class E eliminates the need for servicing and prevents unnecessary downtime.

- protection against mismating eliminates errors
- simple circuits
- with I coding for lighting control (DALI standard)
- exact dimensions
- quick replacement of defective units during ongoing operation

> Global (EN)

> We will be happy to help! ☎ +49 (571) 887-0

