

Select your language

- [German](#)
- [English](#)
- [Spanish](#)
- [French](#)
- [Dutch](#)
- [Italian](#)
- [Polish](#)
- [Czech](#)
- [Russian](#)
- [Norwegian Bokmål](#)

Worldwide English



Powering Business Worldwide

CI-K3-125-TS - Insulated enclosure, HxWxD=200x120x125mm, +mounting rail



206884 CI-K3-125-TS

[Overview](#) [Specifications](#) [Resources](#)



## 206884 CI-K3-125-TS

Insulated enclosure, HxWxD=200x120x125mm, +mounting rail

EL-Nummer (Norway)

4138003

Insulated enclosure, With mounting rail to IEC/EN 60715, Product range: CI-K small enclosures, Basic enclosures, Single unit, Degree of Protection: Front IP65, IP65, with push-through cable entry, Material: Glass-fibre reinforced polycarbonate, Colour: Enclosure base RAL 9005, black, Operator only RAL 7035, light gray, Description: Metric cable entry knockouts top, bottom and in the back plate, Control cable entry, Lamp indicator L-... can be mounted in base knock-out M20/M25, Cable entry: hard knockout version, Dimensions Width: 120 mm, Height: 200 mm, Depth: 125 mm, Mounting depth for mounting rail 7.5 mm height: 93 mm, Standards: IEC/EN 60529, DIN EN 62208

- [Delivery program](#)

- [Technical data](#)

- [Design verification as per IEC/EN 61439](#)

- [Technical data ETIM 7.0](#)

- [Dimensions](#)

### Delivery program

Product range

CI-K small enclosures

Basic function

Basic enclosures

Product function

CI-K empty enclosures

Single unit/Complete unit

Single unit

Degree of Protection

Front IP65

IP65, with push-through cable entry

Degree of Protection

Front IP65

IP65, with push-through cable entry

Material

Glass-fibre reinforced polycarbonate

Colour

Enclosure base RAL 9005, black

Operator only RAL 7035, light gray


Description

Metric cable entry knockouts top, bottom and in the back plate


Control cable entry

Lamp indicator L-... can be mounted in base knock-out M20/M25

Cable entry  
hard knockout version  
Dimensions  
Width  
120 mm  
Height  
200 mm  
Depth  
125 mm  
Dimensions



Enclosure depth  
Legend for the graphic  
Dimensions from top:  
Mounting depth with mounting plate  
Mounting depth for mounting rail 7.5 mm height  
Mounting depth for mounting rail 15 mm height  
Enclosure depth



Mounting depth for mounting rail 7.5 mm height  
93 mm

Features  
With mounting rail to IEC/EN 60715

**Notes**

N	R
Knockouts	Knockouts
2 x M25/20	2 x M25/20
	1 x M20
<b>U</b>	
Back plate:	
2 x M25/20	

**Technical data**

General  
Standards  
IEC/EN 60529  
DIN EN 62208  
Climatic proofing  
Damp heat, constant, to IEC 60068-2-78  
Damp heat, cyclic, to IEC 60068-2-30  
Ambient temperature  
-25 - +70  
-25 - +40 (with push-through cable entry) °C  
Degree of Protection  
Front IP65  
IP65, with push-through cable entry  
Power lossMax. radiated heat dissipation with separate mounting, ambient air temperature +20 °C  
21.5 W  
Material characteristics  
MaterialBase  
Glass-fibre reinforced polycarbonate  
MaterialCover  
Glass-fibre reinforced polycarbonate  
Surface treatment

Resistant to corrosion  
 ColourBase  
 RAL 9005, black (matt)  
 ColourHousing body  
 Enclosure cover RAL 7035, light grey (matt)  
 Material properties  
 ElectricalTrack resistance  
 CTI 175 (base, to IEC 60112)  
 CTI 175 (cover, to IEC 60112)  
 ElectricalSurface resistance to IEC 60093  
 $1 \Omega \times 10^{13}$   
 ElectricalDielectric strength to IEC 60243-1  
 30 kV/mm  
 ThermalTemperature resistant  
 -40 °C - 120 °C (enclosure)  
 -40 °C - +80 °C (gasket)  
 MechanicalImpact resistance  
 IK06 according to EN 50102  
 Mechanicalmax. assembly weightsMounting plate  
 0.85 kg  
 Mechanicalmax. assembly weightsMounting rail  
 0.85 kg  
 Chemical resistanceChemical resistant  
 Base, Cover  
 Resistant against: Acids < 10 %, mineral oil, alcohol, gasoline, greases, salt solutions  
 Partly resistant to: Acids > 10 %, alcohol  
 Not resistant to: alkalis, benzene  
 Push-through membrane (CI-K1/CI-K2) and sealing material  
 Resistant against: Acids < 10 %, alkalis, benzene, salt solutions  
 Partly resistant to: Acids > 10 %, greases, benzene  
 Not resistant to: Mineral oil, benzene  
 AtmosphericSaline spray  
 IEC 60068-2-11  
 AtmosphericUV resistance  
 Beneath protective shield  
 AtmosphericWater consumption to DIN EN ISO 62  
 0.29 %  
 Flammability characteristicsGlow wire testFlammability characteristics  
 960 °C/1mm thickness (base, cover; glow wire to VDE 0471 Part 2)  
 650 °C/1mm thick (push-through membrane) to VDE 0471 Part 2)  
 Flammability characteristicsGlow wire testto UL 94  
 VO/1.5 mm thickness  
 Flammability characteristicsGlow wire testto UL 94  
 HB  
 Flammability characteristicsHalogen free  
 Yes

## Design verification as per IEC/EN 61439

Technical data for design verification  
 Rated operational current for specified heat dissipation [ $I_n$ ]  
 0 A  
 Heat dissipation per pole, current-dependent [ $P_{id}$ ]  
 0 W  
 Equipment heat dissipation, current-dependent [ $P_{id}$ ]  
 0 W  
 Static heat dissipation, non-current-dependent [ $P_s$ ]  
 0 W  
 Heat dissipation capacity [ $P_{diss}$ ]  
 21.5 W  
 Operating ambient temperature min.  
 -25 °C  
 Operating ambient temperature max.  
 +70 °C  
 Degree of Protection  
 Front IP65  
 IP65, with push-through cable entry  
 Max. radiated heat dissipation with separate mounting, ambient air temperature +20 °C  
 21.5 W

Flammability characteristics  
 960 °C/1mm thickness (base, cover; glow wire to VDE 0471 Part 2)  
 650 °C/1mm thick (push-through membrane) to VDE 0471 Part 2)  
 Track resistance  
 CTI 175 (base, to IEC 60112)  
 CTI 175 (cover, to IEC 60112)  
 Surface treatment  
 Resistant to corrosion  
 Impact resistance  
 IK06 according to EN 50102  
 Temperature resistant  
 -40 °C - 120 °C (enclosure)  
 -40 °C - +80 °C (gasket)  
 UV resistance  
 Beneath protective shield  
 IEC/EN 61439 design verification  
 10.2 Strength of materials and parts 10.2.2 Corrosion resistance  
 Meets the product standard's requirements.  
 10.2 Strength of materials and parts 10.2.3.1 Verification of thermal stability of enclosures  
 Meets the product standard's requirements.  
 10.2 Strength of materials and parts 10.2.3.2 Verification of resistance of insulating materials to normal heat  
 Meets the product standard's requirements.  
 10.2 Strength of materials and parts 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects  
 Meets the product standard's requirements.  
 10.2 Strength of materials and parts 10.2.4 Resistance to ultra-violet (UV) radiation  
 Please enquire  
 10.2 Strength of materials and parts 10.2.5 Lifting  
 Not applicable.  
 10.2 Strength of materials and parts 10.2.6 Mechanical impact  
 Does not apply, since the entire switchgear needs to be evaluated.  
 10.2 Strength of materials and parts 10.2.7 Inscriptions  
 Meets the product standard's requirements.  
 10.3 Degree of protection of ASSEMBLIES  
 Meets the product standard's requirements.  
 10.4 Clearances and creepage distances  
 Meets the product standard's requirements.  
 10.5 Protection against electric shock  
 Does not apply, since the entire switchgear needs to be evaluated.  
 10.6 Incorporation of switching devices and components  
 Does not apply, since the entire switchgear needs to be evaluated.  
 10.7 Internal electrical circuits and connections  
 Is the panel builder's responsibility.  
 10.8 Connections for external conductors  
 Is the panel builder's responsibility.  
 10.9 Insulation properties 10.9.2 Power-frequency electric strength  
 Is the panel builder's responsibility.  
 10.9 Insulation properties 10.9.3 Impulse withstand voltage  
 Is the panel builder's responsibility.  
 10.9 Insulation properties 10.9.4 Testing of enclosures made of insulating material  
 Meets the product standard's requirements.  
 10.10 Temperature rise  
 The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.  
 10.11 Short-circuit rating  
 Is the panel builder's responsibility. The specifications for the switchgear must be observed.  
 10.12 Electromagnetic compatibility  
 Is the panel builder's responsibility. The specifications for the switchgear must be observed.  
 10.13 Mechanical function  
 The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Empty enclosure for switchgear (EC000712)  
 Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Empty housing for switch devices (ecl@ss10.0.1-27-37-13-01 [AKN343014])  
 Material housing  
 Plastic  
 Width

120 mm  
Height  
200 mm  
Depth  
125 mm  
With transparent cover  
No  
Suitable for emergency stop  
Yes  
Model  
Surface mounting  
Degree of protection (IP)  
IP65  
Degree of protection (NEMA)  
Other

Dimensions

CAD data

- [Product-specific CAD data](#)  
(Web)
- [3D Preview](#)  
(Web)

DWG files

- [DA-CD-ci\\_k3\\_ts](#)  
File  
(Web)

edz files


- [DA-CE-ETN.CI-K3-125-TS](#)  
File  
(Web)

Step files


- [DA-CS-ci\\_k\\_ts\\_7](#)  
File  
(Web)

Dimensions single product

- [321X003](#)  
Line drawing  
Basic enclosure



- [461N006](#)  
Line drawing  
Mounting depth



- [461N008](#)  
Line drawing  
Mounting depth

# Product photo



# Instruction Leaflet

- [Insulated small enclosures \(IL01502081Z\)](#)  
Asset  
(PDF, multilingual)

# Declaration of Conformity

## UK

- [C-K General Purpose Enclosures \(DA-DC-00004028\)](#)  
Asset  
(PDF)

# Download-Center

- [Download-Center \(this item\)](#)  
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)  
Eaton EMEA Download-Center

 [Generate data sheet in PDF format](#)

 [Generate data sheet in Excel format](#)

 [Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)  
© 2021 by Eaton Industries GmbH

