



106826
LS-S11-120AMT-ZBZ/X



Overview



Specifications



Resources



[Delivery program >](#)

[Technical data >](#)

[Design verification as per IEC/EN 61439 >](#)

[Technical data ETIM 7.0 >](#)

[Approvals >](#)

[Dimensions >](#)

DELIVERY PROGRAM

Basic function
Position switches
Safety position switches

Part group reference
LS...ZBZ/X

Product range
Basic devices with magnet-powered interlock
(open-circuit principle)

Degree of Protection
IP65

Features
Basic device, expandable

Ambient temperature
-25 - +40 °C

Description

With interlock monitoring
Monitoring of door position: continuous
Time control of the release operation possible
using ESR5-NV3-30

Contacts

N/O = Normally open
1 N/O

N/C = Normally closed
1 N/C ☐

Notes

☐ = safety function, by positive opening to IEC/EN
60947-5-1

Contact sequence

Rated control voltage for magnetic drive [U_s]
120 V 50/60 Hz V

Housing
Insulated material

Connection type
Screw terminal

Notes

Switch must never be used as a mechanical stop!
The operating head can be rotated manually in 90°
steps without tools to suit the specified level of
actuation.
With the actuator inserted, the N/O contact is open
and the N/C contact is closed.
For degree of protection IP65, use V-M20
(206910) cable glands with connecting thread of
max. 9 mm length.

TECHNICAL DATA

General

Standards
IEC/EN 60947

Climatic proofing
Damp heat, constant, to IEC 60068-2-78; damp
heat, cyclical, to IEC 60068-2-30

Ambient temperature
-25 - +40 °C

Mounting position
As required

Degree of Protection
IP65

Terminal capacities
Solid
1 x (0.75 - 2.5)
2 x (0.75 - 1.5) mm²

Terminal capacities
Flexible with ferrule
1 x (0.5 - 1.5)
2 x (0.5 - 1.5) mm²

Repetition accuracy
0.02 mm

Contacts/switching capacity

Rated impulse withstand voltage [U_{imp}]
4000 V AC

Rated insulation voltage [U_i]
400 V

Overvoltage category/pollution degree
III/3

Rated operational current [I_e]
AC-15
24 V [I_e]
6 A

Rated operational current [I_e]
AC-15
220 V 230 V 240 V [I_e]
6 A

Rated operational current [I_e]
AC-15
380 V 400 V 415 V [I_e]
4 A

Rated operational current [I_e]
DC-13
24 V [I_e]
3 A

Rated operational current [I_e]
DC-13
110 V [I_e]
0.8 A

Rated operational current [I_e]
DC-13
220 V [I_e]
0.3 A

Supply frequency
max. 400 Hz

Short-circuit rating to IEC/EN 60947-5-1
max. fuse
6 A gG/gL

Rated conditional short-circuit current
1 kA

Mechanical variables

Lifespan, mechanical [Operations]
 1×10^6

Mechanical shock resistance (half-sinusoidal
shock, 20 ms)
Standard-action contact
10 g

Operating frequency [Operations/h]
☐ 800

Actuation

Mechanical
Actuating force at beginning/end of stroke
25/15 (plug-in/pull-out) N

Mechanical
Mechanical holding force acc. to GS-ET-19
(04/2004)
XG, XW, XNG
1700 N

Mechanical
Mechanical holding force acc. to GS-ET-19
(04/2004)
XWA, XFG, XF
1600 N

Mechanical
Mechanical holding force acc. to GS-ET-19
(04/2004)
XNW
1200 N

Electromechanical
For magnet
Power consumption
at 120 V AC
8 VA

Electromechanical
For magnet
Power consumption
at 230 V AC
11 VA

Electromechanical
For magnet
Power consumption
at 24 V DC
8 W

Electromechanical
Pick-up and drop-out values
 $0.85 - 1.1 \times U_s$

Electromechanical
Magnet duty factor
100 % ED

DESIGN VERIFICATION AS PER IEC/EN 61439

Technical data for design verification

Rated operational current for specified heat dissipation [I_n]
6 A

Heat dissipation per pole, current-dependent [P_{vd}]
0.13 W

Equipment heat dissipation, current-dependent [P_{vd}]
0 W

Static heat dissipation, non-current-dependent [P_{vs}]
0 W

Heat dissipation capacity [P_{diss}]
0 W

Operating ambient temperature min.
-25 °C

Operating ambient temperature max.
+40 °C

IEC/EN 61439 design verification

10.2 Strength of materials and parts
10.2.2 Corrosion resistance
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.3.1 Verification of thermal stability of enclosures
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.3.2 Verification of resistance of insulating materials to normal heat
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.3.3 Verification of resistance of insulating

materials to abnormal heat and fire due to internal electric effects
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.4 Resistance to ultra-violet (UV) radiation
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.5 Lifting
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts
10.2.6 Mechanical impact
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts
10.2.7 Inscriptions
Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES
Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances
Meets the product standard's requirements.

10.5 Protection against electric shock
Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components
Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections
Is the panel builder's responsibility.

10.8 Connections for external conductors
Is the panel builder's responsibility.

10.9 Insulation properties
10.9.2 Power-frequency electric strength
Is the panel builder's responsibility.

10.9 Insulation properties
10.9.3 Impulse withstand voltage
Is the panel builder's responsibility.

10.9 Insulation properties
10.9.4 Testing of enclosures made of insulating material
Is the panel builder's responsibility.

10.10 Temperature rise
The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function
The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

TECHNICAL DATA ETIM 7.0

Sensors (EG000026) / End switch (EC000030)

Electric engineering, automation, process control engineering / Binary sensor technology, safety-related sensor technology / Position switch / Position switch (Type 1) (ecl@ss10.0.1-27-27-06-01 [AGZ382015])

Width sensor
60 mm

Diameter sensor
0 mm

Height of sensor
173 mm

Length of sensor
39 mm

Rated operation current I_e at AC-15, 24 V
6 A

Rated operation current I_e at AC-15, 125 V
6 A

Rated operation current I_e at AC-15, 230 V
6 A

Rated operation current I_e at DC-13, 24 V
3 A

Rated operation current I_e at DC-13, 125 V
0.8 A

Rated operation current I_e at DC-13, 230 V
0.3 A

Switching function
Slow-action switch

Switching function latching
No

Output electronic
No

Forced opening
Yes

Number of safety auxiliary contacts
1

Number of contacts as normally closed contact
1

Number of contacts as normally open contact
1

Number of contacts as change-over contact
0

Type of interface
None

Type of interface for safety communication
None

Construction type housing
Cuboid

Material housing
Plastic

Coating housing
Other

Type of control element
Other

Alignment of the control element
Other

Type of electric connection
Other

With status indication
No

Suitable for safety functions
Yes

Explosion safety category for gas
None

Explosion safety category for dust
None

Ambient temperature during operating
25 - 70 °C

Degree of protection (IP)

IP65

Degree of protection (NEMA)
13

APPROVALS

Product Standards
IEC/EN 60947-5; UL 508; CSA-C22.2 No. 14; CE
marking

UL File No.
E29184

UL Category Control No.
NKCR

CSA File No.
12528

CSA Class No.
3211-03

North America Certification
UL listed, CSA certified

Degree of Protection
IEC: IP65, UL/CSA Type 3R, 4X (indoor use only),
12, 13

DIMENSIONS



