

Select your language

- [German](#)
- [English](#)
- [Spanish](#)
- [French](#)
- [Dutch](#)
- [Italian](#)
- [Polish](#)
- [Czech](#)
- [Russian](#)
- [Norwegian Bokmål](#)

Worldwide English



EML30 - Terminal block, 4 x 4/0-500 MCM, 4 x 120-240 mm<sup>2</sup>, For use with: S801+, S811+, frame size V



127667 EML30

[Overview](#) [Specifications](#) [Resources](#)



## 127667 EML30

Terminal block, 4 x 4/0-500 MCM, 4 x 120-240 mm<sup>2</sup>, For use with: S801+, S811+, frame size V

Alternate Catalog No.

EML30

EL-Nummer (Norway)

4137503

Terminal block for S801+ and S811+ soft starters, for size S8x1+V, 4x240mm<sup>2</sup>

- [Delivery program](#)

Design verification as per  
IEC/EN 61439

- [Technical data ETIM 7.0](#)

- [Approvals](#)

### Delivery program

Accessories

Terminal blocks

Ordering information

1 set required for each connection side.

For use with

S801+, S811+, frame size V

Terminal capacities

4 x 4/0-500 MCM, 4 x 120-240 mm<sup>2</sup> mm<sup>2</sup>

#### Instructions

Tools with dimensions in inches required

### Design verification as per IEC/EN 61439

Technical data for design verification

Operating ambient temperature min.

-30 °C

Operating ambient temperature max.

+50 °C

IEC/EN 61439 design verification

10.2 Strength of materials and parts 10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.7 Inscriptions

Meets the product standard's requirements.

#### 10.3 Degree of protection of ASSEMBLIES

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.4 Clearances and creepage distances

Meets the product standard's requirements.

#### 10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

#### 10.8 Connections for external conductors

Is the panel builder's responsibility.

#### 10.9 Insulation properties10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

#### 10.9 Insulation properties10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

#### 10.9 Insulation properties10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

#### 10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

#### 10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

#### 10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

#### 10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Connection vane/phase spreader (EC002019)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Connection vane/phase spreader (ec1@ss10.0.1-27-37-13-05 [ACN990012])

Suitable for number of poles

3

## Approvals

Product Standards

UL508, CSA C22.2 No. 65

UL File No.

E202571

UL Category Control No.

NMFT

CSA File No.

LR353

CSA Class No.

6223-02

North America Certification

UL listed, CSA certified

## Product photo



8250PIC-108

Photo

## 3D drawing



8250DRV-115

Line drawing

## Download-Center

- [Download-Center \(this item\)](#)  
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)  
Eaton EMEA Download-Center



[Generate data sheet in PDF format](#)



[Generate data sheet in Excel format](#)



[Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2021 by Eaton Industries GmbH

