

Select your language

- German
- English
- Spanish
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norwegian Bokmål

Worldwide English



NZMN3-PX250-TAZ-AVE - NZM3 PXR25 circuit breaker - integrated energy measurement class 1, 250A, 3p, earth-fault protection, ARMS and zone selectivity



192268 NZMN3-PX250-TAZ-AVE

[Overview](#) [Specifications](#) [Resources](#)



192268 NZMN3-PX250-TAZ-AVE

NZM3 PXR25 circuit breaker - integrated energy measurement class 1, 250A, 3p, earth-fault protection, ARMS and zone selectivity

EL-Nummer (Norway)

4362940

The xEffect NZM...PX...-TAZ circuit breaker range with power expert release (PXR) electronic triggering system covers use cases for full range protection including earth fault protection with only four compact sizes and is suitable for the IEC market. The integrated energy measuring function supplies currents, voltages and active energy (kWh) with accuracy class 1 according to IEC 61557-12. Maintenance mode ARMS and zone selectivity for extended protection included. Test function and settings via micro USB port directly on the switch. Modular function groups always make mounting flexible and may be supplemented by the comprehensive range of accessories. R.m.s. value measurement and thermal memory.



- Delivery program
- Technical data
- Design verification as per IEC/EN 61439
- Technical data ETIM 7.0
- Characteristics
- Dimensions

Delivery program

Product range
Circuit-breaker
Protective function
Systems, cable, selectivity and generator protection
Earth-fault protection
Zone selectivity
ARMS maintenance mode
Standard/Approval
IEC
Installation type
Withdrawable
Release system
Electronic release
Construction size
NZM3
Description
LSIG overload protection and delayed and non-delayed short-circuit protective device, earth-fault protection
Class 1 energy measurement, r.m.s. value measurement, and "thermal memory"
USB interface for configuration and test function with Power Xpert Protection Manager software

Zone selectivity ZSI
 Maintenance Mode ARMS
 Interface module in equipment supplied.
 Optionally communication-capable with internal Modbus RTU module or CAM
 Number of poles
 3 pole
 Standard equipment
 Screw connection
 Switching capacity
 400/415 V 50 Hz [I_{cu}]
 50 kA
 Rated current = rated uninterrupted current [$I_n = I_u$]
 Rated current = rated uninterrupted current [$I_n = I_u$]
 250 A

Setting range

Overload trip  [I_t]
 100 - 250 A
 Short-circuit releases  [I_{rm}] Non-delayed  [$I_t = I_n \times \dots$]
 2 - 18
 Short-circuit releases  [I_{rm}] Delayed  [$I_{sd} = I_t \times \dots$]
 2 - 10
 Setting range of earth fault release min. [$I_g = I_n \times \dots$]
 50
 Setting range of earth fault release max. [$I_g = I_n \times \dots$]
 250

Technical data

General

Standards

IEC/EN 60947

Protection against direct contact

Finger and back of hand proof to VDE 0106 Part 100

Climatic proofing

Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30

Ambient temperature Ambient temperature, storage

- 40 - + 70 °C

Ambient temperature Operation

-25 - +70 °C

Mechanical shock resistance (10 ms half-sinusoidal shock) according to IEC 60068-2-27

20 (half-sinusoidal shock 20 ms) g

Safe isolation to EN 61140 Between auxiliary contacts and main contacts

500 V AC

Safe isolation to EN 61140 between the auxiliary contacts

300 V AC

Mounting position

Vertical and 90° in all directions	
<input type="checkbox"/>	With XFI earth-fault release:
	- NZM1, N1, NZM2, N2: vertical and 90° in all directions
	with plug-in unit
	- NZM1, N1, NZM2, N2: vertical, 90° right/left
	with withdrawable unit:
	- NZM3, N3: vertical, 90° right/left
	- NZM4, N4: vertical
	with remote operator:
	- NZM2, N(S)2, NZM3, N(S)3, NZM4, N(S)4: vertical and 90° in all directions

Direction of incoming supply

as required

Degree of protection Device

In the operating controls area: IP20 (basic degree of protection)

Degree of protection Enclosures

With insulating surround: IP40

With door coupling rotary handle: IP66

Degree of protection Terminations

Tunnel terminal: IP10

Phase isolator and strip terminal: IP00

Other technical data (sheet catalogue)

Weight

Temperature dependency, Derating

Effective power loss

Circuit-breakers

Rated current = rated uninterrupted current [$I_n = I_u$]

250 A

Rated surge voltage invariability [U_{imp}]Main contacts

8000 V

Rated surge voltage invariability [U_{imp}]Auxiliary contacts

6000 V

Rated operational voltage [U_e]

690 V AC

Overvoltage category/pollution degree

III/3

Rated insulation voltage [U_i]

690 V

Use in unearthed supply systems

690 V

Switching capacity

Rated short-circuit making capacity [I_{cm}]240 V [I_{cm}]

187 kA

Rated short-circuit making capacity [I_{cm}]400/415 V [I_{cm}]

105 kA

Rated short-circuit making capacity [I_{cm}]440 V 50/60 Hz [I_{cm}]

74 kA

Rated short-circuit making capacity [I_{cm}]525 V 50/60 Hz [I_{cm}]

53 kA

Rated short-circuit making capacity [I_{cm}]690 V 50/60 Hz [I_{cm}]

40 kA

Rated short-circuit breaking capacity I_{cn} [I_{cn}] I_{cu} to IEC/EN 60947 test cycle O-t-CO [I_{cu}]240 V 50/60 Hz [I_{cu}]

85 kA

Rated short-circuit breaking capacity I_{cn} [I_{cn}] I_{cu} to IEC/EN 60947 test cycle O-t-CO [I_{cu}]400/415 V 50/60 Hz [I_{cu}]

50 kA

Rated short-circuit breaking capacity I_{cn} [I_{cn}] I_{cu} to IEC/EN 60947 test cycle O-t-CO [I_{cu}]440 V 50/60 Hz [I_{cu}]

35 kA

Rated short-circuit breaking capacity I_{cn} [I_{cn}] I_{cu} to IEC/EN 60947 test cycle O-t-CO [I_{cu}]525 V 50/60 Hz [I_{cu}]

25 kA

Rated short-circuit breaking capacity I_{cn} [I_{cn}] I_{cu} to IEC/EN 60947 test cycle O-t-CO [I_{cu}]690 V 50/60 Hz [I_{cu}]

20 kA

Rated short-circuit breaking capacity I_{cn} [I_{cn}] I_{cs} to IEC/EN 60947 test cycle O-t-CO-t-CO [I_{cs}]240 V 50/60 Hz [I_{cs}]

85 kA

Rated short-circuit breaking capacity I_{cn} [I_{cn}] I_{cs} to IEC/EN 60947 test cycle O-t-CO-t-CO [I_{cs}]400/415 V 50/60 Hz [I_{cs}]

50 kA

Rated short-circuit breaking capacity I_{cn} [I_{cn}] I_{cs} to IEC/EN 60947 test cycle O-t-CO-t-CO [I_{cs}]440 V 50/60 Hz [I_{cs}]

35 kA

Rated short-circuit breaking capacity I_{cn} [I_{cn}] I_{cs} to IEC/EN 60947 test cycle O-t-CO-t-CO [I_{cs}]525 V 50/60 Hz [I_{cs}]

13 kA

Rated short-circuit breaking capacity I_{cn} [I_{cn}] I_{cs} to IEC/EN 60947 test cycle O-t-CO-t-CO [I_{cs}]690 V 50/60 Hz [I_{cs}]

5 kA

Rated short-circuit breaking capacity I_{cn} [I_{cn}]

Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit-breaker.

Rated short-time withstand current I_{cw} = 0.3 s [I_{cw}]

3.3 kA

Rated short-time withstand current I_{cw} = 1 s [I_{cw}]

3.3 kA

Utilization category to IEC/EN 60947-2

A

Lifespan, mechanical (of which max. 50 % trip by shunt/undervoltage release) [Operations]

15000

Lifespan, electrical AC-1400 V 50/60 Hz [Operations]

5000

Lifespan, electrical AC-1415 V 50/60 Hz [Operations]

5000

Lifespan, electrical AC-1690 V 50/60 Hz [Operations]

3000

Lifespan, electrical Max. operating frequency

60 Ops/h

Total break time at short-circuit

< 10 ms

Terminal capacity

Standard equipment

Screw connection

Accessories required

NZMB-XAVS

Optional accessories

Box terminal

Tunnel terminal

connection on rear

Round copper conductorBox terminalSolid

2 x 16 mm²

Round copper conductorBox terminalStranded

1 x (35 - 240)

2 x (25-120) mm²

Round copper conductorTunnel terminalSolid

1 x 16 mm²

Round copper conductorTunnel terminalStranded1-hole

1 x (16 - 185) mm²

Round copper conductorBolt terminal and rear-side connectionDirect on the switchSolid

1 x 16

2 x 16 mm²

Round copper conductorBolt terminal and rear-side connectionDirect on the switchStranded

1 x (25 - 240)

2 x (25 - 240) mm²

Round copper conductorBolt terminal and rear-side connectionConnection width extensionConnection width extension

2 x 300 mm²

Al circular conductor Tunnel terminalSolid

1 x 16 mm²

Al circular conductor Tunnel terminalStrandedStranded

1 x (25 - 185) ²⁾ mm²

Al circular conductor Tunnel terminalStrandedDouble hole

1 x (50 - 240)

2 x (50 - 240) mm²

Al circular conductor Tunnel terminalStranded

²⁾ Up to 240 mm² can be connected depending on the cable manufacturer.

Cu strip (number of segments x width x segment thickness)Box terminal [min.]

6 x 16 x 0.8 mm

Cu strip (number of segments x width x segment thickness)Box terminal [max.]

10 x 24 x 1.0

+ 5 x 24 x 1.0

(2 x) 8 x 24 x 1.0 mm

Cu strip (number of segments x width x segment thickness)Bolt terminal and rear-side connectionFlat copper strip, with holes [min.]

6 x 16 x 0.8 mm

Cu strip (number of segments x width x segment thickness)Bolt terminal and rear-side connectionFlat copper strip, with holes [max.]

10 x 32 x 1.0 + 5 x 32 x 1.0 mm

Cu strip (number of segments x width x segment thickness)Bolt terminal and rear-side connectionConnection width extension

(2 x) 10 x 50 x 1.0 mm

Copper busbar (width x thickness) [mm]Bolt terminal and rear-side connectionScrew connection

M10

Copper busbar (width x thickness) [mm]Bolt terminal and rear-side connectionDirect on the switch [min.]

20 x 5 mm

Copper busbar (width x thickness) [mm]Bolt terminal and rear-side connectionDirect on the switch [max.]

30 x 10

+ 30 x 5 mm

Copper busbar (width x thickness) [mm]Bolt terminal and rear-side connectionConnection width extensionConnection width extension [max.]

2 x (10 x 50) mm

Control cables

1 x (0.75 - 2.5)

2 x (0.75 - 1.5) mm²

Design verification as per IEC/EN 61439

Technical data for design verification

Rated operational current for specified heat dissipation [I_n]

250 A

Equipment heat dissipation, current-dependent [P_{id}]

18.75 W

Operating ambient temperature min.

-25 °C

Operating ambient temperature max.

+70 °C

IEC/EN 61439 design verification

10.2 Strength of materials and parts 10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Power circuit-breaker for trafo/generator/installation protection (EC000228)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Circuit breaker for power transformer, generator and system protection (ecl@ss10.0.1-27-37-04-09 [AJZ716013])

Rated permanent current I_n

250 A

Rated voltage

690 - 690 V

Rated short-circuit breaking capacity I_{cu} at 400 V, 50 Hz

50 kA

Overload release current setting

100 - 250 A

Adjustment range short-term delayed short-circuit release
2 - 10 A
Adjustment range undelayed short-circuit release
2 - 18 A
Integrated earth fault protection
Yes
Type of electrical connection of main circuit
Other
Device construction
Built-in device slide-in technique (withdrawable)
Suitable for DIN rail (top hat rail) mounting
No
DIN rail (top hat rail) mounting optional
No
Number of auxiliary contacts as normally closed contact
0
Number of auxiliary contacts as normally open contact
0
Number of auxiliary contacts as change-over contact
0
With switched-off indicator
No
With under voltage release
No
Number of poles
3
Position of connection for main current circuit
Connection at separate chassis part
Type of control element
Rocker lever
Complete device with protection unit
Yes
Motor drive integrated
No
Motor drive optional
Yes
Degree of protection (IP)
IP20

Characteristics

Characteristic curve

Let-through current

Characteristic curve

Let-through energy

Dimensions

Blow out area, minimum clearance to adjacent parts

Minimum clearance to adjacent parts

CAD data

- [Product-specific CAD data](#)
(Web)
- [3D Preview](#)
(Web)

DWG files

- [DA-CD-nzm3_3p](#)
File
(Web)

Step files

- [DA-CS-nzm3_3p](#)
File
(Web)

Additional product information

- [Weight](#)
(Web)
- [Temperature dependency, Derating](#)
(Web)
- [Effective power loss](#)
(Web)
- [additional technical information for NZM power switch](#)
(PDF)

Product photo



Dimensions single product

- [123X330](#)
Line drawing
Circuit-breakers
 Blow out area, minimum clearance to adjacent parts
 Minimum clearance to adjacent parts
- [123X553](#)
Line drawing
Circuit-breakers, switch-disconnectors

Characteristic curve

- [1230DIA-181](#)
Coordinate visualization
- [1230DIA-188](#)
Coordinate visualization

Instruction Leaflet

- [IL012100ZU](#)
Asset
(PDF, Language independent)

Download-Center

- [Download-Center \(this item\)](#)
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)



[Generate data sheet in PDF format](#)



[Generate data sheet in Excel format](#)



[Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2021 by Eaton Industries GmbH

