

FLOODLIGHTS

OFR/AFR

Home | Floodlights | OFR/AFR |



AFR 350 LED 5K WH

Item number EL10750304

This product has expired and cannot be reordered

Thanks to rear projection technology, OFR/AFR LED floodlights generate a powerful yet glare-free light that illuminates paths, squares and façades. What's more, they are optimally protected thanks to the aluminium housing and are particularly flexible thanks to the horizontally or vertically adjustable lamp head. The optional integrated motion detector ensures automatic energy efficiency.

SHORTFACTS

TECHNICAL DATA

DOWNLOADS

LIGHT CALCULATION

Device category	Floodlights
Installation type	Surface mounting
Installation position	Wall
Protection type	IP55
Dimensions	Length 176 mm x Width 137 mm x Height/Depth 216 mm
Diffusor	transparent
Luminous efficacy	64 lm/W
Luminous flux	1670 lm
Rated output P	26 W
Colour temperature	5000 K

Detection angle	140°
Permissible ambient temperature	-25 °C...+50 °C
Warranty	3-year



CONTACT US

Salutation

Firstname *

Lastname *

Company *

Phone

E-mail-address *


Subject *

Your message *

Yes, I agree that ESYLUX will inform me about news in the future via newsletter.

I have read and agreed to the [privacy policy](#) *

* Required





Solutions

Offices

Education

Health Care

Innovations

Demand-driven Automation

Intelligent Lighting

Human Centric Lighting

Light control with DALI-2

Service

Downloads

Knowledge

Support

ESYLUX Services

Company

Vision and mission

Experience and quality

Corporate responsibility

Research and development

Cooperations and
memberships

Awards and prizes

References

Highlights

ESYLUX Light Control

DEFENSOR

COMPACT

ESY-Pen

ALVA

FLAT

ISABELLE

[Imprint](#) |
[Privacy policy](#) |
[Privacy settings](#) |
[General terms and conditions](#) |
[Guarantee](#) |
[Disclaimer](#) |
[Contact](#)

© 2021 ESYLUX GmbH

