



Overview

Leveringstid	Usually in Stock
--------------	------------------

General

Tilgjengelig utstyr	Horizontal mounting brackets Installation guide Brukermanual Kabel
---------------------	---

Physical

Kabellengde	2,50 m
Farge	Sort
Dybde	4,4 cm
Høyde	4,44 cm
Vekt	0,7 kg
Bredde	48,2 cm

Input

Input current limits	16 A
Load capacity	3680 VA
Network frequency	50/60 Hz
Plug standard	IEC 60320 C20
Forsyningsspenning	200 V 208 V 230 V

Output

Number of power socket outlets	8 IEC 60320 C13
--------------------------------	-----------------

Conformance

Produktsertifikater	CE TÜV
---------------------	-----------

Environmental

Omgivelsestemperatur drift	-5...45 °C
Relativ fuktighet	5...95 %
Driftshøyde	0...10000 ft
Omgivelsestemperatur for lagring	-25...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0,00...15240,00 m

Packing Units

Forpakning 1 vekt	1,4 kg
Forpakning 1 høyde	8 cm
Forpakning 1 bredde	56 cm
Forpakning 1 lengde	15 cm

Offer Sustainability

EU RoHS-direktiv	I samsvar  EU RoHS-erklæring
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	 Ja

Contractual warranty

Garanti	1 year repair or replace
---------	--------------------------