



Teknisk informasjon

Serie	Compact
Produktnavn	Compact NSX
Produktspekter	ComPact NSX100...250
Kortnavn utstyr	VigiCompact NSX100N
Produkt eller type komponent	Earth leakage circuit breaker
Applikasjon	Distribusjon
Number of poles	3P
Polbeskrivelse	3t
[In] merkestrøm	40 A at 40 °C
[Ue] merkespenning	440 V AC 50/60 Hz
Type nettverk	AC
Nettverksfrekvens	50/60 Hz
Egnethet for isolasjon	Yes conforming to EN/IEC 60947-2
Driftskategori	Kategori A
[Icu] rated ultimate short-circuit breaking capacity	90 KA Icu at 220/240 V AC 50/60 Hz conforming to IEC 60947-2 50 KA Icu at 380/415 V AC 50/60 Hz conforming to IEC 60947-2 50 kA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2
Performance level	N 50 kA 415 V AC
Navn på vern	Micrologic 4.2
Vernteknologi	Elektronisk
Vernfunksjoner	LSolR
Kontrolltype	Kipp
Circuit breaker mounting mode	Fast

Komplementær

[Ui] isolasjonsspenning	500 V AC 50/60 Hz
[Uimp] Nominell impuls-spenning	8 kV
[Ics] rated service short-circuit breaking capacity	90 KA at 220/240 V AC 50/60 Hz conforming to IEC 60947-2 50 KA at 380/415 V AC 50/60 Hz conforming to IEC 60947-2 50 kA at 440 V AC 50/60 Hz conforming to IEC 60947-2
Mekanisk levetid	50000 sykluser
Elektrisk levetid	30000 Cycles at 440 V In 50000 cycles at 440 V In/2
Montering	Bakplate
Tilkobling oppe	Front
Tilkobling i bunn	Front
Connection pitch	35 mm
Beskyttelsestype	L : for overload protection (long time) Short time short-circuit protection with fixed delay I : for instantaneous short-circuit protection R : for earth-leakage protection
Vernstørrelse	40 A at 40 °C
Long-time pick-up adjustment type Ir (thermal protection)	Justerbar 9 innstillinger
[Ir] long-time protection pick-up adjustment range	18...40 A

Long-time protection delay adjustment type tr	Fast
[tr] long-time protection delay adjustment range	11 S at 7.2 x Ir 16 S at 6 x Ir 400 s at 1.5 x Ir
Termisk minne	20 min før og etter utkobling
Short-time protection pick-up adjustment type lsd	Justerbar
[lsd] Short-time protection pick-up adjustment range	1.5...10 x Ir
Short-time protection delay adjustment type tsd	Fast
[tsd] Short-time protection delay adjustment range	0,02 s
Instantaneous protection pick-up adjustment type li	Fast
[li] instantaneous protection pick-up adjustment range	600 A
Jordfeilbeskyttelse	Integrert
Jordfeilvern klasse	A-klasse
Earth-leakage protection sensitivity adjustment type lΔn	Justrbar
[lΔn] earth-leakage protection sensitivity adjustment range	30 MA 100 MA 300 MA 500 MA 1 A 3 A 5 A
Earth-leakage protection specific mode	OFF using the lΔn rotary switch
Earth-leakage protection time delay adjustment type Δt	Justerbar
[Δt] Earth-leakage protection time delay adjustment range	0 Ms 60 Ms 150 Ms 500 Ms 1 s
Zone selektiv forrigling (logisk selektivitet) ZSI	Uten
Number of slots for electrical auxiliaries	5 slot(s)
Lokal varslng	Klar til drift: flashing LED (grønn) LED 105 % Ir (red) for overload LED 90 % Ir (orange) for overload
Width (W)	105 mm
Height (H)	161 mm
Depth (D)	86 mm
Vekt	2,05 kg

Miljø

Standarder	EN/IEC 60947
Produktsertifikater	CCC EAC Marine
Overspenningskategori	Klasse II
Beskyttelsesklasse for elektrisk støt	Klasse II
Forurensninggrad	3 i samsvar med IEC 60664-1
IP-grad	IP40 conforming to IEC 60529
IK beskyttelsesklasse	IK07 conforming to IEC 62262
Omgivelsestemperatur drift	-25...70 °C
Omgivelsestemperatur for lagring	-40...85 °C
Relativ fuktighet	0...95 %
Operating altitude	0...2000 m without derating 2000 m...5000 m with derating

Packing Units

Enhetstype forpakning 1	PCE
Antall enheter forpakning 1	1
Forpakning 1 vekt	2,086 kg
Forpakning 1 høyde	12,6 cm
Forpakning 1 bredde	16,1 cm
Forpakning 1 lengde	10,5 cm
Enhetstype forpakning 2	S03
Antall enheter forpakning 2	6
Forpakning 2 vekt	13,282 kg
Forpakning 2 høyde	30 cm
Forpakning 2 bredde	30 cm
Forpakning 2 lengde	40 cm

Offer Sustainability

Produktets miljøstatus	Green Premium miljømerket produkt
REACH-regelverk	 REACH-erklæring
EU RoHS-direktiv	I samsvar  EU RoHS-erklæring
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	 Ja
Kinas RoHS-forskrift	 Kinas RoHS-Erklæring
Miljøinformasjon	 Produktmiljøprofil
Produktets livssyklus	 Informasjon Om Levetidsslutt
WEEE	Innen EU må produktet avhendes i henhold til bestemte regler for avfallshåndtering og aldri kastes som husholdningsavfall.
PVC-fri	Ja

Contractual warranty

Garanti	18 months
---------	-----------