



Teknisk informasjon

Serie	Compact
Produktnavn	Compact NSX
Produktspekter	ComPact NSX100...250
Kortnavn utstyr	VigiCompact NSX160N
Produkt eller type komponent	Earth leakage circuit breaker
Applikasjon	Distribusjon
Number of poles	4P
Polbeskrivelse	4t 3t 3t + N/2
Plassering av nøytral	VENSTRE
[In] merkestrøm	100 A at 40 °C
[Ue] merkespenning	440 V AC 50/60 Hz
Type nettverk	AC
Nettverksfrekvens	50/60 Hz
Egnethet for isolasjon	Ja i samsvar med EN/IEC 60947-2
Driftkategori	Kategori A
[Icu] rated ultimate short-circuit breaking capacity	90 KA Icu at 220/240 V AC 50/60 Hz conforming to IEC 60947-2 50 KA Icu at 380/415 V AC 50/60 Hz conforming to IEC 60947-2 50 KA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2
Performance level	N 50 kA 415 V AC
Navn på vern	Micrologic 4.2
Vernteknologi	Elektronisk
Vernfunksjoner	LSolR
Kontrolltype	Kipp
Circuit breaker mounting mode	Fast

Komplementær

[Ui] isolasjonsspenning	500 V AC 50/60 Hz
[Uimp] Nominell impuls-spenning	8 kV
[Ics] rated service short-circuit breaking capacity	90 KA at 220/240 V AC 50/60 Hz conforming to IEC 60947-2 50 KA at 380/415 V AC 50/60 Hz conforming to IEC 60947-2 50 KA at 440 V AC 50/60 Hz conforming to IEC 60947-2
Mekanisk levetid	40000 sykluser
Elektrisk levetid	20000 Cycles at 440 V In 40000 cycles at 440 V In/2
Montering	Bakplate
Tilkobling oppe	Front
Tilkobling i bunn	Front
Connection pitch	35 mm
Beskyttelsestype	L : for overload protection (long time) Short time short-circuit protection with fixed delay I : for instantaneous short-circuit protection R : for earth-leakage protection
Vernstørrelse	100 A at 40 °C

Long-time pick-up adjustment type Ir (thermal protection)	Justerbar 9 innstillinger
[Ir] long-time protection pick-up adjustment range	40...100 A
Long-time protection delay adjustment type tr	Fast
[tr] long-time protection delay adjustment range	11 S at 7.2 x Ir 16 S at 6 x Ir 400 s at 1.5 x Ir
Termisk minne	20 min før og etter utkobling
Short-time protection pick-up adjustment type Isd	Justerbar
[Isd] Short-time protection pick-up adjustment range	1.5...10 x Ir
Short-time protection delay adjustment type tsd	Fast
[tsd] Short-time protection delay adjustment range	0,02 s
Instantaneous protection pick-up adjustment type li	Fast
[li] instantaneous protection pick-up adjustment range	1500 A
Jordfeilbeskyttelse	Integrert
Jordfeilvern klasse	A-klasse
Earth-leakage protection sensitivity adjustment type IΔn	Justrbar
[IΔn] earth-leakage protection sensitivity adjustment range	30 MA 100 MA 300 MA 500 MA 1 A 3 A 5 A
Earth-leakage protection specific mode	OFF using the IΔn rotary switch
Earth-leakage protection time delay adjustment type Δt	Justerbar
[Δt] Earth-leakage protection time delay adjustment range	0 Ms 60 Ms 150 Ms 500 Ms 1 s
Neutral protection settings	0.5 x Ir (3t + N/2) 1 x Ir (4t) No protection (3t)
Zone selektiv forrigling (logisk selektivitet) ZSI	Uten
Number of slots for electrical auxiliaries	5 slot(s)
Lokal varslng	Klar til drift: flashing LED (grønn) LED 105 % Ir (red) for overload LED 90 % Ir (orange) for overload
Width (W)	140 mm
Height (H)	161 mm
Depth (D)	86 mm
Vekt	2,4 kg

Miljø

Standarder	EN/IEC 60947
Produktsertifikater	CCC EAC Marine
Overspenningskategori	Klasse II
Beskyttelsesklasse for elektrisk støt	Klasse II
Forurensningsgrad	3 i samsvar med IEC 60664-1
IP-grad	IP40 i samsvar med IEC 60529
IK beskyttelsesklasse	IK07 i samsvar med IEC 62262
Omgivelsestemperatur drift	-25...70 °C
Omgivelsestemperatur for lagring	-40...85 °C
Relativ fuktighet	0...95 %
Operating altitude	0...2000 m without derating 2000 m...5000 m with derating

Packing Units

Enhetstype forpakning 1	PCE
Antall enheter forpakning 1	1
Forpakning 1 vekt	2,78 kg
Forpakning 1 høyde	12,6 cm
Forpakning 1 bredde	16,1 cm
Forpakning 1 lengde	14 cm
Enhetstype forpakning 2	S03
Antall enheter forpakning 2	4
Forpakning 2 vekt	11,886 kg
Forpakning 2 høyde	30 cm
Forpakning 2 bredde	30 cm
Forpakning 2 lengde	40 cm

Offer Sustainability

Produktets miljøstatus	Green Premium miljømerket produkt
REACH-regelverk	 REACH-erklæring
EU RoHS-direktiv	I samsvar  EU RoHS-erklæring
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	 Ja
Kinas RoHS-forskrift	 Kinas RoHS-Erklæring
Miljøinformasjon	 Produktmiljøprofil
Produktets livssyklus	 Informasjon Om Levetidsslutt
WEEE	Innen EU må produktet avhendes i henhold til bestemte regler for avfallshåndtering og aldri kastes som husholdningsavfall.
PVC-fri	Ja

Contractual warranty

Garanti	18 months
---------	-----------