

C16N3TM125

Effektbryter ComPacT NSX med
termomagnetisk vern NSX160N-TM125D 3P3T
125A 90kA/230VAC - 50kA/415VAC



Teknisk informasjon

Serie	ComPacT new generation
Produktnavn	ComPacT NSX new generation
Produktspekter	ComPacT NSX100...250 new generation
Kortnavn utstyr	NSX160N
Produkt eller type komponent	Effektbryter
Applikasjon	Distribusjon
Antall poler	3P
Polbeskrivelse	3t
[In] merkestrøm	125 A at 40 °C
[Ue] merkespenning	690 V AC 50/60 Hz
Type nettverk	AC
Nettverksfrekvens	50/60 Hz
Egnethet for isolasjon	Yes conforming to EN/IEC 60947-2
Driftskategori	Kategori A
[Icu] rated ultimate short-circuit breaking capacity	10 KA at 600 V AC 50/60 Hz conforming to UL 508 85 KA at 240 V AC 50/60 Hz conforming to UL 508 10 KA Icu at 660/690 V AC 50/60 Hz conforming to IEC 60947-2 35 KA Icu at 525 V AC 50/60 Hz conforming to IEC 60947-2 50 KA at 480 V AC 50/60 Hz conforming to UL 508 36 KA Icu at 500 V AC 50/60 Hz conforming to IEC 60947-2 50 KA Icu at 380/415 V AC 50/60 Hz conforming to IEC 60947-2 50 KA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2 90 KA Icu at 220/240 V AC 50/60 Hz conforming to IEC 60947-2
Performance level	N 50 kA 415 V AC
Navn på vern	TM-D
Vernteknologi	Termisk-magnetisk
Vernfunksjoner	LI
Kontrolltype	Kipp
Circuit breaker mounting mode	Fast

Komplementær

[Ui] isolasjonsspenning	800 V AC 50/60 Hz
[Uimp] Nominell impuls-spenning	8 kV
[Ics] rated service short-circuit breaking capacity	10 KA at 660/690 V AC 50/60 Hz conforming to IEC 60947-2 35 KA at 525 V AC 50/60 Hz conforming to IEC 60947-2 36 KA at 500 V AC 50/60 Hz conforming to IEC 60947-2 50 KA at 380/415 V AC 50/60 Hz conforming to IEC 60947-2 50 KA at 440 V AC 50/60 Hz conforming to IEC 60947-2 90 KA at 220/240 V AC 50/60 Hz conforming to IEC 60947-2
Mekanisk levetid	40000 sykluser
Elektrisk levetid	7500 Cycles at 690 V In 15000 Cycles at 690 V In/2 20000 Cycles at 440 V In 40000 cycles at 440 V In/2
Power losses	10,78 W

Montering	Bakplate
Tilkobling oppe	Front
Tilkobling i bunn	Front
Connection pitch	35 mm
Beskyttelsestype	L : for overload protection (thermal) I : for short-circuit protection (magnetic)
Vernstørrelse	125 A at 40 °C
Long-time pick-up adjustment type Ir (thermal protection)	Justerbar
[Ir] long-time protection pick-up adjustment range	0.7...1 x In
Long-time protection delay adjustment type tr	Fast
[tr] long-time protection delay adjustment range	120...400 S at 1.5 x In 15 s at 6 x Ir
Short-time protection pick-up adjustment type Isd	Fast
[Isd] Short-time protection pick-up adjustment range	1250 A
Short-time protection delay adjustment type tsd	Fast
Jordfeilbeskyttelse	Uten
Number of slots for electrical auxiliaries	5 slot(s)
Width (W)	105 mm
Height (H)	161 mm
Depth (D)	86 mm
Vekt	2,2 kg

Miljø

Standarder	EN/IEC 60947
Produktsertifikater	CCC EAC Marine
Overspenningskategori	Klasse II
Beskyttelsesklasse for elektrisk støt	Klasse II
Forurensninggrad	3 i samsvar med IEC 60664-1
IP-grad	IP40 conforming to IEC 60529
IK beskyttelsesklasse	IK07 conforming to IEC 62262
Omgivelsestemperatur drift	-25...70 °C
Omgivelsestemperatur for lagring	-50...85 °C
Relativ fuktighet	0...95 %
Operating altitude	0...2000 m without derating 2000 m...5000 m with derating

Packing Units

Enhetstype forpakning 1	PCE
Antall enheter forpakning 1	1
Forpakning 1 vekt	1,822 kg
Forpakning 1 høyde	12 cm
Forpakning 1 bredde	14 cm
Forpakning 1 lengde	19 cm
Enhetstype forpakning 2	S03
Antall enheter forpakning 2	7
Forpakning 2 vekt	14,694 kg
Forpakning 2 høyde	30 cm
Forpakning 2 bredde	30 cm
Forpakning 2 lengde	40 cm

Offer Sustainability

REACH-regelverk	 REACH-erklæring
EU RoHS-direktiv	I samsvar  EU RoHS-erklæring
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	 Ja
Kinas RoHS-forskrift	 Kinas RoHS-Erklæring

Contractual warranty

Garanti	18 måneder
---------	------------