

Mer om VW3A46101

- [Karakteristikk](#)
- [Download & Dokumenter](#)

Discover your Schneider-
Electric tools

**VW3A46101****Passiva filter 6A 400V 50Hz 10%THDi**

EI-nummer: 4177419

EAN: 3606480639920

[Last ned produktdatablad for VW3A46101](#)**Karakteristikk****Teknisk informasjon**

Produkt eller type komponent	Passive filter
Produktspesifikk applikasjon	Reduction of current harmonics

Komplementær

Serie kompatibilitet	Altivar Process ATV900 Altivar Process ATV600 Altivar 61 Altivar 71
[Us] matespenning	400 V +/- 10 %
Power supply frequency	50 Hz +/- 2 %

Kv antum per stasjon	1 filter per drive for variable speed drive ATV61W motor: 0,75 kW/1 hp 1 filter per drive for variable speed drive ATV61W motor: 1,5 kW/2 hp 1 filter per drive for variable speed drive ATV61W motor: 2,2 kW/3 hp 1 filter per drive for variable speed drive ATV61W motor: 3 kW 1 filter per drive for variable speed drive ATV61H motor: 0,75 kW/1 hp 1 filter per drive for variable speed drive ATV61H motor: 1,5 kW/2 hp 1 filter per drive for variable speed drive ATV61H motor: 2,2 kW/3 hp 1 filter per drive for variable speed drive ATV61H motor: 3 kW 1 filter per drive for variable speed drive ATV71H motor: 0,75 kW/1 hp 1 filter per drive for variable speed drive ATV71H motor: 1,5 kW/2 hp 1 filter per drive for variable speed drive ATV71H motor: 2,2 kW/3 hp 1 filter per drive for variable speed drive ATV71H motor: 3 kW 1 filter per drive for variable speed drive ATV71P motor: 0,75 kW/1 hp 1 filter per drive for variable speed drive ATV71P motor: 1,5 kW/2 hp 1 filter per drive for variable speed drive ATV71P motor: 2,2 kW/3 hp 1 filter per drive for variable speed drive ATV71P motor: 3 kW 1 filter per drive for variable speed drive ATV71W motor: 0,75 kW/1 hp 1 filter per drive for variable speed drive ATV71W motor: 1,5 kW/2 hp 1 filter per drive for variable speed drive ATV71W motor: 2,2 kW/3 hp 1 filter per drive for variable speed drive ATV71W motor: 3 kW 1 filter per drive for variable speed drive ATV630 veggmontering, motor: 0,75 kW/1 hp 1 filter per drive for variable speed drive ATV630 veggmontering, motor: 1,5 kW/2 hp 1 filter per drive for variable speed drive ATV630 veggmontering, motor: 2,2 kW/3 hp 1 filter per drive for variable speed drive ATV630 veggmontering, motor: 3 kW 1 filter per drive for variable speed drive ATV650 veggmontering, motor: 0,75 kW/1 hp 1 filter per drive for variable speed drive ATV650 veggmontering, motor: 1,5 kW/2 hp 1 filter per drive for variable speed drive ATV650 veggmontering, motor: 2,2 kW/3 hp 1 filter per drive for variable speed drive ATV650 veggmontering, motor: 3 kW 1 filter per drive for variable speed drive ATV930 veggmontering, motor: 0,75 kW/1 hp 1 filter per drive for variable speed drive ATV930 veggmontering, motor: 1,5 kW/2 hp 1 filter per drive for variable speed drive ATV930 veggmontering, motor: 2,2 kW/3 hp 1 filter per drive for variable speed drive ATV930 veggmontering, motor: 3 kW 1 filter per drive for variable speed drive ATV950 veggmontering, motor: 0,75 kW/1 hp 1 filter per drive for variable speed drive ATV950 veggmontering, motor: 1,5 kW/2 hp 1 filter per drive for variable speed drive ATV950 veggmontering, motor: 2,2 kW/3 hp 1 filter per drive for variable speed drive ATV950 veggmontering, motor: 3 kW
[In] merkestrøm	6 A for inngang 6,2 A for utgang
Antall faser i nettverket	3 faser

THDI

10 % for variable speed drive ATV61W motor:
0,75 kW/1 hp
10 % for variable speed drive ATV61W motor:
1,5 kW/2 hp
10 % for variable speed drive ATV61W motor:
2,2 kW/3 hp
10 % for variable speed drive ATV61W motor:
3 kW
16 % for variable speed drive ATV61H motor:
0,75 kW/1 hp
16 % for variable speed drive ATV61H motor:
1,5 kW/2 hp
16 % for variable speed drive ATV61H motor:
2,2 kW/3 hp
16 % for variable speed drive ATV61H motor:
3 kW
16 % for variable speed drive ATV71H motor:
0,75 kW/1 hp
16 % for variable speed drive ATV71H motor:
1,5 kW/2 hp
16 % for variable speed drive ATV71H motor:
2,2 kW/3 hp
16 % for variable speed drive ATV71H motor:
3 kW
16 % for variable speed drive ATV71P motor:
0,75 kW/1 hp
16 % for variable speed drive ATV71P motor:
1,5 kW/2 hp
16 % for variable speed drive ATV71P motor:
2,2 kW/3 hp
16 % for variable speed drive ATV71P motor:
3 kW
16 % for variable speed drive ATV71W motor:
0,75 kW/1 hp
16 % for variable speed drive ATV71W motor:
1,5 kW/2 hp
16 % for variable speed drive ATV71W motor:
2,2 kW/3 hp
16 % for variable speed drive ATV71W motor:
3 kW
10 % for variable speed drive ATV630 motor:
0.75 kW/1 hp
10 % for variable speed drive ATV630 motor:
1.5 kW/2 hp
10 % for variable speed drive ATV630 motor:
2.2 kW/3 hp
10 % for variable speed drive ATV630 motor:
3 kW
10 % for variable speed drive ATV650 motor:
0.75 kW/1 hp
10 % for variable speed drive ATV650 motor:
1.5 kW/2 hp
10 % for variable speed drive ATV650 motor:
2.2 kW/3 hp
10 % for variable speed drive ATV650 motor:
3 kW
10 % for variable speed drive ATV930 motor:
0.75 kW/1 hp
10 % for variable speed drive ATV930 motor:
1.5 kW/2 hp
10 % for variable speed drive ATV930 motor:
2.2 kW/3 hp
10 % for variable speed drive ATV930 motor:
3 kW
10 % for variable speed drive ATV950 motor:
0.75 kW/1 hp
10 % for variable speed drive ATV950 motor:
1.5 kW/2 hp
10 % for variable speed drive ATV950 motor:
2.2 kW/3 hp
10 % for variable speed drive ATV950 motor:
3 kW

Max strøm	1.5 x nominell strøm (varighet = 60 s)
Effektivitet	98 %
Varmetap	88 W

Cos phi	1 (150 % of line current) 0.85 (75 % of line current) 0.99 (100 % of line current)
Elektrisk tilkobling	X1-1...X2-3 klemme, tilkoblingskapasitet: 0.5 ... 10 mm ² A, B terminal, connection capacity: 2.5 mm ²
Elektrisk isolasjonsklasse	Klasse F
Vekt	12 kg
Miljø	
IP-grad	IP20 IP55 (enclosure mounting)
Vibrasjonsmotstand	2 mm peak to peak (f= 5...13.2 Hz) conforming to EN 60068-2-6 0.7 gn (f= 13.2...150 Hz) conforming to EN 60068-2-6
Relativ fuktighet	5...85 % without condensation
Omgivelsestemperatur for drift	45...60 °C (with current derating 3 % per °C) 5...45 °C (without current derating)
Omgivende lufttemperatur for oppbevaring	-25...55 °C storage in original packaging -25...65 °C during transport
Operating altitude	<= 1000 m uten strøm belastningsreduksjon > 1000...4000 m with current derating 5 % per 1000 m
Standarder	EN/IEC 61000-3-4 EN/IEC 61000-2-2 G5/4 engineering recommendation EN/IEC 61000-3-12 EN/IEC 61000-3-2 EN/IEC 61000-2-4
Packing Units	
Enhetsstype forpakning 1	PCE
Antall enheter forpakning 1	1
Forpakning 1 vekt	18,25 kg
Forpakning 1 høyde	40 cm
Forpakning 1 bredde	56 cm
Forpakning 1 lengde	59 cm
Offer Sustainability	
REACH-regelverk	REACH-erklæring
REACH fri for SVHC	Ja
EU RoHS-direktiv	Proaktivt i samsvar (Produktet inngår ikke i EUs RoHS direktivet) EU RoHS-erklæring
Fri for giftige tungmetaller	Ja
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	Ja
Kinas RoHS-forskrift	Kinas RoHS-erklæring
Contractual warranty	
Garanti	18 måneder

