




Teknisk informasjon

Serie	TeSys
Produkt eller type komponent	Kontaktor
Produktnavn	TeSys K
Kortnavn utstyr	LC1K
Applikasjon	Kontroll
Contactor application	Omsk last Motor control

Komplementær

Driftskategori	AC-1 AC-3 AC-4
Antall poler	3P
Power pole contact composition	3 NO
[Ue] merkespenning	Power circuit: 690 V AC 50/60 Hz Signalling circuit: ≤ 690 V AC 50/60 Hz
[Ie] nominell driftsstrøm	20 A (at <50 °C) at ≤ 440 V AC AC-1 for power circuit 12 A at ≤ 440 V AC AC-3 for power circuit 16 A (at <70 °C) at 690 V AC AC-1 for power circuit
Kontrollkretstype	AC at 50/60 Hz
Styrespenning	230 V AC 50/60 Hz
Motoreffekt kW	4 kW på 480 V AC 50/60 Hz AC-3 4 kW på 500...600 V AC 50/60 Hz AC-3 4 kW på 660...690 V AC 50/60 Hz AC-3 2,2 kW på 400V AC 50/60 Hz AC-4 3 kW at 220...230 V AC 50/60 Hz AC-3 5.5 kW at 380...415 V AC 50/60 Hz AC-3 5.5 kW at 440 V AC 50/60 Hz AC-3
Hjelpkontakt sammensetning	1 NC
[Uimp] Nominell impuls-spenning	8 kV
Overspenningskategori	III
[Ith] fri luft termisk strøm	20 A (at 50 °C) for power circuit 10 A (at 50 °C) for signalling circuit
Irms rated making capacity	110 A AC for signalling circuit conforming to IEC 60947 144 A AC for power circuit conforming to NF C 63-110 144 A AC for power circuit conforming to IEC 60947
Rated breaking capacity	110 A at 440 V conforming to IEC 60947 80 A at 500 V conforming to IEC 60947 70 A at 660...690 V conforming to IEC 60947
[Icw] kort-tids/kortsluttnings merkestrøm	115 A 50 °C - 1 s for power circuit 105 A 50 °C - 5 s for power circuit 100 A 50 °C - 10 s for power circuit 75 A 50 °C - 30 s for power circuit 55 A 50 °C - 1 min for power circuit 50 A 50 °C - 3 min for power circuit 80 A - 1 s for signalling circuit 90 A - 500 ms for signalling circuit 110 A - 100 ms for signalling circuit 25 A 50 °C - ≥ 15 min for power circuit

Sikringsstørrelse	25 A gG at <= 440 V for power circuit 25 A aM for power circuit 10 A gG for signalling circuit conforming to IEC 60947 10 A gG for signalling circuit conforming to VDE 0660
Gjennomsnittlig impedanse	3 mOhm - lth 20 A 50 Hz for power circuit
[Ui] isolasjonsspenning	Power circuit: 600 V conforming to UL 508 Hovedstrøm: 690 V i samsvar med IEC 60947-4-1 Signalling circuit: 690 V conforming to IEC 60947-4-1 Signalling circuit: 690 V conforming to IEC 60947-5-1 Signalling circuit: 600 V conforming to UL 508 Power circuit: 600 V conforming to CSA C22.2 No 14 Signalling circuit: 600 V conforming to CSA C22.2 No 14
Isolasjonsmotstand	> 10 MOhm for signale krets
Inrush power in VA	30 VA (at 20 °C)
Hold-in strømforbruk i VA	4.5 VA (at 20 °C)
Varmeavgivelse	1.3 W
Control circuit voltage limits	Operational: 0.8...1.15 U _c (at <50 °C) Drop-out: 0.2...0.75 U _c (at <50 °C)
Tilkoblingsklemmer	Screw clamp terminals 1 cable(s) 1.5...4 mm ² solid Screw clamp terminals 1 cable(s) 0.75...4 mm ² flexible without cable end Screw clamp terminals 1 cable(s) 0.34...2.5 mm ² flexible with cable end Screw clamp terminals 2 cable(s) 1.5...4 mm ² solid Screw clamp terminals 2 cable(s) 0.75...4 mm ² flexible without cable end Screw clamp terminals 2 cable(s) 0.34...1.5 mm ² flexible with cable end
Bruksområde	3600 cyc/h
Auxiliary contacts type	Type instantaneous 1 NC
Signale krets frekvens	<= 400 Hz
Minimum brytestrøm	5 mA for signale krets
Minimum switching voltage	17 V for signale krets
Montering	Skinne Plate
Tiltrekningsmoment	1.3 N.M - on screw clamp terminals - with screwdriver Philips No 2 1.3 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm
Driftstid	10...20 ms coil de-energisation and NO opening 10...20 ms coil energisation and NO closing
Sikkerhet pålitelighet nivå	B10d = 1369863 sykluser kontaktor med nominell last i samsvar med EN/ISO 13849-1 B10d = 20000000 sykluser kontaktor med mekanisk belastning i samsvar med EN/ISO 13849-1
Non overlapping avstand	0.5 mm
Mekanisk levetid	10 Mcycles
Elektrisk levetid	0.3 Mcycles 20 A AC-1 at U _e <= 440 V 1.3 Mcycles 12 A AC-3 at U _e <= 440 V
Mekanisk robusthet	Shocks contactor closed, on X axis: 10 Gn for 11 ms conforming to IEC 60068-2-27 Shocks contactor closed, on Y axis: 15 Gn for 11 ms conforming to IEC 60068-2-27 Shocks contactor closed, on Z axis: 15 Gn for 11 ms conforming to IEC 60068-2-27 Shocks contactor opened, on X axis: 6 Gn for 11 ms conforming to IEC 60068-2-27 Shocks contactor opened, on Y axis: 10 Gn for 11 ms conforming to IEC 60068-2-27 Shocks contactor opened, on Z axis: 10 Gn for 11 ms conforming to IEC 60068-2-27 Vibrations contactor closed: 4 Gn, 5...300 Hz conforming to IEC 60068-2-6 Vibrations contactor opened: 2 Gn, 5...300 Hz conforming to IEC 60068-2-6
Høyde	58 mm
Bredde	45 mm
Dybde	57 mm
Vekt	0,18 kg

Miljø

Standarder	BS 5424 IEC 60947 NF C 63-110 VDE 0660
Produktsertifikater	CSA UL
IP-grad	IP2x conforming to VDE 0106
Protective treatment	TC conforming to IEC 60068 TC conforming to DIN 50016
Omgivelsestemperatur for lagring	-50...80 °C
Operating altitude	2000 m without derating
Flammehemming	V1 i samsvar med UL 94 Requirement 2 conforming to NF F 16-101 Requirement 2 conforming to NF F 16-102

Packing Units

Enhetstype forpakning 1	PCE
Antall enheter forpakning 1	1
Forpakning 1 vekt	178,9 g
Forpakning 1 høyde	4,7 cm
Forpakning 1 bredde	6 cm
Forpakning 1 lengde	6,5 cm
Enhetstype forpakning 2	S02
Antall enheter forpakning 2	50
Forpakning 2 vekt	9,205 kg
Forpakning 2 høyde	15 cm
Forpakning 2 bredde	30 cm
Forpakning 2 lengde	40 cm

Offer Sustainability

REACH-regelverk	 REACH-erklæring
REACH fri for SVHC	Ja
EU RoHS-direktiv	I samsvar  EU RoHS-erklæring
Fri for giftige tungmetaller	Ja
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	 Ja
Kinas RoHS-forskrift	 Kinas RoHS-Erklæring
WEEE	Innen EU må produktet avhendes i henhold til bestemte regler for avfallshåndtering og aldri kastes som husholdningsavfall.

Contractual warranty

Garanti	18 months
---------	-----------