



Overview

Presentasjon	Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
Leveringstid	Usually in Stock

General

Inkludert utstyr	CD with software Documentation CD Installation guide Rack mounting support rails Smart UPS signalling RS-232 cable USB cable Warranty card
Number of tare power	17 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Physical

Kabellengde	2,44 m
Number of rack unit	1U
Farge	Black
Dybde	66,5 cm
Høyde	4,4 cm
Montasjeplassering	Front
Mounting preference	Lower
Vekt	24,09 kg
Monteringsmetode	Rack-mounted
Two post mountable	0
USB compatible	No
Bredde	43,2 cm

Input

Network frequency	50/60 Hz
Plug standard	IEC 320 C14
Input voltage limits	174...286 V
Forsyningsspenning	230 V

Output

Merkeeffekt i W	1000 W
Maximum configurable power in W	1000 W
Harmonic distortion	Mindre enn 5 %
Output voltage	220 V 240 V
UPS type	Line interactive
Wave type	Sine wave
Nb of power socket outlets	4 IEC 320 C13 2 IEC Jumpers
Output voltage	230 V
Maximum configurable power in VA	1500 VA
Merkeeffekt VA	1500 VA

Conformance

Produktsertifikater	CE EAC RCM VDE
Standarder	EN/IEC 62040-1 EN/IEC 62040-2

Environmental

Omgivelsestemperatur drift	0...40 °C
Relativ fuktighet	0...95 %
Driftshøyde	0...10000 ft
Omgivelsestemperatur for lagring	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0,00...15240,00 m
Akkustikknivå	46 dBA
Varmeavgivelse	116 Btu/t

Batteries & Runtime

Batteritype	Bly-syre batteri
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	4 t
Number of battery replacement quantity	1
Liquid value	0
Battery charger power	73 W rated
Battery power in VAH	293 VAh runtime
Batterilevetid	3...5 år
Extended runtime	0

Communications & Management

Ledige plasser	1
Control panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

Surge Protection and Filtering

Surge energy rate	540 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Packing Units

Forpakning 1 vekt	29,09 kg
Forpakning 1 høyde	20 cm
Forpakning 1 bredde	57,5 cm
Forpakning 1 lengde	79,4 cm
Antall enheter forpakning 3	10

Offer Sustainability

Produktets miljøstatus	Green Premium miljømerket produkt
REACH-regelverk	 REACH-erklæring
EU RoHS-direktiv	I samsvar  EU RoHS-erklæring
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	 Ja
Miljøinformasjon	 Produktmiljøprofil
Produktets livssyklus	 Informasjon Om Levetidsslutt
WEEE	Innen EU må produktet avhendes i henhold til bestemte regler for avfallshåndtering og aldri kastes som husholdningsavfall.
Optimalisert energieffektivitet	Energieffektivt produkt
Take-back	Take-back program available

Contractual warranty

Garanti	3 years repair or replace (excluding battery) and 2 years for battery
---------	---