



Overview

Presentasjon	Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
Leveringstid	Usually Ships within 4 Weeks

General

Inkludert utstyr	CD with software Documentation CD Installation guide Rack mounting hardware Rack mounting support rails Smart UPS signalling RS-232 cable User manual Web/SNMP management card
Number of tare power	75 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Physical

Number of rack unit	5U
Farge	Black
Dybde	66 cm
Høyde	22,2 cm
Montasjeplassering	Front
Mounting preference	No preference
Vekt	97,73 kg
Monteringsmetode	Rack-mounted
Two post mountable	0
USB compatible	No
Bredde	48,3 cm

Input

Network frequency	50/60 Hz +/- 3 Hz auto-sensing
Number of input connectors	1 hard wire 3-wire
Input voltage limits	151...302 V Justrbar 160...286 V
Forsyningsspenning	230 V

Output

Merkeeffekt i W	4000 W
Maximum configurable power in W	4000 W
Harmonic distortion	Mindre enn 5 % ved full last
Output frequency	47...53 Hz for 50 Hz nominal sync to mains
Output voltage	220 V 240 V
Crest faktor	3:1
UPS type	Line interactive
Wave type	Sine wave
Nb of power socket outlets	8 IEC 320 C13 4 IEC Jumpers 2 IEC 320 C19
Effektivitet	96 % (fullastet)
Output voltage	230 V
Maximum configurable power in VA	5000 VA
Merkeeffekt VA	5000 VA
Transfer time	2 ms typical : 4 ms maximum

Conformance

Produktsertifikater	C-Tick CE GOST VDE
Merking	GS Mark
Standarder	EN 50091-1 EN 50091-2

Environmental

Omgivelsestemperatur drift	0...40 °C
Relativ fuktighet	0...95 %
Driftshøyde	0...10000 ft
Omgivelsestemperatur for lagring	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0,00...15240,00 m
Akkustikknivå	53 dBA
Varmeavgivelse	430 Btu/t

Batteries & Runtime

Batteritype	VRLA
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 t
Number of battery replacement quantity	2
Tilleggsinformasjon	Configurable for 220 : 230 or 240 nominal output voltage
Liquid value	0
Battery charger power	542 W rated
Battery power in VAH	1632 VAh runtime
Batterilevetid	3...5 år
Extended runtime	0

Communications & Management

Ledige plasser	0
Preinstalled device	Network management card
Control panel	LED status display with on line : on battery : replace battery and overload indicators
Alarm	Audible and visible alarms : configurable delays

Surge Protection and Filtering

Surge energy rate	480 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Packing Units

Forpakning 1 vekt	106,82 kg
Forpakning 1 høyde	63,5 cm
Forpakning 1 bredde	61 cm
Forpakning 1 lengde	76,2 cm
Antall enheter forpakning 2	1
Antall enheter forpakning 3	4

Offer Sustainability

Produktets miljøstatus	Green Premium miljømerket produkt
REACH-regelverk	 REACH-erklæring
EU RoHS-direktiv	I samsvar  EU RoHS-erklæring
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	 Ja
Miljøinformasjon	 Produktmiljøprofil
Produktets livssyklus	 Informasjon Om Levetidsslutt
WEEE	Innen EU må produktet avhendes i henhold til bestemte regler for avfallshåndtering og aldri kastes som husholdningsavfall.
Optimalisert energieffektivitet	Energieffektivt produkt
Take-back	Take-back program available

Contractual warranty

Garanti	2 years repair or replace
---------	---------------------------