



Overview

Leveringstid	Usually in Stock
--------------	------------------

General

Inkludert utstyr	Basic UPS signalling RS-232 cable CD with software 1 x DC cable Rack mounting brackets User manual USB cable
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
UPS size	WS

Physical

Number of rack unit	4U
Farge	Black
Dybde	61,5 cm
Høyde	17,3 cm
Vekt	69 kg
Monteringsmetode	Rack-mounted with kit
USB compatible	Yes
Bredde	43,8 cm

Input

Network frequency	40...70 Hz
Number of input connectors	1 hard wire 3-wire
Input voltage limits	110...300 V half load 176...300 V fullastet
Inputvolt_other	220 V 240 V
Forsyningsspenning	230 V

Output

Merkeeffekt i W	10000 W
Maximum configurable power in W	10000 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Output voltage	220 V 240 V
Crest faktor	3:1
UPS type	Double conversion online
Wave type	Sine wave
Output connector type	Hard wire 3-wire (H N + E) 1
Bypass type	Internal bypass (automatic and manual)
Curve equation	Efficiency
Curve load maximum	100 %
Curve X-axis maximum	100 %
Curve test cond ID	Curve fit to measured efficiency data. All measurements taken in normal operating mode, at typical environmental conditions, with nominal electrical input and balanced resistive load (PF = 1.0) output.
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Effektivitet	94 % (full load)
Graph display	2
Half load runtime	00:07:00 5000 W
Output voltage	230 V
Maximum configurable power in VA	10000 VA
Merkeeffekt VA	10000 VA

Conformance

Produktsertifikater	CE
Standarder	IEC 62040-1-1 IEC 62040-1-2

Environmental

Omgivelsestemperatur drift	0...40 °C
Relativ fuktighet	0...95 % non-condensing
Driftshøyde	0...3000 m
Omgivelsestemperatur for lagring	-15...60 °C
Storage Relative Humidity	0...95 % Ikke-kondenserende
Storage altitude	0...15000 m
Akkustikknivå	58 dB
Show note OP temperature	No
IP-grad	IP20

Batteries & Runtime

Batteritype	Bly-syre batteri
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 t
Tilleggsinformasjon	Configurable for 220 : 230 or 240 nominal output voltage
Battery charger power	531 W rated

Communications & Management

Ledige plasser	1
Control panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Emergency power off	Yes

Surge Protection and Filtering

Surge energy rate	600 J
-------------------	-------

Packing Units

Forpakning 1 vekt	1,670 kg
Forpakning 1 høyde	24,000 cm
Forpakning 1 bredde	56,500 cm
Forpakning 1 lengde	70,000 cm

Contractual warranty

Garanti	2 years repair or replace
---------	---------------------------