



Overview

Presentasjon	For small to medium businesses, Easy UPS 1 Ph On-Line provides essential power protection for unstable power conditions, ensuring consistent and reliable connectivity at the most critical moments.
Leveringstid	Usually in Stock

General

Inkludert utstyr	Basic UPS signalling RS-232 cable CD with software User manual USB cable
Max runtime	4 min
Number of tare power	41 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Physical

Kabellengde	1,50 m
Farge	Black
Dybde	28,8 cm
Høyde	22,3 cm
Vekt	9,3 kg
Monteringsmetode	Not rack-mountable
USB compatible	Yes
Bredde	14,5 cm

Input

Network frequency	40...70 Hz
Plug standard	IEC 60320 C14
Input voltage limits	110...285 V half load 160...280 V fullastet
Inputvolt_other	220 V 240 V
Antall kabler	1
Forsyningsspenning	230 V

Output

Merkeeffekt i W	800 W
Maximum configurable power in W	800 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Output voltage	220 V 240 V
Crest faktor	3:1
UPS type	Double conversion online
Wave type	Sine wave
Nb of power socket outlets	3 IEC 60320 C13
Bypass type	Internal bypass (automatic and manual)
Effektivitet	88 % (fullastet)
Output voltage	230 V
Maximum configurable power in VA	1000 VA
Merkeeffekt VA	1000 VA

Conformance

Produktsertifikater	CE
Standarder	IEC 62040-1 safety IEC 62040-2 EMC/EMI

Environmental

Omgivelsestemperatur drift	0...40 °C
Relativ fuktighet	0...95 % non-condensing
Driftshøyde	0...3000 m
Omgivelsestemperatur for lagring	-20...50 °C
Storage Relative Humidity	0...95 % Ikke-kondenserende
Storage altitude	0...15000 m
Akkustikknivå	50 dB
IP-grad	IP20

Batteries & Runtime

Batteritype	Bly-syre batteri
Number of battery filled slots	1
Number of battery free slots	0
Battery recharge time	4 t
Tilleggsinformasjon	Configurable for 220 : 230 or 240 nominal output voltage
Liquid value	0
Batterispenningen	24 V
Battery curve	D
Battery charger power	38 W rated
Battery power in VAh	152 VAh runtime

Communications & Management

Ledige plasser	1
Control panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rate	600 J
-------------------	-------

Packing Units

Enhetstype forpakning 1	PCE
Antall enheter forpakning 1	1
Forpakning 1 vekt	10,6 kg
Forpakning 1 høyde	33 cm
Forpakning 1 bredde	23,5 cm
Forpakning 1 lengde	36,5 cm

Contractual warranty

Garanti	2 years repair or replace
---------	---------------------------